



Absolutely The Best Crane Mats In The World.

This document is stored and available in the Raptor Tech Technical Document Repository.

To help our customers understand certain critical data points that factor into purchasing crane mats, Raptor Tech maintains a repository of technical documents with data from all major crane manufacturers.

You can visit Raptor Tech's repository to get crane specifications and technical details for crane models in addition to this model at:

<https://library.steelcranemats.com>

Thank You for Visiting the [SteelCraneMats.com](https://library.steelcranemats.com) Technical Specifications Document Repository.

Mobile Crane Grue mobile

LTM 1350-6.1

Technical Data
Caractéristiques techniques



LIEBHERR

Table of content


Tables des matières

Technical Data · Caractéristiques technique

Dimensions · Encombrement	A
Boom/jib combinations · Configurations de flèche	B
Weights · Poids	C
T	D
TY	E
TF	F
TYVEF	G
TYF	H
TN	I
TYVEN	J
Equipment · Equipement	K
Description of symbols · Explication des symboles	L
Remarks · Remarques	M

Dimensions Encombrement

A



US2271.05

R₁ = All-wheel steering · Direction toutes roues

Dimensions · Encombrement											
	A	A 6"	B	C	D	E	F	G	H	I	K
445/95 R 25 (16.00 R 25)	13'1"	12'9"	9'10"	8'4"	12'4"	6'7"	9°	14°	1'4"	1'2"	15°
525/80 R 25 (20.5 R 25)	13'1"	12'9"	10'2"	8'5"	12'4"	6'7"	9°	14°	1'4"	1'2"	15°

* lowered · abaissé

Boom/jib combinations Configurations de flèche


B

T Telescopic boom · Flèche télescopique

Y Y-shaped guying system · Haubanage Y

F Fixed lattice jib · Fléchette treillis fixe


H Auxiliary jib · Fléchette auxiliaire
see supplement to technical data sheet: · voir supplément au descriptif: www.liebherr.com



T




D



TY



E



TFH



F

S2816

Boom/jib combinations Configurations de flèche

VE Telescopic boom extension 11.5 ft + Eccentric
Rallonge de flèche télescopique 11.5 ft + Axe excentrique

N Luffing fly jib · Fléchette treillis à volée variable



TYVEFH

G

TYF

H

TNH

I


TYVENH

J



S2816

Boom/jib combinations - Luffing fly jib Configurations de flèche - Fléchette à volée variable

B




S2435





S2583

Boom/jib combinations - Fixed fly jib **Configurations de flèche - Fléchette fixe**



B



US2434



S2584



US2436

Weights Poids



Axle
Essieu

lbs 26400 26400 26400 26400 26400 26400 158400



Load kips
Forces de levage kips

No. of sheaves
Poulies

No. of lines
Brins

Weight lbs
Poids lbs

463

12

24 (20)

7500

343.3

7

14

4850

275.6

5

11

3630

176.4

3

7

3200 / 6615*

79.8

1

3

2200

27.1

—

1

1320

* only necessary for operation with 39 ft luffing fly jib · nécessaire uniquement en cas de fonctionnement avec la fléchette à volée variable de 39 ft

Working speeds Vitesses



445/95 R 25 (16.00 R 25)
525/80 R 25 (20.5 R 25)

mph min.

1.5

mph max.

50

%

50.9 %



12 / R2



Drive
Mécanismes

infinitely variable
en continu

Rope diameter / length
Diamètre / Longueur du câble

Max. single line pull
Effort au brin maxi.



0 – 446 ft/min single line
ft/min au brin simple

0.9" / 1148 ft

27420 lbs



0 – 459 ft/min single line
ft/min au brin simple

0.9" / 2067 ft

27420 lbs



0 – 1.1 rpm




approx. 75 seconds to reach 84° boom angle
env. 75 s jusqu'à 84°



approx. 533 seconds for boom extension from 49 ft – 230 ft
env. 533 s pour passer de 49 ft – 230 ft

Lifting capacities Forces de levage

T




ft	49 ft	66 ft	82 ft	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	ft
18	323.7	319												18
20	308.8	309												20
22	288.4	289.6	272.2	245.5	185.1									22
24	269.8	271.5	260.2	240.7	185									24
26	253	254.8	247	233.9	197.6									26
28	238.7	240.5	235.7	223.4	197.4	151.3	121.3	95.3						28
30	225.3	227.1	224.6	212.9	195.4	156.1	119.5	94.9						30
32	213.5	215.2	213.4	203.9	192.7	156.1	116.4	93.9	74.8					32
34	202.7	204.3	202.7	195.7	187.7	155.5	113.1	92.4	74.5					34
36	192.4	194.1	192.5	187.9	181.1	154.5	109.7	90.6	73.9					36
38	182.4	185.2	183.6	180.8	174.6	151.9	106.1	88.4	73.1	60.4				38
40	163.8	176.8	175.2	173.7	168.4	149	102.7	86.1	72.1	60				40
42		169.3	167.4	166.4	162.6	145.8	99.4	83.8	70.6	59.5	48.3			42
44		162.2	160.3	159.4	157.1	142	96.1	81.5	69.1	58.8	48.1	40.6	39	44
46		155.4	153.5	152.6	151.8	137.9	92.9	79.3	67.5	57.9	47.9	40.3	38.9	46
48		149.4	147.7	146.8	146.8	133.9	90	77.2	66	56.8	47.5	39.9	38.6	48
50		143.4	142	141.1	141.8	129.8	87.2	75.1	64.4	55.7	47	39.5	38.4	50
55			128.7	127.9	129.4	120.6	80.4	70.2	60.6	53	45.7	38.2	37.4	55
60			116.6	116.7	117.2	112.4	74.2	65.5	57	50.2	44.1	36.7	36.2	60
65			106.2	107.8	106.7	105	69.9	60.9	53.7	47.5	42.3	35.2	34.7	65
70				99.2	97.9	98.5	66.1	56.9	50.6	45.1	40.4	33.6	33.2	70
75				91.4	90.1	91.8	62.8	53.1	47.6	42.8	38.6	32.2	31.8	75
80				83.7	83.1	85.1	59.9	49.7	44.7	40.5	36.7	30.8	30.5	80
85				74.4	76.9	79	57	46.6	42.2	38.3	35.1	29.4	29.1	85
90					71.7	73.6	54.6	43.9	39.7	36.3	33.4	28.2	27.9	90
95					67.1	68.8	52.3	41.2	37.5	34.4	31.8	26.9	26.7	95
100						64.5	50.2	39	35.4	32.5	30.3	25.7	25.5	100
105						60.5	48.3	37.4	33.3	30.8	28.8	24.5	24.3	105
110						56.5	46.6	36	31.4	29.2	27.4	23.4	23.2	110
115						50.2	45	34.6	29.8	27.7	26.1	22.3	22	115
120							43.5	33.3	28.4	26.2	24.9	21.2	20.9	120
125							42.2	32	27.1	24.9	23.8	20.3	19.9	125
130							41.1	30.8	26	23.9	22.6	19.4	19	130
135								29.8	25	22.8	21.5	18.6	18	135
140								28.8	24	21.8	20.5	17.7	17.1	140
145								27.8	23.1	20.9	19.5	16.9	16.2	145
150								27	22.3	20.1	18.6	16.2	15.4	150
155									21.6	19.2	17.7	15.5	14.6	155
160									20.9	18.4	16.9	14.8	13.9	160
165									20.3	17.7	16	14.2	13.1	165
170										17	15.2	13.6	12.5	170
175										16.4	14.5	13.1	11.8	175
180										15.8	13.8	12.5	11.2	180
185										14.7	13.2	12	10.6	185
190											12.5	11.5	10	190
195											11.9	11.1	9.5	195
200												10.6	9	200
205												10.1	8.5	205
210												9.7	8.1	210
215													7.7	215

D

t_180_50301_00_000

Lifting capacities Forces de levage

T



	49 ft	66 ft	82 ft	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	
9	343.3													9
10	343.3													10
11	343.3	343.3												11
12	343.3	343.3												12
13	343.3	343.3	342											13
14	343.3	343.3	341.7	252.5										14
15	343.3	343.2	338.7	252.5										15
16	343.3	342.4	328	252.5										16
17	342.2	337	318.3	252.5										17
18	340.3	328.5	309.2	252.5	205									18
20	333.9	311.6	291.3	251.8	204.7									20
22	314.2	295.2	275	247.3	202.8	156.1								22
24	296.1	279.6	260.2	241.3	201	156.1								24
26	279.6	264.5	247	233.9	199.3	156.1	122.9							26
28	264	251.7	236	223.4	197.4	156.1	121.4	95.3						28
30	248.5	239.6	225.6	212.9	195.4	156.1	119.5	94.9						30
32	232.7	228.8	216	203.9	192.7	156.1	116.4	93.9	74.8					32
34	218.3	217.3	206.9	195.7	187.7	155.5	113.1	92.4	74.5					34
36	204.9	205.5	197.9	187.9	181.1	154.5	109.7	90.6	73.9					36
38	187.9	194.4	190.1	180.9	174.6	151.9	106.1	88.4	73.1	60.4				38
40	164.2	183.9	182.1	174.1	168.4	149	102.7	86.1	72.1	60				40
42		174.8	173.7	167.5	162.6	145.8	99.4	83.8	70.6	59.5	48.3			42
44		166.8	165.4	161.3	157.1	142	96.1	81.5	69.1	58.8	48.1	40.6	39	44
46		159.3	157.3	155.3	151.8	137.9	92.9	79.3	67.5	57.9	47.9	40.3	38.9	46
48		152.3	150.6	148.9	146.9	133.9	90	77.2	66	56.8	47.5	39.9	38.6	48
50		145.3	144	142.5	142	129.8	87.2	75.1	64.4	55.7	47	39.5	38.4	50
55			129.2	128.3	129.5	120.6	80.4	70.2	60.6	53	45.7	38.2	37.4	55
60			116.6	116.7	117.2	112.4	74.2	65.5	57	50.2	44.1	36.7	36.2	60
65			106.2	107.8	106.7	105	69.9	60.9	53.7	47.5	42.3	35.2	34.7	65
70				99.2	97.9	98.5	66.1	56.9	50.6	45.1	40.4	33.6	33.2	70
75				91.4	90.1	91.8	62.8	53.1	47.6	42.8	38.6	32.2	31.8	75
80				83.7	83.1	85.1	59.9	49.7	44.7	40.5	36.7	30.8	30.5	80
85				74.4	76.9	79	57	46.6	42.2	38.3	35.1	29.4	29.1	85
90					71.7	73.6	54.6	43.9	39.7	36.3	33.4	28.2	27.9	90
95					67.1	68.8	52.3	41.2	37.5	34.4	31.8	26.9	26.7	95
100						64.5	50.2	39	35.4	32.5	30.3	25.7	25.5	100
105						60.5	48.3	37.4	33.3	30.8	28.8	24.5	24.3	105
110						56.5	46.6	36	31.4	29.2	27.4	23.4	23.2	110
115						50.2	45	34.6	29.8	27.7	26.1	22.3	22	115
120							43.5	33.3	28.4	26.2	24.9	21.2	20.9	120
125							42.2	32	27.1	24.9	23.8	20.3	19.9	125
130							41.1	30.8	26	23.9	22.6	19.4	19	130
135								29.8	25	22.8	21.5	18.6	18	135
140								28.8	24	21.8	20.5	17.7	17.1	140
145								27.8	23.1	20.9	19.5	16.9	16.2	145
150								27	22.3	20.1	18.6	16.2	15.4	150
155									21.6	19.2	17.7	15.5	14.6	155
160									20.9	18.4	16.9	14.8	13.9	160
165									20.3	17.7	16	14.2	13.1	165
170										17	15.2	13.6	12.5	170
175										16.4	14.5	13.1	11.8	175
180										15.8	13.8	12.5	11.2	180
185										14.7	13.2	12	10.6	185
190											12.5	11.5	10	190
195											11.9	11.1	9.5	195
200												10.6	9	200
205												10.1	8.5	205
210												9.7	8.1	210
215													7.7	215

t_180_50201_00_000

Lifting capacities Forces de levage

T



	49 ft		66 ft	82 ft	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	
	*														
9		343.3													9
10	742	343.3													10
11	554	343.3	343.3												11
12	454.8	343.3	343.3												12
13	438.6	343.3	343.3	342											13
14	417.7	343.3	343.3	341.7	252.5										14
15	397.4	343.1	343	338.7	252.5										15
16	381.3	342.2	341.6	328	252.5										16
17	367.8	334.7	334.3	318.3	252.5										17
18	356.1	322.7	323	309.2	252.5	205									18
20	332.1	299.3	300.8	291.3	251.8	204.7									20
22	304.4	279.5	281.1	275	247.3	202.8	156.1								22
24	279.3	261.4	263.2	259.5	241.3	201	156.1								24
26	256.7	245.1	246.9	244.9	233.9	199.3	156.1	122.9							26
28	238.3	231.2	233	231.3	223.4	197.4	156.1	121.4	95.3						28
30	221.4	218	219.8	218.2	212.7	195.4	156.1	119.5	94.9						30
32	207.1	206.1	208	206	202.8	192.7	156.1	116.4	93.9	74.8					32
34	194.2	194.2	196.1	194.2	192.4	187.7	155.5	113.1	92.4	74.5					34
36	182.2	182.2	184.2	182.4	181.6	181	154.5	109.7	90.6	73.9					36
38	172.2	172.2	174.1	172.4	173	172.6	151.9	106.1	88.4	73.1	60.4				38
40	155.6	155.6	164.6	162.9	164.5	164	149	102.7	86.1	72.1	60				40
42			156.3	154.5	156.4	155.4	145.8	99.4	83.8	70.6	59.5	48.3			42
44			148.7	147.6	148.8	147.6	142	96.1	81.5	69.1	58.8	48.1	40.6	39	44
46			141.3	141.5	141.5	140.3	137.9	92.9	79.3	67.5	57.9	47.9	40.3	38.9	46
48			135.3	135.6	135.4	134.2	133.3	90	77.2	66	56.8	47.5	39.9	38.6	48
50			129.3	129.7	129.4	128.2	128.6	87.2	75.1	64.4	55.7	47	39.5	38.4	50
55				116.5	116	114.7	116.9	80.4	70.2	60.6	53	45.7	38.2	37.4	55
60				105.2	104.7	103.6	105.5	74.2	65.5	57	50.2	44.1	36.7	36.2	60
65				95.7	95.3	95.6	96	69.9	60.9	53.7	47.5	42.3	35.2	34.7	65
70					87.3	88.8	87.9	66.1	56.9	50.6	45.1	40.4	33.6	33.2	70
75					79.8	82	80.5	62.8	53.1	47.6	42.8	38.6	32.2	31.8	75
80					73.4	75.3	73.6	59.9	49.7	44.7	40.5	36.7	30.8	30.5	80
85					69.2	69.1	67.4	57	46.6	42.2	38.3	35.1	29.4	29.1	85
90						63.9	62.2	54.6	43.9	39.7	36.3	33.4	28.2	27.9	90
95						59.2	57.5	52.3	41.2	37.5	34.4	31.8	26.9	26.7	95
100							53.2	50.2	39	35.4	32.5	30.3	25.7	25.5	100
105							49.4	48.3	37.4	33.3	30.8	28.8	24.5	24.3	105
110							46	46.5	36	31.4	29.2	27.4	23.4	23.2	110
115							43	44.2	34.6	29.8	27.7	26.1	22.3	22	115
120								41.8	33.3	28.4	26.2	24.9	21.2	20.9	120
125								39.1	32	27.1	24.9	23.8	20.3	19.9	125
130								36.8	30.8	26	23.9	22.6	19.4	19	130
135									29.8	25	22.8	21.5	18.6	18	135
140									28.8	24	21.8	20.5	17.7	17.1	140
145									27.8	23.1	20.9	19.5	16.9	16.2	145
150									27	22.3	20.1	18.6	16.2	15.4	150
155										21.6	19.2	17.7	15.5	14.6	155
160										20.9	18.4	16.9	14.8	13.9	160
165										20.3	17.7	16	14.2	13.1	165
170											17	15.2	13.6	12.5	170
175											16.4	14.5	13.1	11.8	175
180											15.8	13.8	12.5	11.2	180
185											14.7	13.2	12	10.6	185
190												12.5	11.5	10	190
195												11.9	11.1	9.5	195
200													10.6	9	200
205													10.1	8.5	205
210													9.7	8.1	210
215														7.7	215


* over rear - en arrière

t_180_50005_00_000 / 50305_00_000

Lifting heights Hauteurs de levage

T

D



Lifting capacities Forces de levage

TY

     85%											
 ft	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	 ft
26	236.9	217.6									26
28	227	212.9	189.3								28
30	217.3	207.4	186.1								30
32	207.7	199.7	184.2	166.8							32
34	199.5	192.1	179.7	165.3							34
36	192.4	184.4	173.7	163.1							36
38	183.8	177.9	168.6	159.2	144.7						38
40	175.4	171.4	163.4	155	143.2						40
42	167.3	165.2	157.7	150.5	140	124.5	106.1	93.9		80.2	42
44	159.9	159.3	152.9	146	136.4	123.8	105.8	93.6	82.7	80	44
46	152.9	153.5	148.5	141.5	132.8	122.9	105.4	93.1	81.8	79.6	46
48	146.8	147.7	144.2	137.8	129.6	120.5	104.7	92.3	80.8	79.2	48
50	140.8	141.9	139.9	134.1	126.3	118.2	104	91.5	79.7	78.7	50
55	127.2	128.7	129.1	125	118.4	111.6	101.5	88.6	76.9	77.2	55
60	115.5	117.1	118.5	116.2	111	104.5	98	84.9	73.9	75.2	60
65	105.6	107.1	108.7	107.8	104.4	98.3	92.9	81.6	70.9	72.7	65
70	96.5	98.3	100	99.9	97.8	92.9	87.8	78.4	68.3	70.1	70
75	88.3	90.3	91.9	92.2	91.4	87.6	83.1	75.4	65.9	67.6	75
80	79.6	82.9	84.4	84.8	85	82.5	78.7	72.6	63.7	65.3	80
85	68.2	76.2	77.9	78.2	78.5	77.6	74.3	69.4	61.6	63.1	85
90		70.5	72.2	72.6	72.9	72.5	70.4	65.7	59.7	60.9	90
95		63.8	67.1	67.5	67.8	67.4	66.6	62.2	57.7	58.9	95
100			62.4	62.8	63.1	62.7	62.6	59	55.8	56.8	100
105			58.1	58.5	58.8	58.4	58.3	56	53.9	54.5	105
110			53	54.7	55.1	54.7	54.6	53	51.9	52	110
115			45.8	51.2	51.7	51.2	51.1	49.8	49.5	49.4	115
120				47.6	48.4	48	47.8	46.7	46.8	46.7	120
125				43.6	45.4	45.1	44.8	43.7	44	44	125
130				37.8	42.6	42.3	42.1	40.9	41.4	41.4	130
135					39.7	39.7	39.6	38.3	38.9	38.9	135
140					36.1	37.3	37.1	35.8	36.4	36.5	140
145					31.4	34.8	34.9	33.5	34.1	34.3	145
150					25.7	32.5	32.7	31.3	32	32	150
155						29.2	30.5	29.3	29.9	30	155
160						25.2	28.5	27.4	28	28	160
165						20.5	26.5	25.5	26.1	26.2	165
170							23.6	23.8	24.3	24.4	170
175							20.3	22.2	22.8	22.8	175
180							16.4	20.3	21.3	21.3	180
185								17.9	19.8	19.8	185
190								15.2	18.2	18.4	190
195								11.9	15.9	16.4	195
200									13.4	14.1	200
205										11.5	205
210										8.6	210

TAB 180_60101_00_000

Lifting capacities Forces de levage

TY




85%

E

	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	
15	256.7										15
16	259.8										16
17	261.2										17
18	261.7										18
20	262	231.6									20
22	259.1	234.4									22
24	251.8	232	198.9								24
26	240.4	224.8	198.8								26
28	228.6	216.1	196.8	167.4							28
30	217.1	207.4	193.9	167.8	145.1						30
32	206.4	199.7	189	167.8	145.3						32
34	196.5	192.1	182.8	166.7	145.4						34
36	187.1	184.4	175.8	164.7	145.4						36
38	177.6	176.7	169.5	159.9	144.7	124.6	106.3				38
40	168.2	168.8	163.4	155	143.2	124.6	106.3	94.2		79.8	40
42	159.1	160.3	157.7	150.5	140	124.5	106.1	93.9	82.8	80.2	42
44	150.8	152.2	151.6	146	136.4	123.8	105.8	93.6	82.7	80	44
46	143	144.4	145.4	141.5	132.8	122.9	105.4	93.1	81.8	79.6	46
48	136.5	138.1	139.2	136.6	129.6	120.5	104.7	92.3	80.8	79.2	48
50	130.1	131.7	133	131.7	126.3	118.2	104	91.5	79.7	78.7	50
55	115.7	117.5	119	119.3	117.3	111.4	101.5	88.6	76.9	77.2	55
60	103.6	105.3	106.9	107.2	107.3	103.6	97.8	84.9	73.9	75.2	60
65	93.5	95.2	96.8	97.1	97.3	94.7	91.4	81.6	70.9	72.7	65
70	84.7	86.6	88.2	88.5	88.8	86.7	84.1	78.1	68.3	70.1	70
75	77	79.1	80.6	81	81.3	79.6	77.2	73.4	65.9	67.5	75
80	70.1	72.3	73.9	74.3	74.6	73.2	71.1	67.7	63.5	64.8	80
85	63.6	66.1	68	68.3	68.7	67.5	65.6	62.4	60.8	61.6	85
90		60.6	62.5	62.9	63.3	62.4	60.7	57.7	57	57.1	90
95		55.4	57.4	57.9	58.3	57.7	56.2	53.3	53	52.9	95
100			52.8	53.3	53.6	53.2	52.1	49.3	49.1	49	100
105			48.5	49	49.4	49	48.3	45.7	45.5	45.4	105
110			44.7	45.2	45.7	45.2	44.8	42.4	42.3	42.2	110
115			41.1	41.7	42.3	41.8	41.6	39.3	39.3	39.3	115
120				38.5	39.1	38.6	38.4	36.5	36.5	36.5	120
125				35.6	36.1	35.8	35.5	33.9	33.9	33.9	125
130				32.8	33.5	33.1	32.9	31.5	31.6	31.6	130
135					31	30.7	30.5	29.2	29.4	29.4	135
140					28.7	28.3	28.2	27	27.3	27.3	140
145					26.5	26.2	26.1	24.9	25.3	25.4	145
150					24.3	24.2	24.1	22.9	23.4	23.5	150
155						22.4	22.2	21.1	21.6	21.7	155
160						20.7	20.5	19.4	20	20	160
165						18.5	18.9	17.8	18.3	18.4	165
170							17.4	16.2	16.8	16.9	170
175							15.9	14.9	15.4	15.5	175
180							14.2	13.5	14.1	14.1	180
185								12.3	12.8	12.8	185
190								11.1	11.6	11.6	190
195								9.9	10.5	10.5	195
200									9.4	9.4	200
205										8.4	205
210										7.3	210

TAB 180_60105_00_000



Angle of the Y-suspension between 35° and 50° depending on the extension condition of the individual telescopic sections.
Angle du haubanage Y entre 35° et 50°, en fonction de l'état de sortie des différents éléments télescopiques.

Lifting capacities Forces de levage

TY

E

99 – 230 ft 15° 360° 308600 lbs 85% 15°												
ft	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	ft	
26	225.7	168.4									26	
28	219.4	166.4	145.2								28	
30	211.3	168.5	141.8								30	
32	199.6	179.4	148.5								32	
34	189.7	182.3	150.5								34	
36	181.1	179.8	149.4								36	
38	172.3	173.7	148.2	125.6							38	
40	163.9	167.3	146.8	125.6	104.7						40	
45	145.6	151	141.9	122.5	105.4						45	
50	131.3	136.4	134.2	119	103.4	86.4	62.6	47		35.5	50	
55	119.2	123.4	124.5	115.2	100.8	87.5	65.6	49.7	41.1	38.1	55	
60	108.7	112.1	113.6	110.7	98	86.5	68.1	52.4	44.2	41.2	60	
65	99	102.5	104.1	103.7	95.3	84.7	69.8	54.2	46.2	43.2	65	
70	90.4	94.2	95.7	95.9	92.2	82.6	70.6	55.9	47.8	44.8	70	
75	82.5	86.4	88	88.3	87.5	80.4	70.1	57.1	49.1	46.3	75	
80	74.7	79.2	80.9	81.3	81.6	77.9	68.5	57.5	49.9	47.4	80	
85	66.1	72.9	74.6	75	75.3	74.7	66.8	56.6	50	47.9	85	
90	44.8	67.4	69.1	69.5	69.9	69.5	65.1	55.6	48.9	47	90	
95		62.1	64.2	64.6	65	64.6	63	54.5	47.8	46.1	95	
100		54.8	59.6	60.1	60.5	60.1	60	53.4	46.7	45.1	100	
105			55.5	56	56.4	56	55.9	52.2	45.7	44.1	105	
110			51.8	52.3	52.7	52.4	52.3	50.5	44.7	43.1	110	
115			45.6	48.9	49.4	49	48.9	47.8	43.6	42.2	115	
120			35.5	45.8	46.3	45.9	45.8	44.8	42.7	41.2	120	
125				42.7	43.4	43.1	42.9	42	41.7	40.4	125	
130				37.7	40.7	40.4	40.3	39.4	39.6	39.1	130	
135				30.3	38.3	38	37.9	36.9	37.3	37.2	135	
140					35.4	35.7	35.5	34.5	34.9	35	140	
150					25.8	31.3	31.2	30.1	30.6	30.6	150	
160						25.3	27.3	26.3	26.8	26.8	160	
170						14.6	23.6	22.9	23.4	23.4	170	
180							16.5	19.8	20.4	20.4	180	
190							4.9	15.3	17.7	17.7	190	
200								8.1	13.5	14.2	200	
210										8.7	210	


t_180_10401_00_000

Lifting capacities Forces de levage

TY

         												
ft	99 ft	115 ft	132 ft	149 ft	165 ft	182 ft	198 ft	215 ft	227 ft	230 ft	ft	
19	238.3		135.9								19	
20	238.3	185.8	135.7								20	
21	236.8	186.2	140.3								21	
22	235.3	186.6	144.8								22	
23	233.7	187	149.3								23	
24	231.1	187.6	149.8								24	
26	225.8	189	150.8								26	
28	215.6	188.3	151.1	123.2							28	
30	205	187	151.2	124.7	97.2						30	
32	195.1	184.8	151.2	125.4	99.3						32	
34	185.1	181.6	150.5	125.8	101.2						34	
36	175.2	177.8	149.4	126.1	102.9						36	
38	165.8	169	148.2	126	103.9	76.3					38	
40	156.8	160.6	146.8	125.6	104.7	78.1	57.5				40	
45	138.3	142.5	138.9	122.5	105.4	82.9	59.4	44.6			45	
50	122.8	126.4	126.5	119	103.4	86.4	62.6	47	38.4	35.5	50	
55	109	112.6	114.1	112.4	100.8	87.5	65.6	49.7	41.1	38.1	55	
60	97.3	101	102.5	102.8	97.6	86.5	68.1	52.4	44.2	41.2	60	
65	87.5	91.2	92.8	93.2	92.7	84.7	69.8	54.2	46.2	43.2	65	
70	79.2	83	84.6	84.9	85.2	81.3	70.6	55.9	47.8	44.8	70	
75	71.8	75.7	77.3	77.6	78	76.2	70.1	57.1	49.1	46.3	75	
80	65.1	69.2	70.8	71.2	71.6	70.1	67.6	57.5	49.9	47.4	80	
85	58.8	63.3	65.1	65.5	65.8	64.7	62.8	56.6	50	47.9	85	
90	42.7	57.9	59.9	60.3	60.7	59.9	58.2	54.5	48.9	47	90	
95		52.9	55	55.5	55.9	55.3	53.9	51.3	47.7	46.1	95	
100		48	50.5	51.1	51.5	51.1	49.9	47.5	46	44.9	100	
105			46.4	46.9	47.4	47	46.3	44	43.6	43.4	105	
110			42.7	43.3	43.8	43.4	43	40.8	40.6	40.5	110	
115			39.3	40	40.5	40.1	39.9	37.9	37.7	37.7	115	
120			32.9	36.9	37.4	37.1	36.9	35.2	35.1	35.1	120	
125				34	34.6	34.3	34.1	32.7	32.6	32.6	125	
130				31.4	32	31.7	31.6	30.4	30.3	30.3	130	
135				27.9	29.7	29.4	29.2	28.1	28.2	28.2	135	
140					27.5	27.2	27	26	26.2	26.2	140	
150					23.5	23.2	23.1	22.1	22.5	22.6	150	
160						19.8	19.7	18.7	19.1	19.2	160	
170						14.3	16.7	15.7	16.1	16.2	170	
180							13.9	13	13.5	13.5	180	
190							4.9	10.4	11	11	190	
200								7.1	8.7	8.7	200	
210										6.6	210	

t_180_10405_00_000



Lifting capacities Forces de levage

TF




	49 + 8 ft*				132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	20 ft				20 ft				20 ft				20 ft				20 ft				20 ft				20 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
11	99.3																											11	
12	98.9																											12	
13	98.1																											13	
14	96.3																											14	
15	94.3																											15	
16	91.6																											16	
17	89.1																											17	
18	86.7	74.6																										18	
20	81.9	72.4																										20	
22	77.5	69	61																									22	
24	73.4	65.9	59.9																									24	
26	69.5	63	57.7	53.6	99.2																							26	
28	66.3	60.4	55.6	53.2	98.5																							28	
30	63.2	57.9	53.7	52.4	97.4																							30	
32	60.3	55.7	51.9	50.9	95.5	75.9			79.8																			32	
34	57.8	53.7	50.3	49.6	93.3	74.8			79.8																			34	
36	55.3	51.8	48.7	48.3	90.7	73			79.8				65.5															36	
38	53.1	50.1	47.3	47.3	88.4	71.4	60.5		79.5	69.9			65.2				52.1											38	
40	51	48.4	46	46.4	86	69.8	59.7		78.8	68.9			64.6				52											40	
42	49.1	46.9	44.8	45.8	83.8	68.2	58.6	53.6	77.3	67.5	57.9		63.7				51.7											42	
44	47.3	45.5	43.7	45.2	81.5	66.7	57.6	53.6	75.4	66.2	57.3	53.4	62.4	61.7			51.4				41.2							44	
46	45.6	44.1	42.6	44.5	79.3	65.3	56.7	53.5	73.4	64.9	56.5	53.2	61	60.7			50.9				41.1							46	
48	44.2	42.9	41.7	40.7	77.3	64	55.8	52.8	71.5	63.7	55.7	52.6	59.5	59.2			49.9				40.8							48	
50	42.8	41.6	40.8	36.9	75.4	62.8	54.9	52.2	69.6	62.6	54.9	52	58.1	57.8	53.4	50.6	48.9	48.3			40.5	39.5			33			50	
55	39.6	38.8	38.8		70.8	59.8	52.8	50.6	65.1	59.8	53	50.6	54.6	54.3	52.4	49.8	46.3	46.2	46.5	46.1	39.2	38.8	37.9		32.5	31.5		55	
60	37	36.5	34.8		66.6	57	50.9		61	57.3	51.3	49.3	51.3	51.1	50.7	48.6	43.7	43.8	44.4	45	37.5	37.4	37.4		31.7	31.2		60	
65					63	54.6	49.2		57.1	54.9	49.7	48.1	48.4	48.2	48.4	47.5	41.3	41.4	42	42.8	35.6	35.7	35.9	36.4	30.6	30.3	30.4		65
70					59.7	52.3	47.6		53.4	52.4	48.1		45.5	45.5	45.7	45.8	39	39.2	39.7	40.5	33.8	34.1	34.3	34.9	29.3	29.2	29.4	29.7	70
75					56.7	50.3	46.1		50	49.6	46.6		42.9	42.9	43.1		36.9	37.1	37.6	38.3	32	32.4	32.8	33.3	28	28	28.3	28.7	75
80					54	48.4	44.8		46.7	46.7	45.1		40.4	40.4	40.6		34.8	35.1	35.5		30.4	30.8	31.2	31.8	26.7	26.8	27.1	27.6	80
85					51.5	46.7	43.6		43.8	43.7	43.4		38	38.1	38.1		32.9	33.2	33.6		28.8	29.2	29.7	30.3	25.5	25.7	26	26.5	85
90					49.2	45.2	42.5		41	41.1	41.1		35.8	35.8	36		31.1	31.5	31.8		27.3	27.7	28.2		24.3	24.6	24.9	25.4	90
95					47.2	43.6	41.5		38.5	38.6	38.8		33.7	33.7	33.9		29.4	29.8	30.1		25.8	26.3	26.7		23.1	23.5	23.8		95
100					45.2	42.2			36.2	36.3	36.5		31.6	31.7	32		27.8	28.1	28.4		24.4	24.9	25.3		21.9	22.4	22.7		100
105					43.5	40.8			34	34.1	34.3		29.6	29.8	30.2		26.2	26.5	26.7		23.1	23.6	24		20.7	21.3	21.7		105
110					41.9	39.6			31.9	32.2	32.4		27.9	28.1	28.5		24.7	25.1	25.3		21.9	22.4	22.8		19.7	20.2	20.6		110
115					40.2	38.5			30	30.3			26.2	26.4	26.8		23.3	23.6	23.8		20.7	21.2	21.6		18.7	19.2	19.6		115
120					38.2	37.3			28.3	28.5			24.6	24.8	25.3		21.9	22.3	22.5		19.6	20.1	20.4		17.7	18.2	18.6		120
125					35.7	36			26.7	26.8			23.1	23.3			20.6	21	21.2		18.5	19	19.2		16.8	17.3	17.7		125
130					33.3	33.9			25.4	25.4			21.8	21.9			19.3	19.7	20		17.5	17.9	18.1		15.9	16.4	16.7		130
135					31.1				24.2	24.2			20.5	20.6			18.1	18.6			16.4	16.9	17.1		15	15.5	15.8		135
140					29.1				23	23			19.3	19.5			17	17.5			15.4	15.9	16.1		14.2	14.7	15		140
145					26.6				22	22			18.2	18.5			16	16.4			14.5	15			13.4	13.9	14.1		145
150									20.9				17.3	17.5			15	15.4			13.6	14.1			12.6	13.1	13.3		150
155									20				16.4	16.6			14.1	14.5			12.8	13.2			11.9	12.3	12.5		155
160													15.6				13.3	13.6			12	12.4			11.1	11.6			160
165													14.8				12.6	12.9			11.4	11.6			10.4	10.9			165
170													14				12	12.2			10.7	11			9.7	10.2			170
175													13.4				11.3				10.1	10.4			9.1	9.5			175
180																	10.7				9.5	9.8			8.4	8.8			180
185																	10.1				9	9.2			7.8	8.2			185
190																	9.6				8.5	8.7			7.3	7.6			190
195																					8				6.8	7.1			195
200																					7.6				6.3	6.6			200
205																					7.2				5.8				205
210																					6.8				5.3				210
215																									4.9				215
220																									4.4				220

* adapter - pièce d'adaptateur

t_180_51105_00_000 / 51125_00_000 / 51145_00_000 / 51165_00_000

Lifting capacities Forces de levage

TF



F

	49 + 8 ft*				132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	39 ft				39 ft				39 ft				39 ft				39 ft				39 ft				39 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
14	71.5																											14	
15	71.2																											15	
16	69.9																											16	
17	68.4																											17	
18	66.7																											18	
20	63.5																											20	
22	60.7																											22	
24	58																											24	
26	55.5																											26	
28	53.1	45.4																										28	
30	50.8	44.4																										30	
32	48.6	42.7			69.4																							32	
34	46.6	41.1			67.6																							34	
36	44.6	39.6			65.9			62.8																				36	
38	42.8	38.2	34		64.2			61.5				52.5																38	
40	41.1	36.9	33.5		62.6			60.1				52.5																40	
42	39.6	35.7	32.5		61			58.9				52.3																42	
44	38.2	34.5	31.6		59.6	45.4		57.6				52.1			41.5													44	
46	36.9	33.4	30.8	27	58.2	44.6		56.4				51.8			41.4													46	
48	35.7	32.5	30	27	56.8	43.7		55.3				51			41.2													48	
50	34.5	31.6	29.3	27	55.5	42.8		54.2	42.3			50.1			41			32.8										50	
55	31.8	29.4	27.6	26.9	52.4	40.8	33.8	51.6	40.7	33		47.8	39.4		39.9			32.4			26.1							55	
60	29.4	27.5	26.1	26.6	49.4	38.9	32.6	49.2	38.9	32.6		45.2	38.1		38.3			31.8			25.8							60	
65	27.4	25.9	24.8	26	46.5	37.2	31.5	46.8	37.3	31.6	27	42.9	36.7	31.1	36.4	35.1		30.7			25.3							65	
70	25.7	24.5	23.8	25.2	44	35.6	30.5	44.6	35.9	30.6	27	40.6	35.4	30.3	34.7	34	29.4	29.5	29.3		24.6	23						70	
75	24.3	23.4	23		41.8	34.2	29.6	42.4	34.5	29.7	27	38.5	34.1	29.5	32.9	32.8	28.8	28.2	28.2	26.6	23.8	22.5						75	
80	23	22.4	21.4		39.6	32.8	28.7	40.4	33.2	28.9	27	36.5	33	28.7	31.3	31.6	28.1	27.1	27.1	26	23	21.8						80	
85					37.8	31.6	27.9	38.7	32.1	28.1	27	34.5	31.9	28	29.7	30.2	27.5	25.7	25.7	25	25.1	22.1	21.1	20.3				85	
90					36	30.5	27.2	36.9	31	27.4		32.8	30.9	27.4	28.2	28.7	26.9	24.5	24.9	24.1	21.2	20.4	19.7	19.7				90	
95					34.4	29.4	26.5	35.2	30	26.8		31.1	29.9	26.8	26.7	27.3	26.3	23.3	23.8	23.3	20.4	19.7	19.1	19.1				95	
100					33	28.5	25.8	33.4	29.1	26.2		29.4	28.8	26.2	25.4	26	25.7	22.1	22.7	22.4	19.5	19.1	18.5	18.6				100	
105					31.6	27.6	25.3	31.7	28.2	25.6		27.9	27.7	25.7	24.1	24.7	25	21	21.7	21.6	18.6	18.4	17.9	18				105	
110					30.4	26.7	24.7	30	27.4	25.1		26.3	26.4	25.2	22.8	23.4	23.9	20	20.6	20.7	17.7	17.7	17.4	17.5				110	
115					29.2	26	24.2	28.4	26.7	24.6		24.8	25.1	24.6	21.7	22.2	22.7	19	19.6	19.8	16.9	17.1	16.9					115	
120					28.2	25.2		26.8	25.9	24.2		23.4	23.8	23.8	20.6	21	21.5	18	18.6	18.9	16.1	16.4	16.4					120	
125					27.1	24.6		25.3	25.1	23.8		22.1	22.5	22.8	19.4	19.9	20.3	17.1	17.7	18.1	15.3	15.7	15.8					125	
130					26.3	24		24	24.2	23.5		20.8	21.3	21.6	18.4	18.8	19.2	16.2	16.8	17.2	14.5	15	15.2					130	
135					25.4	23.5		22.7	23.1			19.6	20.1	20.5	17.3	17.8	18.1	15.4	15.9	16.3	13.7	14.3	14.6					135	
140					24.6	23		21.4	22			18.5	19	19.4	16.3	16.8	17.1	14.5	15	15.4	13	13.7	14					140	
145					23.9	22.5		20.2	20.9			17.5	17.9		15.3	15.8	16.2	13.7	14.2	14.6	12.3	13	13.3					145	
150					23.3	22.2		19.1	19.7			16.4	16.9		14.4	14.9	15.2	12.9	13.4	13.8	11.7	12.3	12.7					150	
155					22.7			18.1	18.6			15.5	15.9		13.5	14		12.2	12.6	13	11	11.7	12					155	
160					22.1			17.3	17.6			14.6	15		12.7	13.2		11.4	11.8	12.2	10.4	11	11.3					160	
165					20.8			16.5				13.7	14.1		11.9	12.3		10.7	11.1		9.8	10.4	10.7					165	
170								15.7				12.9	13.2		11.1	11.5		10	10.4		9.2	9.7	10					170	
175								15.1				12.3	12.5		10.4	10.8		9.3	9.7		8.6	9.1	9.4					175	
180												11.6			9.8	10.1		8.7	9.1		8	8.6						180	
185												11			9.3	9.5		8.2	8.5		7.5	8						185	
190												10.5			8.7	8.9		7.8	8		6.9	7.5						190	
195												10			8.2			7.3	7.6		6.4	7						195	
200															7.8			6.9	7.2		5.9	6.5						200	
205															7.4			6.5	6.8		5.4	6						205	
210															7			6.2			5	5.6						210	
215																		5.8			4.5	5.1						215	
220																		5.5			4.1	4.6						220	
225																		5.2			3.7							225	
230																		4.9			3.3							230	
235																					2.9							235	

* adapter · pièce d'adaptateur

t_180_51205_00_000 / 51225_00_000 / 51245_00_000 / 51265_00_000

Lifting capacities Forces de levage

TF



	49 + 8 ft*				132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	59 ft				59 ft				59 ft				59 ft				59 ft				59 ft				59 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
18	52.4																											18	
20	51.5																											20	
22	49.4																											22	
24	47.5																											24	
26	45.5																											26	
28	43.8																											28	
30	42.2																											30	
32	40.6																											32	
34	39.1																											34	
36	37.7				51.3																							36	
38	36.3	30.8			50.1				47.2																			38	
40	35	30.3			48.9				46.7																			40	
42	33.8	29.4			47.7				45.7																			42	
44	32.6	28.5			46.6				44.8			41.4																44	
46	31.4	27.5			45.5				43.9			40.9																46	
48	30.4	26.7			44.5				43			40.2																48	
50	29.3	25.9			43.5				42.2			39.6			34					25.6								50	
55	27	24.1	22.4		41.2	30.4			40.2	29.5		38			33.7					25.6				20.3				55	
60	24.9	22.4	21.3		39	29.4			38.3	29.2		36.5			33.1					25.4				20.3				60	
65	23.1	21	20.1	15.8	37	28			36.6	28		35	27		31.9					25.1				20.1				65	
70	21.6	19.7	19	15.5	35	26.8	22.6		35	26.9		33.7	26.7		30.6	25.5				24.5				19.8				70	
75	20.2	18.6	18.1	15.3	33.2	25.7	22.1	16	33.4	25.8	21.9	32.4	26.1	21.2	29.3	25				23.8	22.8			19.3				75	
80	18.9	17.6	17.3	15.2	31.5	24.7	21.4	15.9	31.9	24.8	21.4	31.2	25.2	21	27.9	24.2				23.1	22.5			18.9				80	
85	17.8	16.7	16.5	15	29.9	23.7	20.7	15.7	30.5	23.9	20.7	15.7	30	24.3	20.5	26.6	23.4	20		22.3	21.9			18.4	17.4			85	
90	16.8	15.9	15.9		28.5	22.8	20.1	15.6	29.2	23.1	20.2	15.6	28.8	23.5	20	15.5	25.4	22.7	19.5	15.4	21.5	21.2		17.8	16.9			90	
95	16	15.3			27.2	22	19.5		27.9	22.3	19.7	15.4	27.6	22.8	19.5	15.4	24.2	22.1	19.1	15.4	20.6	20.4	18.4	15.2	17.3	16.3	15		95
100					26	21.2	19		26.6	21.5	19.2	15.4	26.5	22.1	19.1	15.4	23	21.5	18.7	15.3	19.8	19.7	18	15.2	16.7	15.8	14.9		100
105					24.8	20.5	18.5		25.6	20.8	18.7		25.4	21.4	18.6	15.3	21.9	20.9	18.3	15.2	18.9	19	17.7	15.2	16.1	15.3	14.6		105
110					23.8	19.8	18.1		24.6	20.2	18.3		24.3	20.8	18.2	15.2	20.9	20.3	17.9	15.2	18.1	18.3	17.4	15.2	15.5	14.8	14.2	13.9	110
115					22.8	19.2	17.6		23.6	19.6	17.9		23.1	20.2	17.9		19.8	19.8	17.6	15.2	17.2	17.6	17	15.2	14.9	14.3	13.8	13.7	115
120					21.9	18.6	17.2		22.7	19	17.5		22	19.6	17.5		18.8	19.2	17.3		16.4	16.9	16.6	15.2	14.3	13.9	13.4	13.4	120
125					21	18	16.9		21.9	18.5	17.1		20.8	19.1	17.2		17.9	18.5	17		15.6	16.3	16.1		13.7	13.4	13	13.1	125
130					20.3	17.5	16.5		21.1	18	16.8		19.7	18.6	16.9		17	17.7	16.7		14.9	15.6	15.6		13.1	13	12.6	12.7	130
135					19.6	17	16.2		20.4	17.5	16.5		18.7	18.1	16.6		16.2	16.9	16.4		14.1	14.9	15		12.5	12.6	12.2		135
140					18.9	16.6			19.6	17.1	16.2		17.6	17.6	16.3		15.3	16	16		13.5	14.2	14.5		11.9	12.2	11.9		140
145					18.2	16.2			18.9	16.7	16		16.7	17	16		14.4	15.2	15.6		12.8	13.5	13.9		11.3	11.7	11.6		145
150					17.6	15.8			18.2	16.3	15.7		15.7	16.3	15.8		13.7	14.4	14.9		12.1	12.8	13.3		10.8	11.3	11.2		150
155					17	15.5			17.4	15.9			14.8	15.6	15.5		12.9	13.6	14.1		11.4	12.1	12.6		10.2	10.8	10.9		155
160					16.5	15.2			16.6	15.6			14	14.8	15		12.1	12.9	13.3		10.8	11.5	12		9.6	10.3	10.5		160
165					16	14.9			15.8	15.3			13.2	14			11.3	12.1	12.6		10.2	10.8	11.3		9.1	9.8	10.1		165
170					15.6	14.6			14.9	14.9			12.4	13.2			10.7	11.5	11.8		9.6	10.2	10.6		8.6	9.3	9.7		170
175					15.2				14.1	14.4			11.7	12.4			10	10.8			9	9.6	10		8.1	8.7	9.2		175
180					14.8				13.3	13.7			11	11.7			9.3	10.1			8.5	9	9.4		7.6	8.2	8.6		180
185					14				12.7				10.3	11			8.7	9.5			7.9	8.4			7.1	7.8	8.1		185
190									12.1				9.6	10.3			8.2	8.8			7.4	7.9			6.6	7.3	7.6		190
195									11.6				9.1	9.7			7.7	8.2			6.9	7.4			6.2	6.8	7.2		195
200													8.6				7.3	7.7			6.5	6.9			5.7	6.3			200
205													8.2				6.9	7.2			6.1	6.4			5.3	5.9			205
210													7.7				6.5	6.7			5.8	6			4.8	5.4			210
215													7.4				6.2				5.4	5.7			4.4	5			215
220																	5.8				5.1	5.4			4	4.5			220
225																	5.5				4.8	5			3.6	4.1			225
230																	5.2				4.5				3.2	3.6			230
235																					4.2				2.8	3.2			235
240																					3.8				2.8				240

F

* adapter · pièce d'adaptateur

t_180_51305_00_000 / 51325_00_000 / 51345_00_000 / 51365_00_000

Lifting capacities Forces de levage

TF



F

 ft	49 + 8 ft*				132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				 ft
	79 ft				79 ft				79 ft				79 ft				79 ft				79 ft				79 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
22	39.6																											22	
24	38.8																											24	
26	37.6																											26	
28	36.2																											28	
30	34.9																											30	
32	33.7																											32	
34	32.6																											34	
36	31.5																											36	
38	30.5				39.5																							38	
40	29.5				38.9																							40	
42	28.6				38				35.9																			42	
44	27.7				37.2				35.5																			44	
46	26.8				36.3				34.8																			46	
48	26				35.5				34.2																			48	
50	25.2	22.4			34.8				33.5				31.1															50	
55	23.2	21.2			32.9				31.9				30				26.5				21.2							55	
60	21.4	19.6			31.2				30.4				28.8				26.1				21.1							60	
65	19.8	18.3			29.7	22.9			29.1				27.7				25.6				21				16.5			65	
70	18.4	17.1			28.3	22			27.8	21.6			26.6				25				20.6				16.3			70	
75	17.1	16	14.6		26.9	21			26.6	21			25.6	20.2			24.3				20.2				16			75	
80	16	15.1	14		25.6	20.1			25.5	20.1			24.7	19.7			23.6				19.7				15.7			80	
85	15	14.2	13.3	9.4	24.4	19.3	15.3		24.5	19.3			23.7	19			22.8	18.3			19.1				15.3			85	
90	14.1	13.4	12.6	9.3	23.2	18.5	15		23.4	18.6	14.9		22.9	18.3			22.1	17.7			18.5	16.5			14.8			90	
95	13.3	12.7	12.1	9.1	22	17.8	14.6	9.6	22.4	17.9	14.6		22	17.7	14.5		21.3	17.1			17.8	16.1			14.4	13		95	
100	12.5	12.1	11.5	9.1	21	17.1	14.3	9.5	21.4	17.2	14.3	9.5	21.2	17.1	14.2	9.4	20.5	16.6	13.8		17.2	15.7			14	12.7		100	
105	11.8	11.4	11.1	9	20	16.4	13.9	9.4	20.5	16.6	14	9.4	20.4	16.5	13.9	9.4	19.6	16.1	13.6		16.5	15.3			13.6	12.4		105	
110	11.2	10.9	10.7		19.1	15.8	13.5	9.3	19.6	16.1	13.6	9.3	19.7	16	13.5	9.3	18.7	15.6	13.3	9.2	15.9	14.9	12.8		13.2	12		110	
115	10.7	10.5			18.3	15.3	13.1		18.8	15.6	13.2	9.2	18.9	15.5	13.2	9.2	17.9	15.2	13	9.2	15.2	14.5	12.5	9.1	12.7	11.7	10.3		115
120					17.5	14.8	12.8		18.1	15.1	12.9	9.2	18.2	15	12.9	9.1	17.1	14.7	12.7	9.1	14.6	14.1	12.3	9.1	12.2	11.3	10.1		120
125					16.8	14.3	12.5		17.4	14.6	12.6		17.5	14.6	12.6	9.1	16.3	14.3	12.4	9.1	13.9	13.7	12	9	11.8	11	9.9		125
130					16.1	13.8	12.2		16.6	14.1	12.3		16.9	14.2	12.3	9.1	15.5	13.9	12.1	9	13.3	13.4	11.8	9	11.3	10.6	9.7	8.9	130
135					15.4	13.4	11.9		16	13.7	12		16.3	13.8	12		14.7	13.6	11.9	9	12.7	13	11.6	9	10.9	10.3	9.5	8.9	135
140					14.8	12.9	11.6		15.5	13.3	11.8		15.7	13.4	11.8		14	13.2	11.7		12	12.6	11.4	9	10.4	9.9	9.3	8.9	140
145					14.3	12.5	11.4		14.9	12.9	11.5		15.1	13	11.6		13.4	12.9	11.5		11.4	12.1	11.2		9.9	9.6	9.1	8.9	145
150					13.7	12.2	11.1		14.4	12.5	11.3		14.4	12.7	11.4		12.7	12.6	11.3		10.8	11.6	11.1		9.4	9.3	8.9	8.9	150
155					13.2	11.8	10.9		13.9	12.2	11.1		13.7	12.4	11.2		12	12.2	11.1		10.3	11.1	10.9		9	9	8.7		155
160					12.8	11.5			13.4	11.9	10.9		13	12.1	11		11.4	11.8	10.9		9.7	10.6	10.7		8.5	8.7	8.4		160
165					12.3	11.2			13	11.6	10.8		12.3	11.8	10.8		10.7	11.3	10.8		9.2	10.1	10.4		8	8.4	8.2		165
170					11.9	10.9			12.6	11.3	10.6		11.7	11.5	10.7		10.1	10.8	10.6		8.7	9.5	10		7.6	8.1	7.9		170
175					11.5	10.7			12.2	11			11	11.2	10.5		9.5	10.2	10.4		8.1	9	9.5		7.1	7.8	7.7		175
180					11.2	10.5			11.8	10.8			10.3	10.8	10.4		8.9	9.6	10		7.6	8.5	9		6.6	7.4	7.5		180
185					10.8	10.3			11.4	10.6			9.7	10.4			8.4	9.1	9.5		7.1	8	8.5		6.2	7	7.3		185
190					10.5	10.1			11	10.4			9.1	9.9			7.8	8.5	9		6.6	7.5	8		5.8	6.6	7.1		190
195					10.2				10.5	10.2			8.5	9.4			7.3	8			6.2	7	7.5		5.4	6.2	6.8		195
200					10				10	10.1			8	8.8			6.8	7.5			5.7	6.5	7		5	5.8	6.4		200
205									9.4				7.5	8.2			6.3	7			5.3	6.1			4.6	5.4	6		205
210									9				7.1	7.6			5.9	6.5			5	5.6			4.2	4.9	5.5		210
215									8.6				6.7	7.2			5.5	6			4.6	5.1			3.8	4.5	5		215
220													6.4				5.2	5.6			4.3	4.8			3.4	4.1			220
225													6.1				4.9	5.2			4	4.4			3	3.7			225
230													5.7				4.6	4.9			3.6	4				3.3			230
235													5.5				4.2				3.3	3.7				2.8			235
240																	3.9				3	3.4							240
245																	3.6				3								245


* adapter · pièce d'adaptateur

t_180_51405_00_000 / 51425_00_000 / 51445_00_000 / 51465_00_000

Lifting capacities Forces de levage

TF



	49 + 8 ft*				132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	98 ft				98 ft				98 ft				98 ft				98 ft				98 ft				98 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
26	27																											26	
28	27																											28	
30	27																											30	
32	27																											32	
34	27																											34	
36	26.9																											36	
38	26.4																											38	
40	25.7																											40	
42	25				27																						42		
44	24.2				27				27																			44	
46	23.5				27				27																			46	
48	22.9				27				26.9																			48	
50	22.2				27				26.9				25															50	
55	20.7				26.8				26.3				24.5				21.3											55	
60	19.3 16.5				26.2				25.4				23.8				21.1											60	
65	17.9 15.7				25.1				24.3				22.9				20.7				17.2							65	
70	16.6 14.8				23.9				23.3				22				20.2				17				13.1			70	
75	15.4 13.9				22.8 16.5				22.3				21.2				19.6				16.8				12.9			75	
80	14.4 13				21.8 16.2				21.4				20.4				19				16.6				12.8			80	
85	13.4 12.2 10.2				20.8 15.6				20.5 15.5				19.7				18.4				16.2				12.5			85	
90	12.5 11.4 9.8				19.9 15				19.7 15				19 14.6				17.8				15.8				12.2			90	
95	11.7 10.8 9.3				19 14.4				18.9 14.4				18.3 14.2				17.3 13.5				15.3				11.9			95	
100	11 10.1 9				18 13.8 10.2				18.2 13.9				17.7 13.7				16.7 13.2				14.8 12.1				11.5			100	
105	10.4 9.6 8.6 6				17.2 13.3 10				17.4 13.4				17.1 13.2				16.2 12.8				14.3 12				11.1			105	
110	9.7 9.1 8.3 5.9				16.4 12.8 9.7				16.7 12.9 9.7				16.5 12.7 9.6				15.7 12.3				13.9 11.7				10.8 9.4			110	
115	9.2 8.6 8 5.9				15.6 12.3 9.5 6.1				16 12.4 9.5				15.9 12.3 9.4				15.2 11.9 9.2				13.4 11.3				10.5 9.1			115	
120	8.7 8.2 7.8 5.8				14.9 11.8 9.2 6.1				15.3 12 9.3 6.1				15.3 11.9 9.2 6				14.7 11.6 9.1				12.8 11				10.1 8.8			120	
125	8.2 7.8 7.6 5.8				14.2 11.4 9 6				14.7 11.5 9.1 6				14.7 11.5 9 6				14.2 11.2 8.9				12.3 10.7				9.8 8.6			125	
130	7.8 7.5 7.4				13.6 10.9 8.8 6				14.1 11.1 8.9 6				14.1 11.1 8.8 6				13.7 10.9 8.8 5.9				11.8 10.4 8.6				9.5 8.3			130	
135	7.5 7.2				13 10.6 8.6				13.5 10.8 8.7 5.9				13.6 10.8 8.7 5.9				13.1 10.6 8.6 5.9				11.3 10.2 8.4 5.8				9.2 8.1 7.2			135	
140					12.5 10.2 8.4				12.9 10.4 8.5 5.9				13.1 10.4 8.5 5.9				12.6 10.3 8.5 5.8				10.8 9.9 8.3 5.8				8.8 7.9 7			140	
145					11.9 9.8 8.3				12.4 10.1 8.4				12.6 10.1 8.4 5.8				12.1 10 8.3 5.8				10.3 9.6 8.2 5.8				8.5 7.7 6.9			145	
150					11.4 9.5 8.1				12 9.7 8.2				12.1 9.8 8.2 5.8				11.5 9.7 8.2 5.8				9.7 9.4 8.1 5.8				8.2 7.5 6.8 5.7			150	
155					11 9.2 8				11.5 9.4 8.1				11.7 9.5 8.1				11 9.4 8.1 5.8				9.2 9.1 8 5.8				7.8 7.3 6.6 5.7			155	
160					10.6 8.9 7.9				11.1 9.2 8				11.3 9.3 8				10.4 9.2 8				8.7 8.9 7.9 5.8				7.4 7.1 6.5 5.7			160	
165					10.2 8.6 7.8				10.6 8.9 7.9				10.9 9 7.9				9.9 8.9 7.8				8.2 8.6 7.7				7 6.9 6.4 5.7			165	
170					9.7 8.4 7.6				10.3 8.6 7.8				10.5 8.7 7.8				9.3 8.7 7.7				7.8 8.4 7.6				6.6 6.7 6.3 5.7			170	
175					9.4 8.1 7.5				9.9 8.4 7.6				10.2 8.5 7.7				8.8 8.5 7.6				7.3 8.1 7.5				6.2 6.5 6.2			175	
180					9 7.9				9.6 8.2 7.5				9.7 8.3 7.6				8.3 8.3 7.5				6.9 7.8 7.4				5.8 6.3 6.1			180	
185					8.7 7.7				9.2 8 7.4				9.3 8.1 7.5				7.8 8 7.4				6.4 7.4 7.3				5.4 6.1 5.9			185	
190					8.4 7.5				8.9 7.8 7.3				8.7 7.9 7.4				7.3 7.8 7.4				6 7 7.3				5 5.9 5.8			190	
195					8.1 7.4				8.6 7.6				8.2 7.7 7.3				6.8 7.5 7.3				5.5 6.6 7.1				4.7 5.7 5.7			195	
200					7.9 7.2				8.4 7.5				7.8 7.6 7.2				6.4 7.1 7.2				5.1 6.1 6.8				4.3 5.3 5.5			200	
205					7.6 7.1				8.1 7.3				7.3 7.4				5.9 6.8 7				4.7 5.7 6.5				3.9 4.9 5.4			205	
210					7.4				7.9 7.2				6.9 7.2				5.4 6.3				4.3 5.3 6				3.6 4.5 5.1			210	
215					7.3				7.7 7.1				6.5 6.9				5 5.9				3.9 4.9 5.6				3.2 4.2 4.8			215	
220					7.1				7.4 7				6.1 6.6				4.6 5.4				3.6 4.5 5.1				3.8 4.5			220	
225									7.2				5.7 6.2				4.2 5				3.3 4.1				3.4 4.1			225	
230									6.9				5.3 5.8				3.9 4.5				3.7				3.7			230	
235									6.6				4.9 5.4				3.6 4.1				3.3				3.3			235	
240													4.6				3.3 3.7				2.9							240	
245													4.4				3 3.4											245	
250													4.1				3.1											250	
255													3.8															255	

* adapter · pièce d'adaptateur

t_180_51505_00_000 / 51525_00_000 / 51545_00_000 / 51565_00_000

Lifting capacities Forces de levage

TF



F

 ft	49 + 8 ft*				132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				 ft
	118 ft				118 ft				118 ft				118 ft				118 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
28	24.2																				28
30	24																				30
32	23.6																				32
34	23.1																				34
36	22.4																				36
38	21.9																				38
40	21.3																				40
42	20.8																				42
44	20.3				24.1																44
46	19.8				23.9																46
48	19.3				23.6																48
50	18.8				23.2				21.7												50
55	17.7				22.2				21.2				19.3								55
60	16.6				21.3				20.4				19								60
65	15.6				20.4				19.6				18.3				16.6				65
70	14.5	12			19.6				18.9				17.7				16.2				70
75	13.5	11.5			18.8				18.2				17.2				15.8				75
80	12.6	10.9			18				17.5				16.6				15.3				80
85	11.7	10.2			17.3				16.9				16				14.9				85
90	10.9	9.6			16.5	11.8			16.2				15.5				14.4				90
95	10.2	9			15.8	11.4			15.6	11.3			15				14				95
100	9.5	8.5	6.9		15.1	11			15	10.9			14.4	10.6			13.6				100
105	8.9	8.1	6.7		14.4	10.5			14.4	10.5			14	10.3			13.1				105
110	8.3	7.7	6.4		13.8	10.1			13.8	10.1			13.5	9.9			12.7	9.5			110
115	7.9	7.3	6.2		13.1	9.7	6.9		13.2	9.7			13	9.5			12.3	9.2			115
120	7.4	6.9	6	3.4	12.5	9.3	6.9		12.7	9.4	6.7		12.5	9.2			11.9	8.9			120
125	7	6.6	5.8	3.3	11.9	9	6.7		12.1	9	6.7		12	8.9			11.6	8.6			125
130	6.7	6.3	5.6	3.2	11.4	8.6	6.5		11.6	8.7	6.5		11.6	8.6	6.5		11.2	8.3			130
135	6.3	6	5.4	3.2	10.8	8.3	6.3	3.6	11.1	8.4	6.4		11.1	8.3	6.3		10.8	8.1	6.2		135
140	6	5.7	5.3	3.2	10.3	8.1	6.2	3.6	10.7	8.1	6.2	3.6	10.7	8.1	6.2		10.4	7.9	6.1		140
145	5.7	5.5	5.2	3.1	9.8	7.8	6.1	3.6	10.2	7.9	6.1	3.6	10.2	7.8	6.1	3.6	10	7.6	6		145
150	5.5	5.3	5.2		9.4	7.5	5.9	3.6	9.8	7.6	6	3.6	9.9	7.6	6	3.6	9.6	7.4	5.9	3.6	150
155	5.2	5.1			9	7.3	5.8		9.3	7.4	5.8	3.6	9.5	7.4	5.9	3.6	9.3	7.3	5.8	3.6	155
160					8.6	7.1	5.7		9	7.2	5.7	3.6	9.1	7.2	5.7	3.6	8.9	7.1	5.7	3.6	160
165					8.2	6.9	5.6		8.6	7	5.6		8.8	7	5.7	3.6	8.5	6.9	5.6	3.6	165
170					7.9	6.7	5.5		8.3	6.8	5.5		8.4	6.9	5.6	3.6	8.2	6.8	5.5	3.6	170
175					7.6	6.4	5.4		7.9	6.6	5.5		8.1	6.7	5.5		7.8	6.6	5.5	3.6	175
180					7.3	6.3	5.3		7.7	6.4	5.4		7.9	6.5	5.4		7.4	6.5	5.4		180
185					7.1	6.1	5.3		7.4	6.3	5.3		7.6	6.4	5.3		7	6.3	5.3		185
190					6.8	5.9	5.2		7.2	6.1	5.3		7.3	6.2	5.3		6.6	6.2	5.3		190
195					6.6	5.7	5.2		6.9	5.9	5.2		7.1	6	5.2		6.2	6.1	5.2		195
200					6.4	5.6			6.7	5.8	5.2		6.8	5.9	5.2		5.8	5.9	5.2		200
205					6.1	5.5			6.5	5.6	5.2		6.5	5.8	5.2		5.3	5.7	5.1		205
210					5.9	5.3			6.3	5.5			6.2	5.6	5.1		5	5.5	5.1		210
215					5.8	5.2			6.1	5.4			6	5.5	5.1		4.6	5.3	5.1		215
220					5.6	5.1			5.9	5.3			5.6	5.4	5.1		4.2	5.1	5.1		220
225					5.4	5			5.7	5.2			5.3	5.3			3.8	4.8	5		225
230					5.3				5.6	5.1			4.9	5.2			3.4	4.4			230
235					5.1				5.4	5			4.5	5			3	4			235
240					5				5.3	4.9			4.2	4.8				3.6			240
245									5.2				3.8	4.5				3.2			245
250									5				3.5	4.1							250
255									4.9				3.2	3.7							255
260													2.9								260

* adapter · pièce d'adaptateur

t_180_51605_00_000 / 51625_00_000 / 51645_00_000 / 51665_00_000

Lifting capacities Forces de levage

TF



ft	198 + 8 ft*				215 + 8 ft*				227 + 8 ft*				230 + 8 ft*	ft
	118 ft				118 ft				118 ft				118 ft	
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	
70	13.7													70
75	13.5				9.6									75
80	13.3				9.5				6.3				5.5	80
85	13.1				9.4				6.4				5.5	85
90	12.8				9.3				6.4				5.5	90
95	12.5				9.2				6.4				5.5	95
100	12.2				9				6.3				5.5	100
105	11.9				8.9				6.2				5.5	105
110	11.6				8.8				6.1				5.4	110
115	11.3	8.5			8.5				6				5.4	115
120	10.9	8.3			8.2	6.9			5.9				5.3	120
125	10.6	8.1			8	6.8			5.7				5.3	125
130	10.2	7.8			7.7	6.6			5.6	6			5.2	130
135	9.8	7.6			7.4	6.5			5.3	5.8			5	135
140	9.4	7.5	5.9		7.2	6.3			5.1	5.7			4.8	140
145	9	7.3	5.9		6.9	6.1			4.8	5.5			4.5	145
150	8.6	7.1	5.8		6.7	5.9			4.4	5.4			4.2	150
155	8.2	7	5.7		6.4	5.8			4.1	5.1			3.8	155
160	7.7	6.8	5.6	3.5	6.2	5.6	5		3.7	4.9			3.5	160
165	7.3	6.7	5.5	3.5	5.9	5.5	4.8		3.2	4.6			3.1	165
170	6.9	6.6	5.5	3.6	5.6	5.3	4.7		2.8	4.3	4.3		2.7	170
175	6.5	6.4	5.4	3.6	5.3	5.2	4.6	3.6		4	4.2			175
180	6.1	6.3	5.3	3.6	5	5.1	4.5	3.6		3.6	4.1	3.6		180
185	5.7	6.1	5.3		4.7	4.9	4.4	3.6		3.2	4	3.6		185
190	5.3	6	5.2		4.3	4.8	4.3	3.6		2.8	3.9	3.6		190
195	4.9	5.8	5.2		4	4.6	4.3				3.6			195
200	4.5	5.6	5.1		3.6	4.4	4.2				3.3			200
205	4.1	5.3	5.1		3.3	4.2	4.1							205
210	3.8	4.9	5			4	4							210
215	3.4	4.6	4.9			3.8	4							215
220	3	4.2	4.8			3.4	3.8							220
225		3.8	4.5			3.1	3.7							225
230		3.4	4.2				3.5							230
235		3.1	3.8				3.2							235
240			3.4				2.8							240

* Adapter · adapter

t_180_51605_00_000 / 51625_00_000 / 51645_00_000 / 51665_00_000

F

Lifting capacities Forces de levage


TF



		49 + 8 ft*			132 + 8 ft*			149 + 8 ft*			165 + 8 ft*			182 + 8 ft*			198 + 8 ft*			215 + 8 ft*		227 + 8 ft*		
		138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			138 ft		138 ft		
		0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	0°	20°	
F	32	18.7																					32	
	34	18.6																					34	
	36	18.4																					36	
	38	17.9																					38	
	40	17.5																					40	
	42	17.1																					42	
	44	16.6																					44	
	46	16.2																					46	
	48	15.9																					48	
	50	15.5				18.5																	50	
55	14.6				17.9			16.8														55		
60	13.8				17.2			16.4														60		
65	13				16.4			15.7			14.6											65		
70	12.3				15.8			15.1			14.1			12.8								70		
75	11.5				15.1			14.5			13.7			12.5			10.8					75		
80	10.8				14.5			14			13.2			12.1			10.7					80		
85	10.1	8.4			13.9			13.5			12.8			11.7			10.5		7.1		3.6		85	
90	9.5	7.9			13.4			13			12.3			11.4			10.2		7		3.6		90	
95	8.9	7.5			12.9			12.5			11.9			11.1			9.9		6.9		3.5		95	
100	8.3	7.1			12.3	8.6		12.1	8.3		11.6			10.8			9.6		6.8		3.5		100	
105	7.8	6.7			11.8	8.3		11.6	8.2		11.2			10.4			9.4		6.7		3.5		105	
110	7.3	6.3			11.3	7.9		11.2	7.9		10.8	7.6		10.1			9.1		6.6		3.5		110	
115	6.9	6	4.6		10.8	7.6		10.7	7.6		10.4	7.4		9.8	6.9		8.8		6.5		3.5		115	
120	6.5	5.7	4.5		10.3	7.4		10.3	7.3		10	7.2		9.5	6.9		8.6		6.4		3.5		120	
125	6.1	5.4	4.3		9.8	7.1		9.9	7		9.7	6.9		9.2	6.7		8.3		6.2		3.4		125	
130	5.8	5.2	4		9.4	6.8		9.5	6.8		9.3	6.7		8.9	6.5		8.1	6.1	6		3.4		130	
135	5.5	4.9	3.8		9	6.6	4.8	9.1	6.6		9	6.5		8.5	6.3		7.8	5.9	5.8		3.3		135	
140	5.2	4.7	3.6		8.6	6.4	4.7	8.7	6.4	4.6	8.6	6.3	4.5	8.2	6.1		7.6	5.8	5.7	4.8	3.2		140	
145	4.9	4.5	3.5		8.2	6.1	4.5	8.4	6.2	4.5	8.3	6.1	4.5	7.9	5.9		7.4	5.6	5.5	4.6	3.1		145	
150	4.6	4.3	3.3		7.8	5.9	4.4	8	6	4.4	8	5.9	4.4	7.7	5.7		7.2	5.5	5.3	4.5	2.9	3.7	150	
155	4.4	4	3.2		7.5	5.7	4.3	7.7	5.8	4.3	7.7	5.7	4.3	7.5	5.6	4.2	6.9	5.3	5	4.3		3.6	155	
160	4.2	3.8	3.1		7.2	5.5	4.2	7.4	5.6	4.2	7.4	5.6	4.2	7.2	5.4	4.1	6.7	5.2	4.8	4.2		3.4	160	
165	3.9	3.6	3.1		6.9	5.4	4.1	7.1	5.4	4.1	7.2	5.4	4.1	7	5.3	4	6.3	5.1		4.6	4.1		3.3	165
170	3.8	3.5	3		6.6	5.2	4	6.8	5.3	4	6.9	5.3	4	6.7	5.1	3.9	6	4.9	3.9	4.4	3.9		3.2	170
175	3.6	3.4			6.3	5	3.9	6.6	5.1	3.9	6.7	5.1	3.9	6.5	5	3.9	5.7	4.8	3.8	4.2	3.8		3	175
180					6.1	4.9	3.8	6.3	5	3.8	6.5	5	3.8	6.2	4.9	3.8	5.3	4.7	3.7	4	3.7			180
185					5.9	4.8	3.7	6.1	4.8	3.7	6.2	4.8	3.7	6	4.8	3.7	5	4.6	3.6	3.8	3.6			185
190					5.6	4.6	3.6	5.9	4.7	3.7	6	4.7	3.7	5.7	4.6	3.7	4.6	4.5	3.6	3.5	3.4			190
195					5.4	4.5	3.6	5.7	4.6	3.6	5.8	4.6	3.6	5.5	4.5	3.6	4.3	4.4	3.5	3.2	3.3			195
200					5.2	4.4	3.5	5.5	4.4	3.5	5.6	4.5	3.6	5.1	4.4	3.5	3.9	4.3	3.5	2.8	3.2			200
205					5	4.2	3.5	5.3	4.3	3.5	5.4	4.4	3.5	4.8	4.3	3.5	3.6	4.2	3.4		3			205
210					4.8	4.1	3.4	5.1	4.2	3.4	5.2	4.3	3.5	4.4	4.2	3.4	3.2	4.1	3.4		2.9			210
215					4.6	4	3.4	4.9	4.1	3.4	5	4.2	3.4	4	4.1	3.4	2.8	4	3.4		2.7			215
220					4.5	3.9		4.7	4	3.4	4.8	4.1	3.4	3.7	4	3.4		3.8	3.3					220
225					4.3	3.8		4.6	3.9	3.4	4.5	4	3.3	3.3	3.9	3.3		3.5	3.3					225
230					4.1	3.7		4.4	3.8		4.3	3.9	3.3		3.7	3.3		3.1	3.3					230
235					4	3.6		4.3	3.7		4.1	3.8	3.3		3.6	3.3		2.8	3.2					235
240					3.9	3.5		4.1	3.6		3.8	3.7	3.3		3.4	3.3			3.1					240
245					3.7	3.4		4	3.6		3.4	3.6			3.1	3.3			2.9					245
250					3.6			3.9	3.5		3.1	3.5												250
255					3.5			3.8	3.4		2.8	3.4												255
260					3.4			3.6	3.4			3.2												260
265								3.5				2.9												265
270								3.4																270
275								3.3																275

* adapter - pièce d'adaptateur

t_180_51705_00_000 / 51725_00_000 / 51745_00_000



Lifting capacities Forces de levage

TYVEF

132 – 215 ft T Y 11.5 ft V E 20 ft F 360° 308600 lbs 85%																			
ft	132 + 20 ft*			149 + 20 ft*			165 + 20 ft*			182 + 20 ft*			198 + 20 ft*			215 + 20 ft*			ft
	20 ft			20 ft			20 ft			20 ft			20 ft			20 ft			
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
32	127.3																		32
34	127.3			122.1			104.3												34
36	127.3			121.4			106.4												36
38	127.3	83.5		120.6	84		110.5			93.7									38
40	127.1	82.9		119.6	83.5		110.1			97									40
45	122	80.6	62.8	116.2	82.1	63.4	108.1	82.6	63.6	96	82.5		83.2						45
50	115.4	78.2	61.9	111.2	80	62.4	104.3	81	62.7	94	81.6	63	81.8	78.9		69.8			50
55	109.5	75.9	61	103.3	77.8	61.6	99.9	78.9	61.9	91.2	79.9	62.2	80.5	77.7	63.2	68.6	68.8		55
60	102.9	73.8	60.2	96.3	75.8	60.8	94.8	77	61.2	88	78.1	61.5	78.3	76.9	62.5	67.5	67.8	62.1	60
65	96.5	71.9	59.6	90.3	73.9	60.1	89	75.2	60.5	83.1	76.4	60.8	76	75.3	61.9	66.4	66.7	61.5	65
70	90.4	70.1	58.9	84.9	72.1	59.5	83.9	73.5	59.9	78.2	74.3	60.2	73	72.8	61.3	64.9	65.3	61	70
75	84.6	68.4	58.3	79.9	70.5	58.9	79.3	71.9	59.3	73.8	72.1	59.7	68.9	69.9	60.8	63	63.5	60.4	75
80	79.2	66.9	57.9	74.9	69	58.4	75.1	70.2	58.8	69.9	69.9	59.2	65.1	66	60.3	60.6	61.2	59.9	80
85	73.7	65.5	57.5	70.5	67.5	58	71	68.3	58.3	66.3	66.4	58.7	61.8	62.5	59.8	57.4	57.9	58.2	85
90	68	64.2	57.2	66.4	66.1	57.6	67.1	66.6	57.9	62.8	63.1	58.3	58.6	59.5	58.9	54.5	54.8	55.3	90
95	62.8	62.7	57	62.2	63.5	57.2	63.5	64	57.6	59.3	60	57.6	55.7	56.6	56.6	51.7	52.1	52.5	95
100	58.1	59.7	56.8	57.8	59.5	57	60.1	60.7	57.1	56.2	56.8	56.5	52.7	53.8	54.2	49.1	49.5	49.9	100
105	53.9	55.4	55.8	53.6	55.1	55.7	56.5	57.6	56.6	53.3	53.9	54.4	49.9	51.1	51.6	46.5	47.1	47.5	105
110	50	51.4		49.7	51.2	52	52.9	54.1	54.9	50.5	51.1	51.6	47.2	48.4	49	43.9	44.7	45.3	110
115	46.6	47.8		46.1	47.6	48.3	49.5	50.6	51.3	47.6	48.5	49.1	44.8	45.9	46.5	41.6	42.3	43	115
120	43.1	44.4		42.7	44.2	44.8	46.3	47.3	47.9	44.7	45.9	46.5	42.5	43.6	44.1	39.4	40.1	40.7	120
125	40.1	41.2		39.6	41		43.3	44.2	44.8	42	43.1	43.9	40.3	41.4	41.9	37.3	38	38.6	125
130	37.2	38.3		36.8	38		40.5	41.4	41.9	39.3	40.4	41.2	37.8	39.2	39.9	35.4	36	36.6	130
135	34.2	35.4		34	35.2		37.8	38.7	39.2	36.8	37.8	38.4	35.5	36.8	37.6	33.4	34.2	34.7	135
140	31.7	32.6		31.4	32.6		35.4	36.2		34.4	35.2	35.8	33.2	34.6	35.3	31.4	32.3	32.9	140
145	28.1			29.1	30		33	33.8		31.9	32.9	33.4	31	32.4	33	29.3	30.3	31	145
150	23.8			26.8	27.7		30.8	31.6		29.8	30.6		28.9	30.2	30.7	27.3	28.3	29	150
155	18.6			24.7			28.6	29.4		27.6	28.5		26.8	28	28.5	25.4	26.4	27	155
160	11.9			21.6			26.7	27.3		25.7	26.4		25	26		23.7	24.6	25.2	160
165				18			24.9	25.4		23.9	24.6		23.2	24.2		22	22.8	23.3	165
170				13.8			23	23.6		22.2	22.7		21.4	22.4		20.3	21.1		170
175				8.5			20.2	21.2		20.5	21.1		19.8	20.7		18.8	19.5		175
180							17.1			19	19.5		18.3	19.2		17.1	17.9		180
185							13.6			17.3	18		16.9	17.7		15.8	16.4		185
190							9.3			14.9			15.5	16.2		14.4	15		190
195										12.3			14.2	14.9		13.1	13.6		195
200										9.4			12.6	13.5		11.8	12.4		200
205										6			10.5			10.6	11.1		205
210													8.4			9.5	9.9		210
215													5.9			8	8.7		215
220																6.1			220

* adapter · pièce d'adaptateur

t_180_61101_00_000 / 61121_00_000 / 61141_00_000

Lifting capacities Forces de levage

TYVEF

132 – 215 ft T Y 11.5 ft V E 20 ft F 360° 220500 lbs 85%																											
ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				ft		
	20 ft				20 ft				20 ft				20 ft				20 ft				20 ft						
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°			
28	127.3																								28		
30	127.3				121.5																				30		
32	127.3				122.1																				32		
34	127.3	84.6			122.1				106.5																34		
36	127.3	84.1			121.4	84.4			110.3																36		
38	127.3	83.5	64.4		120.6	84			110.5				96.5												38		
40	127.1	82.9	63.9		119.6	83.5			110.1				97												40		
45	122	80.6	62.8	56	116.2	82.1	63.4	56	108.1	82.6	63.6		96	82.5			83.2								45		
50	115.4	78.2	61.9	55.9	111.2	80	62.4	55.9	104.3	81	62.7	55.8	94	81.6	63		81.8	78.9			69.8				50		
55	109.5	75.9	61	55.7	103.3	77.8	61.6	55.7	99.9	78.9	61.9	55.6	91.2	79.9	62.2	55.6	80.5	77.7	63.2		68.6	68.8			55		
60	100.8	73.8	60.2	55.4	96.1	75.8	60.8	55.6	94.8	77	61.2	55.6	88	78.1	61.5	55.5	78.3	76.9	62.5	56.2	67.5	67.8	62.1		60		
65	91.4	71.9	59.6		88.2	73.9	60.1	55.3	88.9	75.2	60.5	55.4	83.1	76.4	60.8	55.4	76	75.3	61.9	56.2	66.4	66.7	61.5	56.1	65		
70	83	70.1	58.9		80.1	72.1	59.5		81.6	73.5	59.9	55.1	77.8	74.3	60.2	55.2	73	72.8	61.3	56.2	64.9	65.3	61	56.1	70		
75	75.6	68.4	58.3		73	70.4	58.9		74.8	71.2	59.3		71.6	72.1	59.7	54.9	68.2	69.9	60.8	56.2	63	63.5	60.4	56.1	75		
80	69.1	66.9	57.9		66.7	68.8	58.4		68.8	69.6	58.8		65.8	67.8	59.2	54.7	62.9	65.3	60.3	56.2	59.7	61.2	59.9	56.1	80		
85	63.2	64.7	57.5		61.2	63.5	58		63.5	65.1	58.3		60.7	62.6	58.4	54.6	58	60.3	59.5	56.2	55.1	57.2	58.2	56.1	85		
90	58	60.1	57.2		56.2	58.4	57.4		58.6	60.4	57.8		56	57.8	58		53.6	55.8	57.3	56.2	50.9	52.8	54.4	55.6	90		
95	53	54.9	55.3		51.6	53.7	55.1		54.2	55.9	56.2		51.7	53.4	54.7		49.4	51.6	53.1		46.9	48.7	50.2	51.3	95		
100	48.5	50.2	51.2		47.4	49.4	50.6		50.1	51.7	53		47.9	49.4	50.8		45.6	47.6	49.1		43.2	44.9	46.4		100		
105	44.3	46	46.8		43.5	45.4	46.5		46.5	47.9	49.1		44.3	45.7	47		42.1	44.1	45.3		39.9	41.5	42.8		105		
110	40.4	42			40	41.7	42.6		43	44.4	45.4		40.9	42.3	43.4		38.9	40.8	42		36.7	38.3	39.5		110		
115	37.1	38.4			36.6	38.2	38.9		39.9	41.1	42.1		37.8	39.2	40.2		36	37.7	38.9		33.9	35.3	36.5		115		
120	33.8	35.2			33.4	34.9	35.6		37	38.2	39		35	36.2	37.2		33.3	34.9	36		31.3	32.7	33.7		120		
125	30.9	32			30.6	31.8			34.2	35.3	36		32.4	33.6	34.5		30.7	32.3	33.2		28.8	30.1	31.1		125		
130	28.2	29.3			27.9	29.1			31.6	32.6	33.1		30	31.1	31.9		28.4	29.9	30.8		26.6	27.8	28.7		130		
135	25.7	26.7			25.4	26.5			29.1	30	30.5		27.7	28.8	29.5		26.2	27.6	28.4		24.4	25.6	26.4		135		
140	23.4	24.2			23.1	24.2			26.9	27.7			25.6	26.6	27.3		24.2	25.5	26.3		22.4	23.6	24.3		140		
145	21.3				21	21.9			24.7	25.5			23.7	24.6	25.1		22.2	23.6	24.2		20.6	21.6	22.3		145		
150	19.2				19	19.9			22.8	23.4			21.8	22.6			20.4	21.7	22.3		18.8	19.8	20.5		150		
155	17.3				17.1				20.9	21.5			19.9	20.7			18.8	19.9	20.5		17.2	18.1	18.7		155		
160	11.9				15.4				19.1	19.8			18.2	18.9			17.2	18.3			15.6	16.5	17.1		160		
165					13.8				17.5	18			16.6	17.3			15.7	16.8			14.1	15	15.5		165		
170					12.2				16	16.5			15.1	15.6			14.3	15.2			12.8	13.5			170		
175					8.5				14.5	15			13.6	14.2			12.9	13.8			11.5	12.2			175		
180									13.2				12.3	12.7			11.5	12.4			10.2	10.9			180		
185									11.9				11	11.4			10.3	11			9	9.7			185		
190									9.2				9.8				9.1	9.8			7.8	8.5			190		
195													8.6				8	8.6			6.7	7.3			195		
200													7.6				6.9	7.5			5.6	6.2			200		
205													5.8				5.7				4.5	5			205		
210																	4.6				3.4	3.9			210		
215																	3.6					2.7			215		


* adapter · pièce d'adaptateur

t.180_61105_00_000 / 61125_00_000 / 61145_00_000 / 61165_00_000

G

Lifting capacities Forces de levage

TYVEF



G

 ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				 ft	
	39 ft				39 ft				39 ft				39 ft				39 ft				39 ft					
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°		
36	85.5				87																				36	
38	83.4				85																				38	
40	81.4				83.1				82.6																	40
45	76.7				78.7				79				79													45
50	72.7	46.4			74.7	47.2			75.3				75.6				71.2									50
55	68.8	44.8			71.1	45.6			71.9	46.1			72.4	47.3			69.5				62.1					55
60	65.5	43.3	33.4	25.1	67.8	44.2	33.7		68.9	44.8			69.5	46.1			68.2				61.2					60
65	62.2	42	32.8	24.9	64.9	42.9	33.1	24.9	66	43.5	33.2		66.9	44.8	33.9		66.2	44.5			60.2	43.9				65
70	59.1	40.7	32.3	24.7	62.1	41.7	32.5	24.7	63.4	42.3	32.7	24.7	64.3	43.7	33.4	24.7	64	43.4	33.2		59.2	43				70
75	56.3	39.5	31.8	24.4	59.4	40.6	32.1	24.5	61.1	41.2	32.2	24.5	62	42.6	33	24.6	61.9	42.4	32.8	24.4	58.1	42.1	32.7			75
80	53.7	38.4	31.3	24.3	56.9	39.5	31.6	24.3	58.7	40.1	31.8	24.4	59.9	41.6	32.6	24.4	59.9	41.4	32.4	24.3	56.4	41.2	32.3	25.4		80
85	51.4	37.4	30.9		54.4	38.5	31.2	24.2	56.5	39.2	31.4	24.2	57.8	40.6	32.1	24.2	57.3	40.5	32	24.1	54.5	40.3	31.9	25.2		85
90	49.3	36.4	30.5		52.1	37.5	30.8		54.4	38.3	31	24.1	55.8	39.7	31.8	24.1	55	39.7	31.7	24	51.9	39.5	31.6	25.1		90
95	47.2	35.5	30.1		50.2	36.6	30.4		52.4	37.4	30.6		53.7	38.8	31.4	24	53.4	38.9	31.3	23.9	49.3	38.8	31.3	25		95
100	45.3	34.7	29.8		48.4	35.8	30.1		50.5	36.6	30.3		51.8	38	31.1		51.1	38.2	31	23.8	46.9	38	31	24.9		100
105	43.7	34	29.5		46.5	35	29.9		48.8	35.8	30		49.8	37.3	30.8		48.7	37.4	30.7	23.8	44.7	37.3	30.7	24.8		105
110	42.1	33.3	29.3		44.8	34.3	29.6		47.1	35.1	29.7		48.1	36.5	30.5		46.2	36.7	30.5	23.7	42.5	36.7	30.4	24.8		110
115	40.6	32.6	29.2		43.4	33.7	29.4		45.3	34.4	29.5		46.3	35.8	30.2		43.9	36.1	30.2		40.3	36.1	30.2	24.7		115
120	39.3	32	29		41.9	33	29.2		43.4	33.8	29.3		44.2	35.2	30		41.7	35.4	30		38.2	35.5	30			120
125	38.1	31.5	28.8		40.5	32.4	29		42.1	33.2	29.1		41.9	34.6	29.7		39.6	34.8	29.8		36.2	35	29.8			125
130	36.9	31			38.6	31.9	28.9		40.8	32.7	28.9		39.5	34	29.6		37.7	34.3	29.6		34.4	34.4	29.6			130
135	35.6	30.6			36.3	31.4	28.7		39	32.2	28.8		37.2	33.5	29.4		35.8	33.8	29.4		32.6	33.5	29.4			135
140	33.9	30.2			33.8	30.9			36.6	31.7	28.7		35	33	29.2		33.7	33	29.3		31	32.2	29.2			140
145	31.9	29.8			31.3	30.5			34.4	31.1	28.6		32.9	32.3	29.1		31.7	32.4	29.1		29.3	30.5	29.1			145
150	29.6	29.5			29.1	29.6			32.3	30.6	28.5		30.9	31.7	29.1		29.7	31.3	29		27.5	29	29			150
155	27.5	28.4			26.9	28.5			30.2	30.2			28.9	31	29		27.8	29.6	28.9		25.8	27.5	28.2			155
160	25.1	26.7			25.1	26.5			28.1	29			27	28.9	28.9		26.1	27.8	28.3		24	25.8	27			160
165	21.7				23.2	24.5			26.3	27.5			25.2	26.9	27.8		24.4	26	27.2		22.4	24.1	25.4			165
170	18				21.5	22.6			24.6	25.9			23.4	25.2			22.8	24.3	25.3		20.9	22.5	23.7			170
175	13.6				19.2				23	24.1			21.9	23.4			21.3	22.7	23.6		19.4	21	22.1			175
180	7.8				16.4				21.4	22.5			20.3	21.8			19.7	21.1			18.1	19.5	20.5			180
185					13.3				19.9	20.9			18.9	20.3			18.3	19.6			16.8	18.2	19.1			185
190					9.6				17.8	19.3			17.5	18.8			16.9	18.1			15.5	16.8				190
195					5.3				15.4				16.2	17.4			15.6	16.8			14.1	15.5				195
200									12.7				14.9	16			14.4	15.4			13	14.2				200
205									9.6				13	14.7			13.1	14.2			11.7	12.9				205
210									6.2				10.9				12.1	12.9			10.6	11.8				210
215													8.6				10.9	11.8			9.6	10.6				215
220													6.2				9.2	10.6			8.5	9.5				220
225																	7.3				7.4	8.4				225
230																	5.3				6.2	7.3				230
235																					4.7	6.1				235
240																					3					240

* adapter · pièce d'adaptateur

t_180_61201_00_000 / 61221_00_000 / 61241_00_000 / 61261_00_000

Lifting capacities Forces de levage

TYVEF

132 – 215 ft T Y 11.5 ft V E 39 ft F 360° 220500 lbs 85%																											
ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				ft		
	39 ft				39 ft				39 ft				39 ft				39 ft				39 ft						
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°			
32	90																								32		
34	87.7				88.6																				34		
36	85.5				87																				36		
38	83.4				85																				38		
40	81.4				83.1				82.6																40		
45	76.7	48.1			78.7				79				79												45		
50	72.7	46.4			74.7	47.2			75.3				75.6				71.2								50		
55	68.8	44.8	34.1		71.1	45.6			71.9	46.1			72.4	47.3			69.5				62.1				55		
60	65.5	43.3	33.4	25.1	67.8	44.2	33.7		68.9	44.8			69.5	46.1			68.2				61.2				60		
65	62.2	42	32.8	24.9	64.9	42.9	33.1	24.9	66	43.5	33.2		66.9	44.8	33.9		66.2	44.5			60.2	43.9			65		
70	59.1	40.7	32.3	24.7	62.1	41.7	32.5	24.7	63.4	42.3	32.7	24.7	64.3	43.7	33.4	24.7	64	43.4	33.2		59.2	43			70		
75	56.3	39.5	31.8	24.4	59.4	40.6	32.1	24.5	61.1	41.2	32.2	24.5	62	42.6	33	24.6	61.9	42.4	32.8	24.4	58.1	42.1	32.7		75		
80	53.7	38.4	31.3	24.3	56.9	39.5	31.6	24.3	58.7	40.1	31.8	24.4	59.9	41.6	32.6	24.4	59.3	41.4	32.4	24.3	56.4	41.2	32.3	25.4	80		
85	51.4	37.4	30.9		54.4	38.5	31.2	24.2	56.3	39.2	31.4	24.2	56.8	40.6	32.1	24.2	56.6	40.5	32	24.1	53.8	40.3	31.9	25.2	85		
90	49.3	36.4	30.5		52.1	37.5	30.8		53.9	38.3	31	24.1	54.1	39.7	31.8	24.1	53.2	39.7	31.7	24	49.9	39.5	31.6	25.1	90		
95	47.2	35.5	30.1		50.2	36.6	30.4		51.4	37.4	30.6		51.1	38.8	31.4	24	49.2	38.9	31.3	23.9	46.2	38.8	31.3	25	95		
100	45.3	34.7	29.8		47.8	35.8	30.1		49.2	36.6	30.3		47.6	38	31.1		45.6	38.2	31	23.8	42.6	38	31	24.9	100		
105	43.7	34	29.5		44.6	35	29.9		46.5	35.8	30		44.1	37.3	30.8		42.2	37.4	30.7	23.8	39.5	37.3	30.7	24.8	105		
110	42	33.3	29.3		41.2	34.3	29.6		43.2	35.1	29.7		40.9	36.5	30.5		39.1	36.7	30.5	23.7	36.5	36.7	30.4	24.8	110		
115	39.4	32.6	29.2		38	33.7	29.4		40.2	34.4	29.5		38	35.7	30.2		36.3	35.8	30.2		33.8	35.5	30.2	24.7	115		
120	36.2	32	29		35.1	33	29.2		37.4	33.8	29.3		35.2	35.1	30		33.7	35.1	30		31.2	33.8	30		120		
125	33.3	31.5	28.8		32.4	32.4	29		34.8	33.2	29.1		32.7	34.2	29.7		31.2	33.5	29.8		28.9	31.5	29.8		125		
130	30.7	31			30	31.6	28.9		32.3	32.5	28.9		30.4	33	29.5		29	31.3	29.5		26.7	29.1	29.4		130		
135	28.2	29.9			27.5	29.6	28.7		30.1	31.5	28.8		28.2	30.6	29.4		26.8	29.1	29.3		24.6	27	28.4		135		
140	25.9	27.6			25.4	27.1			28	29.9	28.7		26.2	28.5	29.2		24.9	27	28.2		22.7	24.9	26.7		140		
145	23.8	25.3			23.2	24.9			26	27.8	28.3		24.3	26.5	27.9		23	25	26.5		20.9	23	24.7		145		
150	21.8	23.1			21.2	22.9			24.2	25.7	26.7		22.5	24.6	25.9		21.3	23.2	24.6		19.2	21.3	22.8		150		
155	19.9	21.1			19.3	20.8			22.3	23.7			20.8	22.8	24		19.6	21.4	22.7		17.6	19.5	21		155		
160	18.1	19.2			17.6	19			20.6	22			19.2	21.1	22.2		18.1	19.8	21		16.1	17.9	19.3		160		
165	16.5				15.9	17.2			18.9	20.2			17.8	19.5	20.4		16.6	18.2	19.3		14.7	16.4	17.7		165		
170	14.9				14.4	15.5			17.4	18.6			16.3	18			15.3	16.8	17.8		13.4	15	16.1		170		
175	13.4				13				16	17			14.9	16.5			14	15.4	16.3		12.1	13.6	14.7		175		
180	7.8				11.6				14.6	15.6			13.5	15			12.7	14.1			10.9	12.3	13.3		180		
185					10.3				13.3	14.2			12.3	13.6			11.6	12.9			9.8	11.1	12		185		
190					9.1				12.1	12.9			11.1	12.3			10.4	11.6			8.7	9.9			190		
195					5.3				11				9.9	11.1			9.3	10.4			7.6	8.9			195		
200									9.9				8.8	9.9			8.3	9.2			6.6	7.8			200		
205									8.9				7.9	8.8			7.3	8.2			5.6	6.7			205		
210									6.1				7				6.3	7.2			4.6	5.7			210		
215													6				5.2	6.2			4.7				215		
220													5				4.3	5							220		
225																	3.3								225		


* adapter · pièce d'adaptateur

t.180_61205_00_000 / 61225_00_000 / 61245_00_000 / 61265_00_000

G

Lifting capacities Forces de levage

TYVEF



G

	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				
	59 ft				59 ft				59 ft				59 ft				59 ft				59 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
36	63.5																								36
38	61.9				62.6																				38
40	60.4				61.2																				40
45	56.8				57.8				57.8				57.2												45
50	53.6				54.8				55				55.1				53								50
55	50.9	32.6			52.1				52.5				52.7				51.6				50.2				55
60	48.2	31.4			49.7	32			50.2	32.1			50.5				49.7				48.6				60
65	46.1	30.3			47.3	30.9			48	31.1			48.4	31.4			47.8				47				65
70	43.9	29.3	22.1		45.4	29.9			46	30.2			46.6	30.5			46	30.9			45.5				70
75	41.9	28.3	21.6		43.4	29	21.8		44.2	29.3	21.8		44.8	29.6			44.4	30.1			44	30			75
80	39.9	27.4	21.1	14.2	41.6	28.1	21.3	14.2	42.5	28.5	21.4		43.1	28.8	21.5		42.9	29.4			42.6	29.3			80
85	38.1	26.6	20.6	14.1	39.9	27.3	20.8	14.1	40.9	27.7	21	14	41.7	28.1	21.1		41.4	28.6	21.7		41.4	28.6			85
90	36.3	25.8	20.2	13.9	38.3	26.5	20.4	14	39.3	26.9	20.5	13.9	40.2	27.4	20.7	13.9	40.2	28	21.4		40.2	28	21.3		90
95	34.8	25.1	19.7	13.8	36.7	25.8	20	13.8	38	26.2	20.2	13.8	38.7	26.7	20.3	13.8	38.9	27.3	21.1	14.4	39	27.4	21.1		95
100	33.4	24.4	19.4	13.7	35.3	25.1	19.7	13.7	36.7	25.6	19.8	13.7	37.5	26.1	20	13.7	37.7	26.7	20.8	14.3	38	26.8	20.8	14.2	100
105	32	23.8	19		34	24.5	19.3	13.6	35.4	25	19.5	13.6	36.4	25.5	19.7	13.6	36.6	26.1	20.5	14.2	36.9	26.3	20.5	14.2	105
110	30.6	23.2	18.7		32.7	23.9	19		34.2	24.4	19.2	13.5	35.2	24.9	19.4	13.5	35.5	25.6	20.2	14.1	35.9	25.7	20.2	14.1	110
115	29.5	22.6	18.4		31.4	23.3	18.7		33	23.8	18.9		34.1	24.3	19.1	13.4	34.5	25	19.9	14	35	25.2	20	14	115
120	28.4	22.1	18.1		30.2	22.8	18.4		31.8	23.3	18.6		33.1	23.8	18.8		33.5	24.5	19.7	14	34.1	24.8	19.7	14	120
125	27.4	21.6	17.9		29.2	22.3	18.1		30.7	22.8	18.4		32.1	23.3	18.5		32.6	24.1	19.4		33.2	24.3	19.5	13.9	125
130	26.5	21.1	17.7		28.2	21.8	17.9		29.6	22.4	18.1		31	22.8	18.3		31.7	23.6	19.2		32.4	23.9	19.3	13.9	130
135	25.6	20.6	17.5		27.3	21.4	17.7		28.7	21.9	17.9		30	22.4	18.1		30.8	23.2	19		31.6	23.5	19.1	13.8	135
140	24.8	20.2	17.3		26.4	20.9	17.5		27.8	21.5	17.7		29.2	22	17.9		30	22.8	18.8		30.4	23.1	18.9		140
145	24	19.7	17.1		25.6	20.5	17.3		27	21.1	17.5		28.3	21.6	17.7		29.1	22.4	18.6		29.2	22.7	18.7		145
150	23.2	19.4			24.9	20.1	17.2		26.1	20.7	17.4		27.5	21.2	17.5		27.9	22	18.4		27.8	22.3	18.5		150
155	22.5	19			24.2	19.7	17.1		25.5	20.2	17.2		26.5	20.8	17.4		27.1	21.7	18.2		26.3	22	18.3		155
160	21.8	18.6			23.4	19.3			24.8	19.9	17.1		25.7	20.4	17.2		26.3	21.3	18.1		24.7	21.6	18.2		160
165	21.1	18.4			22.8	19			23.9	19.5	17		25	20	17.1		24.8	21	17.9		23.1	21.3	18		165
170	20.4	18.1			22.1	18.6			23.2	19.2			24.4	19.7	17		23.3	20.7	17.8		21.6	21	17.9		170
175	19.7	17.9			21.1	18.4			22.6	18.9			23.2	19.4	16.9		21.8	20.4	17.7		20.2	20.7	17.8		175
180	19				20.2	18.1			22	18.6			21.7	19.1			20.5	20.1	17.6		18.9	20.3	17.7		180
185	16.9				18.8	17.9			21.2	18.3			20.2	18.7			19.2	19.8	17.5		17.6	19.7	17.6		185
190	13.6				17.2	17.6			20	18			18.9	18.4			17.9	19.4	17.5		16.4	18.4	17.5		190
195	9.7				14.9				18.8	17.8			17.6	18.2			16.6	18.8	17.4		15.2	17.2	17.4		195
200					12.4				17.5	17.6			16.4	17.4			15.4	17.5			14.2	16	17.2		200
205					9.7				15.9	17.1			15.2	16.5			14.3	16.2			13.1	14.8	16		205
210					6.6				14	13.5			14.1	15.4			13.1	15			12	13.7			210
215									11.8				12.9	14.2			12.1	13.8			11	12.6			215
220									9.4				11.5	13.1			11.1	12.7			9.9	11.5			220
225									6.8				9.8	11.8			10.1	11.6			8.9	10.4			225
230									3.6				8				9	10.5			8	9.4			230
235													6				7.7	9.5			7.1	8.4			235
240													3.6				6.2	8.3			6.1	7.4			240
245																					5.1	6.5			245
250																					3.8	5.4			250
255																						4.2			255

* adapter · pièce d'adaptateur

t_180_61301_00_000 / 61321_00_000 / 61341_00_000 / 61361_00_000

Lifting capacities Forces de levage

TYVEF

		 132 – 215 ft				 11.5 ft				 59 ft				 360°				 220500 lbs				 85%					
 ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				 ft		
	59 ft				59 ft				59 ft				59 ft				59 ft				59 ft						
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°			
34	64.9																								34		
36	63.5																								36		
38	61.9				62.6																				38		
40	60.4				61.2																				40		
45	56.8				57.8				57.8				57.2												45		
50	53.6				54.8				55				55.1				53								50		
55	50.9	32.6			52.1				52.5				52.7				51.6				50.2				55		
60	48.2	31.4			49.7	32			50.2	32.1			50.5				49.7				48.6				60		
65	46.1	30.3			47.3	30.9			48	31.1			48.4	31.4			47.8				47				65		
70	43.9	29.3	22.1		45.4	29.9			46	30.2			46.6	30.5			46	30.9			45.5				70		
75	41.9	28.3	21.6		43.4	29	21.8		44.2	29.3	21.8		44.8	29.6			44.4	30.1			44	30			75		
80	39.9	27.4	21.1	14.2	41.6	28.1	21.3	14.2	42.5	28.5	21.4		43.1	28.8	21.5		42.9	29.4			42.6	29.3			80		
85	38.1	26.6	20.6	14.1	39.9	27.3	20.8	14.1	40.9	27.7	21	14	41.7	28.1	21.1		41.4	28.6	21.7		41.4	28.6			85		
90	36.3	25.8	20.2	13.9	38.3	26.5	20.4	14	39.3	26.9	20.5	13.9	40.2	27.4	20.7	13.9	40.2	28	21.4		40.2	28	21.3		90		
95	34.8	25.1	19.7	13.8	36.7	25.8	20	13.8	38	26.2	20.2	13.8	38.7	26.7	20.3	13.8	38.9	27.3	21.1	14.4	39	27.4	21.1		95		
100	33.4	24.4	19.4	13.7	35.3	25.1	19.7	13.7	36.7	25.6	19.8	13.7	37.5	26.1	20	13.7	37.7	26.7	20.8	14.3	38	26.8	20.8	14.2	100		
105	32	23.8	19		34	24.5	19.3	13.6	35.4	25	19.5	13.6	36.4	25.5	19.7	13.6	36.6	26.1	20.5	14.2	36.9	26.3	20.5	14.2	105		
110	30.6	23.2	18.7		32.7	23.9	19		34.2	24.4	19.2	13.5	35.2	24.9	19.4	13.5	35.5	25.6	20.2	14.1	35.6	25.7	20.2	14.1	110		
115	29.5	22.6	18.4		31.4	23.3	18.7		33	23.8	18.9		33.9	24.3	19.1	13.4	34	25	19.9	14	33.7	25.2	20	14	115		
120	28.4	22.1	18.1		30.2	22.8	18.4		31.8	23.3	18.6		32.8	23.8	18.8		33	24.5	19.7	14	31.6	24.8	19.7	14	120		
125	27.4	21.6	17.9		29.2	22.3	18.1		30.6	22.8	18.4		31.5	23.3	18.5		31.1	24.1	19.4		29.3	24.3	19.5	13.9	125		
130	26.5	21.1	17.7		28.2	21.8	17.9		29.3	22.4	18.1		30.3	22.8	18.3		29.1	23.6	19.2		27.2	23.9	19.3	13.9	130		
135	25.6	20.6	17.5		27.3	21.4	17.7		28.4	21.9	17.9		28.7	22.4	18.1		27	23.2	19		25.2	23.5	19.1	13.8	135		
140	24.8	20.2	17.3		26.2	20.9	17.5		27.5	21.5	17.7		26.9	22	17.9		25.1	22.8	18.8		23.4	23.1	18.9		140		
145	24	19.7	17.1		24.9	20.5	17.3		26.5	21.1	17.5		25	21.6	17.7		23.3	22.4	18.6		21.6	22.7	18.7		145		
150	23	19.4			23	20.1	17.2		25.1	20.7	17.4		23.3	21.2	17.5		21.7	22	18.4		20	22.3	18.5		150		
155	21.7	19			21.3	19.7	17.1		23.4	20.2	17.2		21.7	20.7	17.4		20.1	21.7	18.2		18.4	21.2	18.3		155		
160	20.3	18.6			19.5	19.3			21.8	19.8	17.1		20.1	20.3	17.2		18.5	21.3	18.1		16.9	19.6	18.2		160		
165	18.6	18.4			17.9	18.7			20.4	19.4	17		18.6	19.9	17.1		17.1	19.9	17.9		15.6	18.2	18		165		
170	17.1	17.9			16.4	18			18.9	19.1			17.3	19.2	17		15.8	18.5	17.8		14.3	16.7	17.9		170		
175	15.6	17			14.9	16.8			17.5	18.5			16	18	16.9		14.5	17.1	17.7		13	15.4	16.9		175		
180	14.3				13.5	15.2			16.1	17.5			14.8	16.7			13.3	15.8	17		11.8	14.1	15.8		180		
185	13				12.3	13.8			14.8	16.4			13.6	15.4			12.2	14.5	15.9		10.7	12.8	14.4		185		
190	11.7				11	12.4			13.6	15.1			12.5	14.2			11.1	13.3	14.6		9.6	11.7	13.1		190		
195	9.6				9.9				12.4	13.8			11.3	12.9			10	12.2	13.4		8.6	10.5	11.9		195		
200					8.8				11.4	12.6			10.3	11.7			9.1	11.1			7.7	9.5	10.7		200		
205					7.8				10.3	11.4			9.2	10.6			8.2	10			6.7	8.5	9.6		205		
210					6.5				9.3	7.8			8.3	9.5			7.2	9			5.8	7.5			210		
215									8.4				7.4	8.4			6.4	8.1			4.9	6.6			215		
220									7.6				6.6	7.6			5.5	7.1			4	5.6			220		
225									6.7				5.7	6.7			4.6	6.2			3.1	4.7			225		
230									3.6				4.8				3.7	5.2				3.8			230		
235													3.9				2.7	4.3				2.8			235		
240													3					3.2							240		


* adapter · pièce d'adaptateur

t_180_61305_00_000 / 61325_00_000 / 61345_00_000 / 61365_00_000

G

Lifting capacities Forces de levage

TYVEF



G

	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				
	79 ft				79 ft				79 ft				79 ft				79 ft				79 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
40	47.4																								40
45	44.9				45.3				44.6																45
50	42.5				43.1				43				42.5												50
55	40.4				41				41.1				41				40.2								55
60	38.4				39.1				39.3				39.4				38.6				36.7				60
65	36.5 24				37.4				37.6				37.8				37.2				35.8				65
70	34.8 23.1				35.6 23.5				36.1				36.4				35.8				34.5				70
75	33.3 22.2				34.1 22.6				34.6 22.8				35 22.9				34.5				33.4				75
80	31.8 21.5				32.8 21.9				33.2 22.1				33.7 22.4				33.4 22.2				32.3				80
85	30.3 20.8 14.9				31.4 21.2				32 21.4				32.4 21.7				32.2 21.7				31.3 21.3				85
90	29.1 20.1 14.5				30.1 20.5 14.6				30.8 20.8				31.3 21.1				31.1 21.1				30.4 20.8				90
95	27.8 19.4 14.1				29 19.9 14.3				29.6 20.2 14.3				30.3 20.5 14.4				30.2 20.6				29.5 20.3				95
100	26.6 18.8 13.8 8.9				28 19.3 14 8.9				28.6 19.6 14				29.2 20 14.1				29.3 20 14.1				28.6 19.8				100
105	25.5 18.1 13.5 8.8				26.9 18.7 13.7 8.8				27.6 19.1 13.8 8.8				28.2 19.4 13.9				28.4 19.5 13.8				27.8 19.3 13.7				105
110	24.5 17.6 13.2 8.7				25.9 18.1 13.4 8.7				26.7 18.5 13.5 8.7				27.3 18.9 13.6 8.7				27.5 19 13.6 8.6				27.1 18.8 13.5				110
115	23.4 17 12.9 8.6				24.9 17.6 13.1 8.6				25.8 18 13.2 8.6				26.5 18.4 13.3 8.6				26.7 18.5 13.4 8.6				26.3 18.4 13.2 8.5				115
120	22.4 16.5 12.7 8.5				24 17.1 12.9 8.5				24.9 17.5 13 8.5				25.6 17.9 13.1 8.5				25.9 18 13.2 8.5				25.6 17.9 13 8.4				120
125	21.6 16 12.4				23 16.6 12.6 8.5				24.1 17 12.8 8.5				24.9 17.4 12.9 8.5				25.1 17.6 12.9 8.4				24.9 17.5 12.9 8.4				125
130	20.8 15.5 12.2				22.1 16.1 12.4				23.3 16.6 12.6 8.4				24.1 17 12.7 8.4				24.4 17.1 12.7 8.4				24.2 17.1 12.7 8.3				130
135	20 15.1 12				21.3 15.7 12.2				22.4 16.1 12.4				23.4 16.5 12.5 8.4				23.7 16.7 12.5 8.3				23.6 16.7 12.5 8.3				135
140	19.2 14.7 11.8				20.6 15.3 12				21.7 15.7 12.2				22.6 16.1 12.3				23.1 16.4 12.3 8.3				23 16.4 12.3 8.2				140
145	18.5 14.3 11.6				19.8 14.9 11.8				20.9 15.3 12				21.9 15.7 12.1				22.4 16 12.2				22.4 16 12.2 8.2				145
150	17.8 14 11.5				19.1 14.5 11.7				20.2 14.9 11.8				21.2 15.4 12				21.8 15.6 12				21.8 15.7 12 8.2				150
155	17.1 13.6 11.3				18.4 14.2 11.5				19.5 14.6 11.7				20.6 15 11.8				21.2 15.3 11.9				21.3 15.4 11.9 8.2				155
160	16.4 13.3 11.2				17.8 13.8 11.4				18.8 14.3 11.5				19.9 14.7 11.7				20.6 15 11.7				20.8 15.1 11.7				160
165	15.8 13 11.1				17.2 13.5 11.3				18.3 14 11.4				19.3 14.4 11.5				20 14.6 11.6				20.2 14.8 11.6				165
170	15.3 12.8				16.6 13.3 11.1				17.7 13.7 11.3				18.6 14.1 11.4				19.4 14.3 11.5				19.7 14.5 11.5				170
175	14.7 12.5				16 13 11.1				17.1 13.4 11.2				18.1 13.8 11.3				18.8 14.1 11.4				19.2 14.2 11.4				175
180	14.2 12.2				15.5 12.7				16.6 13.1 11.1				17.6 13.5 11.2				18.2 13.8 11.3				18.6 13.9 11.3				180
185	13.7 12				14.9 12.5				16 12.9 11				17 13.3 11.1				17.5 13.6 11.2				17.7 13.7 11.2				185
190	13.2 11.9				14.5 12.3				15.5 12.7				16.4 13 11				17 13.3 11.1				16.5 13.5 11.1				190
195	12.8 11.7				14 12.1				15.1 12.5				15.9 12.8 10.9				16.6 13.1 11				15.3 13.2 11				195
200	12.4				13.6 11.9				14.6 12.2				15.4 12.6				15.8 12.9 10.9				14.2 13 10.9				200
205	12				13.1 11.7				14.1 12				15 12.4				14.9 12.6 10.9				13.2 12.8 10.9				205
210	9.8				12.3 11.6				13.6 11.9				14.6 12.2				14.1 12.4 10.8				12.3 12.6 10.8				210
215	6.7				11.2				13.3 11.7				13.8 12				13.1 12.2				11.4 12.4 10.8				215
220					9				12.9 11.6				12.9 11.8				12.1 12				10.4 12.1 10.8				220
225					6.7				11.9 11.5				12 11.7				11 11.9				9.5 11.5 10.7				225
230					3.9				10.6 9.6				11 11.6				10.1 11.3				8.6 10.6				230
235									8.6				9.9 11.4				9.2 10.7				7.8 9.7				235
240									6.7				8.5 10.5				8.3 9.9				6.9 8.7				240
245									4.3				6.9 9.3				7.4 9				6.1 7.8				245
250													5.3				6.3 8.1				5.3 6.9				250
255													3.4				5 7.1				4.4 6.1				255
260																	3.6 5.9				3.4 5.2				260
265																					4.3				265
270																					3.3				270

* adapter · pièce d'adaptateur

t_180_61401_00_000 / 61421_00_000 / 61441_00_000 / 61461_00_000

Lifting capacities Forces de levage

TYVEF

		 132 – 215 ft T				 11.5 ft V				 79 ft F				 360°				 220500 lbs				85%							
 ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				 ft				
	79 ft				79 ft				79 ft				79 ft				79 ft				79 ft								
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
38	48.5																												38
40	47.4																												40
45	44.9					45.3				44.6																			45
50	42.5					43.1				43				42.5															50
55	40.4					41				41.1				41				40.2											55
60	38.4					39.1				39.3				39.4				38.6				36.7							60
65	36.5 24					37.4				37.6				37.8				37.2				35.8							65
70	34.8 23.1					35.6 23.5				36.1				36.4				35.8				34.5							70
75	33.3 22.2					34.1 22.6				34.6 22.8				35 22.9				34.5				33.4							75
80	31.8 21.5					32.8 21.9				33.2 22.1				33.7 22.4				33.4 22.2				32.3							80
85	30.3 20.8 14.9					31.4 21.2				32 21.4				32.4 21.7				32.2 21.7				31.3 21.3							85
90	29.1 20.1 14.5					30.1 20.5 14.6				30.8 20.8				31.3 21.1				31.1 21.1				30.4 20.8							90
95	27.8 19.4 14.1					29 19.9 14.3				29.6 20.2 14.3				30.3 20.5 14.4				30.2 20.6				29.5 20.3							95
100	26.6 18.8 13.8 8.9					28 19.3 14 8.9				28.6 19.6 14				29.2 20 14.1				29.3 20 14.1				28.6 19.8							100
105	25.5 18.1 13.5 8.8					26.9 18.7 13.7 8.8				27.6 19.1 13.8 8.8				28.2 19.4 13.9				28.4 19.5 13.8				27.8 19.3 13.7							105
110	24.5 17.6 13.2 8.7					25.9 18.1 13.4 8.7				26.7 18.5 13.5 8.7				27.3 18.9 13.6 8.7				27.5 19 13.6 8.6				27.1 18.8 13.5							110
115	23.4 17 12.9 8.6					24.9 17.6 13.1 8.6				25.8 18 13.2 8.6				26.5 18.4 13.3 8.6				26.7 18.5 13.4 8.6				26.3 18.4 13.2 8.5							115
120	22.4 16.5 12.7 8.5					24 17.1 12.9 8.5				24.9 17.5 13 8.5				25.6 17.9 13.1 8.5				25.9 18 13.2 8.5				25.6 17.9 13 8.4							120
125	21.6 16 12.4					23 16.6 12.6 8.5				24.1 17 12.8 8.5				24.9 17.4 12.9 8.5				25.1 17.6 12.9 8.4				24.9 17.5 12.9 8.4							125
130	20.8 15.5 12.2					22.1 16.1 12.4				23.3 16.6 12.6 8.4				24.1 17 12.7 8.4				24.4 17.1 12.7 8.4				24.2 17.1 12.7 8.3							130
135	20 15.1 12					21.3 15.7 12.2				22.4 16.1 12.4				23.4 16.5 12.5 8.4				23.7 16.7 12.5 8.3				23.6 16.7 12.5 8.3							135
140	19.2 14.7 11.8					20.6 15.3 12				21.7 15.7 12.2				22.6 16.1 12.3				22.8 16.4 12.3 8.3				22.5 16.4 12.3 8.2							140
145	18.5 14.3 11.6					19.8 14.9 11.8				20.9 15.3 12				21.9 15.7 12.1				22.2 16 12.2				21.4 16 12.2 8.2							145
150	17.8 14 11.5					19.1 14.5 11.7				20.2 14.9 11.8				21.1 15.4 12				21.3 15.6 12				19.9 15.7 12 8.2							150
155	17.1 13.6 11.3					18.4 14.2 11.5				19.4 14.6 11.7				20.3 15 11.8				20.4 15.3 11.9				18.4 15.4 11.9 8.2							155
160	16.4 13.3 11.2					17.8 13.8 11.4				18.7 14.3 11.5				19.6 14.7 11.7				19 15 11.7				17 15.1 11.7							160
165	15.8 13 11.1					17.2 13.5 11.3				18 14 11.4				18.8 14.4 11.5				17.6 14.6 11.6				15.6 14.8 11.6							165
170	15.3 12.8					16.6 13.3 11.1				17.5 13.7 11.3				17.8 14.1 11.4				16.3 14.3 11.5				14.3 14.5 11.5							170
175	14.7 12.5					15.9 13 11.1				16.9 13.4 11.2				16.6 13.8 11.3				15.1 14.1 11.4				13.1 14.2 11.4							175
180	14.2 12.2					14.8 12.7				16.3 13.1 11.1				15.4 13.5 11.2				13.9 13.8 11.3				12 13.9 11.3							180
185	13.7 12					13.7 12.5				15.6 12.9 11				14.2 13.3 11.1				12.8 13.4 11.2				10.9 13.5 11.2							185
190	13.1 11.9					12.5 12.3				14.7 12.7				13.2 13 11				11.7 13.2 11.1				9.8 12.5 11.1							190
195	12.1 11.7					11.3 12.1				13.5 12.4				12.1 12.7 10.9				10.7 12.7 11				8.9 11.5 11							195
200	11					10.2 11.8				12.4 12.2				11.1 12.5				9.8 12 10.9				7.9 10.4 10.9							200
205	9.9					9.2 10.8				11.4 11.9				10.2 11.9				8.8 11 10.9				7 9.4 10.8							205
210	8.9					8.2 9.7				10.3 11.6				9.2 11				7.9 10 10.7				6.2 8.4 10							210
215	6.6					7.3				9.4 11				8.4 10.1				7.1 9.1				5.3 7.5 9.1							215
220						6.5				8.5 9.9				7.5 9.1				6.3 8.2				4.5 6.6 8							220
225						5.5				7.8 9				6.7 8.1				5.4 7.2				3.6 5.7 7.1							225
230						3.7				7 4.4				5.9 7.3				4.7 6.4				4.9							230
235										6.3				5.1 6.5				3.9 5.6				4							235
240										5.5				4.3 5.6				3.1 4.7				3.2							240
245										4.1				3.4 4.7				3.9											245
250														2.6				3											250


* adapter · pièce d'adaptateur

t_180_61405_00_000 / 61425_00_000 / 61445_00_000 / 61465_00_000

G

Lifting capacities Forces de levage

TYVEF



G

	T Y \ V E																								
	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				
	98 ft				98 ft				98 ft				98 ft				98 ft				98 ft				
ft	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	ft
45	35				34.9																				45
50	33.2				33.2				32.7																50
55	31.5				31.6				31.5				31.3												55
60	29.9				30.1				30.1				30.1				29.5								60
65	28.6				28.8				28.8				28.9				28.4				26.9				65
70	27.2				27.6				27.6				27.7				27.4				26.4				70
75	26	17.6			26.4				26.6				26.7				26.4				25.5				75
80	25	16.9			25.3	17			25.6				25.8				25.4				24.7				80
85	23.9	16.2			24.4	16.4			24.6	16.5			24.8				24.6				23.9				85
90	22.9	15.5			23.4	15.8			23.7	15.9			23.9	16.1			23.8				23.2				90
95	22	14.9			22.5	15.2			22.9	15.3			23.2	15.5			23	15.5			22.5				95
100	21.1	14.4	10		21.7	14.6			22.1	14.8			22.4	15			22.3	15			21.8	14.8			100
105	20.2	13.8	9.7		20.9	14.1	9.8		21.3	14.3			21.7	14.6			21.6	14.5			21.2	14.4			105
110	19.4	13.3	9.5		20.2	13.6	9.5		20.6	13.9	9.5		20.9	14.1	9.6		21	14.1			20.6	14			110
115	18.6	12.9	9.2	5.8	19.4	13.2	9.3		19.9	13.4	9.3		20.3	13.7	9.4		20.3	13.7	9.3		20	13.6			115
120	17.8	12.4	9	5.7	18.7	12.8	9.1	5.7	19.2	13	9.1		19.6	13.3	9.2		19.7	13.3	9.1		19.4	13.2	9		120
125	17	12	8.7	5.7	18	12.3	8.9	5.7	18.5	12.6	8.9	5.6	19	12.9	9	5.6	19.1	13	8.9		18.9	12.9	8.8		125
130	16.3	11.6	8.6	5.6	17.2	12	8.7	5.6	17.9	12.2	8.7	5.6	18.3	12.5	8.8	5.6	18.5	12.6	8.8	5.5	18.3	12.5	8.7		130
135	15.6	11.2	8.4	5.6	16.5	11.6	8.5	5.6	17.3	11.9	8.5	5.5	17.8	12.2	8.6	5.5	18	12.3	8.6	5.5	17.8	12.2	8.5	5.4	135
140	15	10.9	8.2	5.5	15.8	11.2	8.3	5.5	16.7	11.6	8.4	5.5	17.2	11.8	8.5	5.5	17.4	12	8.5	5.4	17.3	11.9	8.4	5.4	140
145	14.3	10.6	8		15.3	10.9	8.1	5.5	16	11.2	8.2	5.4	16.7	11.5	8.3	5.4	16.9	11.7	8.3	5.4	16.8	11.6	8.2	5.3	145
150	13.7	10.3	7.9		14.7	10.6	8		15.5	10.9	8.1	5.4	16.1	11.2	8.2	5.4	16.4	11.4	8.2	5.4	16.3	11.3	8.1	5.3	150
155	13.2	10	7.7		14.1	10.3	7.8		14.9	10.6	7.9		15.6	10.9	8	5.4	15.9	11.1	8	5.3	15.8	11.1	8	5.3	155
160	12.6	9.7	7.6		13.5	10.1	7.7		14.4	10.3	7.8		15.1	10.6	7.9		15.5	10.8	7.9	5.3	15.4	10.8	7.9	5.3	160
165	12.1	9.4	7.5		13	9.8	7.6		13.8	10.1	7.7		14.6	10.4	7.8		15	10.5	7.8		15.1	10.6	7.8	5.3	165
170	11.6	9.2	7.4		12.6	9.5	7.5		13.3	9.8	7.6		14.1	10.1	7.7		14.6	10.3	7.7		14.7	10.3	7.7	5.2	170
175	11.1	8.9	7.4		12.1	9.3	7.4		12.9	9.6	7.5		13.6	9.9	7.6		14.1	10	7.6		14.3	10.1	7.6	5.2	175
180	10.7	8.7	7.3		11.7	9.1	7.4		12.4	9.4	7.4		13.2	9.6	7.5		13.7	9.8	7.6		13.9	9.9	7.5		180
185	10.3	8.5	7.2		11.2	8.9	7.3		12	9.1	7.4		12.7	9.4	7.4		13.3	9.6	7.5		13.5	9.7	7.5		185
190	9.9	8.3			10.8	8.6	7.3		11.6	8.9	7.3		12.3	9.2	7.4		12.8	9.4	7.4		13.1	9.5	7.4		190
195	9.6	8.1			10.4	8.5	7.2		11.2	8.7	7.2		12	9	7.3		12.4	9.2	7.3		12.8	9.3	7.3		195
200	9.2	8			10.1	8.3			10.8	8.6	7.2		11.6	8.8	7.2		12.1	9	7.2		12.4	9.1	7.3		200
205	8.9	7.9			9.7	8.1			10.5	8.4	7.1		11.2	8.6	7.2		11.7	8.8	7.2		12	8.9	7.2		205
210	8.6	7.7			9.4	8			10.1	8.2			10.8	8.5	7.1		11.4	8.7	7.1		11.7	8.8	7.1		210
215	8.3	7.6			9.1	7.8			9.8	8.1			10.5	8.3	7.1		10.9	8.5	7.1		11.2	8.6	7.1		215
220	8				8.8	7.7			9.5	7.9			10.2	8.2			10.6	8.3	7.1		10.6	8.4	7.1		220
225	7.7				8.5	7.6			9.2	7.8			9.8	8			10.3	8.2	7		9.8	8.3	7		225
230	6.9				8.2	7.5			8.9	7.7			9.5	7.9			9.9	8.1	7		9	8.2	7		230
235	4.2				7.5				8.6	7.6			9.2	7.8			9.5	7.9			8.2	8	7		235
240					6.3				8.3	7.5			8.9	7.7			9.1	7.8			7.4	7.9	7		240
245					4.2				8.1	7.5			8.6	7.6			8.3	7.7			6.7	7.7			245
250									7.3	7.2			8.2	7.5			7.5	7.6			5.9	7.4			250
255									6.2				7.1	7.4			6.6	7.5			5.2	7.1			255
260									4.2				5.8	7.4			5.8	7.1			4.5	6.5			260
265													4.4	6.9			4.8	6.7			3.8	5.7			265
270																	3.7	6			2.9	4.9			270
275																		5				4.2			275
280																		3.9				3.4			280

* adapter · pièce d'adaptateur

t_180_61501_00_000 / 61521_00_000 / 61541_00_000 / 61561_00_000

Lifting capacities Forces de levage

TYVEF

132 – 215 ft T Y 11.5 ft V E 98 ft F 360° 220500 lbs 85%																											
ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				ft		
	98 ft				98 ft				98 ft				98 ft				98 ft				98 ft						
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°			
40	36.9																								40		
45	35				34.9																				45		
50	33.2				33.2				32.7																50		
55	31.5				31.6				31.5				31.3												55		
60	29.9				30.1				30.1				30.1				29.5								60		
65	28.6				28.8				28.8				28.9				28.4				26.9				65		
70	27.2				27.6				27.6				27.7				27.4				26.4				70		
75	26	17.6			26.4				26.6				26.7				26.4				25.5				75		
80	25	16.9			25.3	17			25.6				25.8				25.4				24.7				80		
85	23.9	16.2			24.4	16.4			24.6	16.5			24.8				24.6				23.9				85		
90	22.9	15.5			23.4	15.8			23.7	15.9			23.9	16.1			23.8				23.2				90		
95	22	14.9			22.5	15.2			22.9	15.3			23.2	15.5			23	15.5			22.5				95		
100	21.1	14.4	10		21.7	14.6			22.1	14.8			22.4	15			22.3	15			21.8	14.8			100		
105	20.2	13.8	9.7		20.9	14.1	9.8		21.3	14.3			21.7	14.6			21.6	14.5			21.2	14.4			105		
110	19.4	13.3	9.5		20.2	13.6	9.5		20.6	13.9	9.5		20.9	14.1	9.6		21	14.1			20.6	14			110		
115	18.6	12.9	9.2	5.8	19.4	13.2	9.3		19.9	13.4	9.3		20.3	13.7	9.4		20.3	13.7	9.3		20	13.6			115		
120	17.8	12.4	9	5.7	18.7	12.8	9.1	5.7	19.2	13	9.1		19.6	13.3	9.2		19.7	13.3	9.1		19.4	13.2	9		120		
125	17	12	8.7	5.7	18	12.3	8.9	5.7	18.5	12.6	8.9	5.6	19	12.9	9	5.6	19.1	13	8.9		18.9	12.9	8.8		125		
130	16.3	11.6	8.6	5.6	17.2	12	8.7	5.6	17.9	12.2	8.7	5.6	18.3	12.5	8.8	5.6	18.5	12.6	8.8	5.5	18.3	12.5	8.7		130		
135	15.6	11.2	8.4	5.6	16.5	11.6	8.5	5.6	17.3	11.9	8.5	5.5	17.8	12.2	8.6	5.5	18	12.3	8.6	5.5	17.8	12.2	8.5	5.4	135		
140	15	10.9	8.2	5.5	15.8	11.2	8.3	5.5	16.7	11.6	8.4	5.5	17.2	11.8	8.5	5.5	17.4	12	8.5	5.4	17.3	11.9	8.4	5.4	140		
145	14.3	10.6	8		15.3	10.9	8.1	5.5	16	11.2	8.2	5.4	16.7	11.5	8.3	5.4	16.9	11.7	8.3	5.4	16.8	11.6	8.2	5.3	145		
150	13.7	10.3	7.9		14.7	10.6	8		15.5	10.9	8.1	5.4	16.1	11.2	8.2	5.4	16.4	11.4	8.2	5.4	16.3	11.3	8.1	5.3	150		
155	13.2	10	7.7		14.1	10.3	7.8		14.9	10.6	7.9		15.6	10.9	8	5.4	15.9	11.1	8	5.3	15.8	11.1	8	5.3	155		
160	12.6	9.7	7.6		13.5	10.1	7.7		14.4	10.3	7.8		15.1	10.6	7.9		15.5	10.8	7.9	5.3	15.4	10.8	7.9	5.3	160		
165	12.1	9.4	7.5		13	9.8	7.6		13.8	10.1	7.7		14.6	10.4	7.8		15	10.5	7.8		15	10.6	7.8	5.3	165		
170	11.6	9.2	7.4		12.6	9.5	7.5		13.3	9.8	7.6		14.1	10.1	7.7		14.3	10.3	7.7		14.1	10.3	7.7	5.2	170		
175	11.1	8.9	7.4		12.1	9.3	7.4		12.9	9.6	7.5		13.6	9.9	7.6		13.9	10	7.6		13.2	10.1	7.6	5.2	175		
180	10.7	8.7	7.3		11.7	9.1	7.4		12.4	9.4	7.4		13.1	9.6	7.5		13.5	9.8	7.6		12.1	9.9	7.5		180		
185	10.3	8.5	7.2		11.2	8.9	7.3		12	9.1	7.4		12.6	9.4	7.4		12.9	9.6	7.5		11.1	9.7	7.5		185		
190	9.9	8.3			10.8	8.6	7.3		11.5	8.9	7.3		12.1	9.2	7.4		11.9	9.4	7.4		10.1	9.5	7.4		190		
195	9.6	8.1			10.4	8.5	7.2		11.1	8.7	7.2		11.8	9	7.3		10.9	9.2	7.3		9.1	9.3	7.3		195		
200	9.2	8			10.1	8.3			10.7	8.6	7.2		11.2	8.8	7.2		10	9	7.2		8.2	9.1	7.3		200		
205	8.9	7.9			9.6	8.1			10.3	8.4	7.1		10.4	8.6	7.2		9.1	8.8	7.2		7.3	8.9	7.2		205		
210	8.6	7.7			9.1	8			10	8.2			9.6	8.5	7.1		8.2	8.6	7.1		6.4	8.7	7.1		210		
215	8.3	7.6			8.4	7.8			9.6	8.1			8.8	8.3	7.1		7.4	8.4	7.1		5.6	8.2	7.1		215		
220	8				7.6	7.7			9	7.9			8	8.1			6.6	8.3	7.1		4.8	7.5	7.1		220		
225	7.5				6.7	7.6			8.4	7.8			7.2	8			5.8	7.9	7		4	6.6	7		225		
230	6.8				6	7.2			7.8	7.7			6.4	7.8			5.1	7.3	7			5.8	7		230		
235	4.2				5.1				7.1	7.6			5.7	7.4			4.4	6.6				5	6.5		235		
240					4.2				6.4	7.5			5	6.7			3.7	5.8				4.3	5.9		240		
245					3.4				5.7	6.9			4.3	6			2.9	5				3.4			245		
250									4.9				3.6	5.3				4.3							250		
255									4.2				2.8	4.5				3.5							255		
260									3.5					3.7				2.7							260		
265														2.8											265		


* adapter · pièce d'adaptateur

t_180_61505_00_000 / 61525_00_000 / 61545_00_000 / 61565_00_000

G

Lifting capacities Forces de levage

TYVEF



G





	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				
	118 ft				118 ft				118 ft				118 ft				118 ft				118 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
45	28.1																							45	
50	26.7				27.7																			50	
55	25.3				26.4				26															55	
60	24.1				25.2				25				25											60	
65	22.9				24.1				24				24				23.5							65	
70	21.9				23				23				23				22.6				21.5			70	
75	20.9				22				22				22.1				21.8				21			75	
80	20				21.1				21.2				21.3				21				20.3			80	
85	19.1	12.8			20.2				20.4				20.5				20.3				19.7			85	
90	18.4	12.2			19.5	13.2			19.6				19.8				19.6				19.1			90	
95	17.6	11.7			18.8	12.8			18.9	12.9			19.1				19				18.4			95	
100	16.8	11.2			18	12.3			18.2	12.4			18.5	12.5			18.3				17.9			100	
105	16.2	10.8			17.3	11.9			17.6	12			17.9	12.2			17.7	12.1			17.4			105	
110	15.5	10.4			16.7	11.5			16.9	11.6			17.3	11.8			17.2	11.8			16.8	11.6		110	
115	14.9	10	6.8		16.1	11.1			16.4	11.3			16.7	11.4			16.7	11.4			16.4	11.3		115	
120	14.2	9.6	6.7		15.5	10.7	7.3		15.8	10.9			16.2	11.1			16.2	11.1			15.9	11		120	
125	13.6	9.2	6.5		15	10.3	7.1		15.3	10.5	7.1		15.6	10.7			15.7	10.8			15.5	10.6		125	
130	13	8.8	6.3		14.4	10	7		14.8	10.2	7		15.2	10.4	7		15.2	10.5			15.1	10.3		130	
135	12.4	8.5	6.2	3.3	13.9	9.6	6.8		14.3	9.8	6.8		14.7	10.1	6.9		14.8	10.1	6.9		14.6	10.1		135	
140	11.8	8.2	6	3.2	13.4	9.3	6.6	3.8	13.8	9.5	6.7		14.2	9.7	6.7		14.4	9.8	6.7		14.2	9.8	6.7	140	
145	11.3	7.9	5.9	3.2	12.8	9	6.5	3.8	13.4	9.2	6.6	3.8	13.8	9.4	6.6	3.8	14	9.5	6.6		13.8	9.5	6.6	145	
150	10.8	7.6	5.8	3.2	12.3	8.7	6.4	3.7	12.9	8.9	6.4	3.8	13.4	9.1	6.5	3.8	13.6	9.3	6.5	3.7	13.5	9.2	6.4	150	
155	10.3	7.4	5.6	3.2	11.9	8.4	6.2	3.7	12.4	8.6	6.3	3.7	13	8.9	6.4	3.8	13.2	9	6.4	3.7	13.1	9	6.3	3.7	155
160	9.9	7.2	5.5	3.2	11.4	8.1	6.1	3.7	12	8.4	6.2	3.7	12.5	8.6	6.2	3.7	12.8	8.7	6.3	3.7	12.8	8.7	6.2	3.7	160
165	9.4	7	5.4		11	7.9	6	3.7	11.6	8.1	6.1	3.7	12.1	8.4	6.1	3.7	12.4	8.5	6.2	3.7	12.4	8.5	6.1	3.7	165
170	9	6.8	5.3		10.5	7.6	5.9		11.1	7.9	6	3.7	11.7	8.1	6	3.7	12.1	8.3	6.1	3.7	12.1	8.3	6.1	3.7	170
175	8.6	6.6	5.2		10.1	7.4	5.8		10.7	7.7	5.9		11.3	7.9	5.9	3.7	11.7	8	6	3.7	11.8	8.1	6	3.7	175
180	8.3	6.5	5.1		9.7	7.2	5.7		10.3	7.5	5.8		11	7.7	5.9		11.3	7.8	5.9	3.7	11.5	7.9	5.9	3.6	180
185	7.9	6.3	5		9.4	7.1	5.6		9.9	7.3	5.7		10.6	7.5	5.8		11	7.6	5.8		11.1	7.7	5.8	3.6	185
190	7.6	6.1	5		9	6.9	5.5		9.6	7.1	5.6		10.2	7.3	5.7		10.6	7.5	5.7		10.8	7.5	5.7	3.6	190
195	7.3	6	4.9		8.7	6.7	5.4		9.2	6.9	5.5		9.9	7.2	5.6		10.3	7.3	5.7		10.5	7.3	5.6		195
200	7.1	5.8	4.9		8.3	6.6	5.4		8.9	6.8	5.4		9.5	7	5.5		10	7.1	5.6		10.2	7.2	5.6		200
205	6.8	5.7	4.8		8	6.4	5.3		8.6	6.6	5.4		9.2	6.8	5.5		9.6	7	5.5		9.9	7	5.5		205
210	6.6	5.6			7.7	6.3	5.3		8.3	6.5	5.3		8.9	6.7	5.4		9.3	6.8	5.4		9.6	6.9	5.5		210
215	6.4	5.5			7.5	6.1	5.2		7.9	6.3	5.3		8.6	6.5	5.3		9	6.7	5.4		9.3	6.8	5.4		215
220	6.2	5.4			7.2	6			7.7	6.2	5.2		8.3	6.4	5.3		8.7	6.6	5.3		9	6.7	5.3		220
225	6	5.3			7	5.9			7.5	6.1	5.2		8	6.3	5.2		8.5	6.4	5.3		8.7	6.5	5.3		225
230	5.8	5.2			6.7	5.8			7.3	6			7.7	6.2	5.2		8.2	6.3	5.2		8.5	6.4	5.2		230
235	5.6	5.2			6.5	5.7			7	5.9			7.5	6.1	5.2		8	6.2	5.2		8.2	6.3	5.2		235
240	5.4				6.3	5.6			6.8	5.8			7.3	5.9			7.6	6.1	5.1		7.7	6.2	5.2		240
245	5.3				6.1	5.5			6.6	5.7			7.1	5.8			7.4	6	5.1		7.2	6.1	5.1		245
250	4.6				5.7	5.5			6.4	5.6			6.9	5.7			7.2	5.9	5.1		6.7	6	5.1		250
255					5.1				6.2	5.5			6.7	5.7			7	5.8			6.1	5.9	5.1		255
260					4				6	5.4			6.5	5.6			6.6	5.7			5.4	5.8	5.1		260
265									5.8	5.4			6.3	5.5			6.1	5.6			4.8	5.7			265
270									5.2	5.3			5.7	5.4			5.5	5.5			4.1	5.6			270
275									4.1				4.8	5.4			4.7	5.5			3.5	5.4			275
280													3.7	5.3			3.9	5.3			2.8	4.8			280
285														4.9			2.8	5.1				4.1			285
290																		4.4				3.5			290
295																		3.6							295

* adapter · pièce d'adaptateur

t_180_61601_00_000 / 61621_00_000 / 61641_00_000 / 61661_00_000

Lifting capacities Forces de levage

TYVEF

		 132 – 215 ft T				 Y				 11.5 ft V				 E				 118 ft F								 360°				 220500 lbs				 85%					
 ft	132 + 20 ft*				149 + 20 ft*				165 + 20 ft*				182 + 20 ft*				198 + 20 ft*				215 + 20 ft*				 ft														
	118 ft				118 ft				118 ft				118 ft				118 ft				118 ft																		
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°							
45	28.1																																45						
50	26.7				27.7																												50						
55	25.3				26.4																												55						
60	24.1				25.2					26				25																			60						
65	22.9				24.1					24				24				23.5															65						
70	21.9				23					23				23				22.6				21.5											70						
75	20.9				22					22				22.1				21.8				21											75						
80	20				21.1					21.2				21.3				21				20.3											80						
85	19.1	12.8			20.2					20.4				20.5				20.3				19.7											85						
90	18.4	12.2			19.5	13.2				19.6				19.8				19.6				19.1											90						
95	17.6	11.7			18.8	12.8				18.9	12.9			19.1				19				18.4											95						
100	16.8	11.2			18	12.3				18.2	12.4			18.5	12.5			18.3				17.9											100						
105	16.2	10.8			17.3	11.9				17.6	12			17.9	12.2			17.7	12.1			17.4											105						
110	15.5	10.4			16.7	11.5				16.9	11.6			17.3	11.8			17.2	11.8			16.8	11.6										110						
115	14.9	10	6.8		16.1	11.1				16.4	11.3			16.7	11.4			16.7	11.4			16.4	11.3										115						
120	14.2	9.6	6.7		15.5	10.7	7.3			15.8	10.9			16.2	11.1			16.2	11.1			15.9	11										120						
125	13.6	9.2	6.5		15	10.3	7.1			15.3	10.5	7.1		15.6	10.7			15.7	10.8			15.5	10.6										125						
130	13	8.8	6.3		14.4	10	7			14.8	10.2	7		15.2	10.4	7		15.2	10.5			15.1	10.3										130						
135	12.4	8.5	6.2	3.3	13.9	9.6	6.8			14.3	9.8	6.8		14.7	10.1	6.9		14.8	10.1	6.9		14.6	10.1										135						
140	11.8	8.2	6	3.2	13.4	9.3	6.6	3.8		13.8	9.5	6.7		14.2	9.7	6.7		14.4	9.8	6.7		14.2	9.8	6.7									140						
145	11.3	7.9	5.9	3.2	12.8	9	6.5	3.8		13.4	9.2	6.6	3.8	13.8	9.4	6.6	3.8	14	9.5	6.6		13.8	9.5	6.6									145						
150	10.8	7.6	5.8	3.2	12.3	8.7	6.4	3.7		12.9	8.9	6.4	3.8	13.4	9.1	6.5	3.8	13.6	9.3	6.5	3.7	13.5	9.2	6.4									150						
155	10.3	7.4	5.6	3.2	11.9	8.4	6.2	3.7		12.4	8.6	6.3	3.7	13	8.9	6.4	3.8	13.2	9	6.4	3.7	13.1	9	6.3	3.7								155						
160	9.9	7.2	5.5	3.2	11.4	8.1	6.1	3.7		12	8.4	6.2	3.7	12.5	8.6	6.2	3.7	12.8	8.7	6.3	3.7	12.8	8.7	6.2	3.7								160						
165	9.4	7	5.4		11	7.9	6	3.7		11.6	8.1	6.1	3.7	12.1	8.4	6.1	3.7	12.4	8.5	6.2	3.7	12.4	8.5	6.1	3.7								165						
170	9	6.8	5.3		10.5	7.6	5.9			11.1	7.9	6	3.7	11.7	8.1	6	3.7	12.1	8.3	6.1	3.7	12.1	8.3	6.1	3.7								170						
175	8.6	6.6	5.2		10.1	7.4	5.8			10.7	7.7	5.9		11.3	7.9	5.9	3.7	11.7	8	6	3.7	11.8	8.1	6	3.7								175						
180	8.3	6.5	5.1		9.7	7.2	5.7			10.3	7.5	5.8		11	7.7	5.9		11.3	7.8	5.9	3.7	11.5	7.9	5.9	3.6								180						
185	7.9	6.3	5		9.4	7.1	5.6			9.9	7.3	5.7		10.6	7.5	5.8		11	7.6	5.8		11.1	7.7	5.8	3.6								185						
190	7.6	6.1	5		9	6.9	5.5			9.6	7.1	5.6		10.2	7.3	5.7		10.5	7.5	5.7		10.4	7.5	5.7	3.6								190						
195	7.3	6	4.9		8.7	6.7	5.4			9.2	6.9	5.5		9.8	7.2	5.6		10.2	7.3	5.7		9.7	7.3	5.6									195						
200	7.1	5.8	4.9		8.3	6.6	5.4			8.9	6.8	5.4		9.4	7	5.5		9.8	7.1	5.6		8.9	7.2	5.6									200						
205	6.8	5.7	4.8		8	6.4	5.3			8.6	6.6	5.4		9.1	6.8	5.5		9.4	7	5.5		8	7	5.5									205						
210	6.6	5.6			7.7	6.3	5.3			8.3	6.5	5.3		8.8	6.7	5.4		8.8	6.8	5.4		7.2	6.9	5.5									210						
215	6.4	5.5			7.5	6.1	5.2			7.9	6.3	5.3		8.4	6.5	5.3		8.1	6.7	5.4		6.3	6.8	5.4									215						
220	6.2	5.4			7.2	6				7.6	6.2	5.2		8.1	6.4	5.3		7.3	6.6	5.3		5.6	6.7	5.3									220						
225	6	5.3			6.8	5.9				7.4	6.1	5.2		7.7	6.3	5.2		6.6	6.4	5.3		4.9	6.5	5.3									225						
230	5.8	5.2			6.4	5.8				7.2	6			7.2	6.2	5.2		5.9	6.3	5.2		4.2	6.4	5.2									230						
235	5.6	5.2			5.8	5.7				7	5.9			6.5	6.1	5.2		5.2	6.2	5.2		3.4	6.1	5.2									235						
240	5.4				5.4	5.6				6.7	5.8			5.8	5.9			4.5	6.1	5.1		2.7	5.5	5.2									240						
245	5.2				4.6	5.5				6.3	5.7			5.1	5.8			3.9	5.9	5.1			4.8	5.1									245						
250	4.5				3.8	5.3				5.8	5.6			4.5	5.7			3.2	5.5	5.1			4.1	5.1									250						
255					3.1					5.2	5.5			3.8	5.3			2.6	4.8				3.4	4.9									255						
260										4.6	5.4			3.2	5				4.1				2.7	4.4									260						
265										3.9	5.1				4.4				3.4														265						
270										3.2	4.7				3.7																		270						
275										2.6					3																		275						


* adapter · pièce d'adaptateur

t_180_61605_00_000 / 61625_00_000 / 61645_00_000 / 61665_00_000

G

Lifting capacities Forces de levage

TYVEF



G

 ft	132 + 20 ft*			149 + 20 ft*			165 + 20 ft*			182 + 20 ft*			198 + 20 ft*		 ft
	138 ft			138 ft			138 ft			138 ft			138 ft		
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	
50	22.4														50
55	21.3			21.1											55
60	20.3			20.2			20.2			19.9					60
65	19.3			19.3			19.4			19.3					65
70	18.5			18.5			18.6			18.5			18		70
75	17.7			17.7			17.8			17.8			17.3		75
80	16.9			17			17.1			17.1			16.7		80
85	16.1			16.3			16.4			16.4			16.1		85
90	15.5			15.6			15.8			15.9			15.6		90
95	14.8	10		15			15.2			15.3			15		95
100	14.2	9.6		14.5	9.7		14.6			14.7			14.5		100
105	13.6	9.2		13.9	9.3		14.1	9.5		14.2			14.1		105
110	13.1	8.9		13.3	9		13.6	9.1		13.8	9.2		13.6		110
115	12.6	8.5		12.8	8.7		13.1	8.8		13.3	8.9		13.1	8.8	115
120	12.1	8.2		12.4	8.3		12.6	8.5		12.8	8.6		12.7	8.5	120
125	11.6	7.9		11.9	8		12.2	8.2		12.4	8.3		12.3	8.3	125
130	11.1	7.5		11.5	7.7		11.8	7.9		12	8		11.9	8	130
135	10.7	7.3	5.1	11.1	7.4	5.1	11.4	7.6		11.6	7.7		11.6	7.7	135
140	10.2	7	5	10.7	7.2	5	11	7.4	5	11.2	7.5		11.2	7.5	140
145	9.7	6.8	4.8	10.3	7	4.9	10.6	7.1	4.9	10.9	7.3	4.9	10.9	7.2	145
150	9.3	6.5	4.7	9.9	6.7	4.7	10.3	6.9	4.8	10.5	7	4.8	10.5	7	150
155	8.9	6.3	4.6	9.4	6.5	4.6	9.9	6.7	4.7	10.2	6.8	4.7	10.2	6.9	155
160	8.5	6.1	4.5	9	6.3	4.5	9.5	6.5	4.6	9.8	6.6	4.6	9.9	6.7	160
165	8.2	5.9	4.3	8.7	6.1	4.4	9.2	6.3	4.4	9.5	6.4	4.5	9.6	6.5	165
170	7.8	5.7	4.2	8.3	5.9	4.3	8.8	6.1	4.3	9.2	6.3	4.4	9.3	6.3	170
175	7.4	5.5	4.1	8	5.7	4.2	8.5	5.9	4.3	8.9	6.1	4.3	9	6.1	175
180	7.2	5.4	4	7.7	5.6	4.1	8.2	5.8	4.2	8.6	5.9	4.2	8.7	6	180
185	6.9	5.2	3.9	7.4	5.4	4	7.9	5.6	4.1	8.3	5.7	4.1	8.5	5.8	185
190	6.6	5.1	3.9	7.1	5.2	3.9	7.6	5.4	4	8	5.6	4.1	8.2	5.7	190
195	6.4	4.9	3.8	6.8	5.1	3.8	7.3	5.3	3.9	7.7	5.4	4	7.9	5.5	195
200	6.1	4.7	3.7	6.6	5	3.8	7	5.1	3.8	7.5	5.3	3.9	7.6	5.4	200
205	5.8	4.6	3.6	6.4	4.8	3.7	6.8	5	3.8	7.2	5.2	3.8	7.4	5.3	205
210	5.6	4.5	3.6	6.1	4.7	3.6	6.6	4.9	3.7	6.9	5	3.8	7.2	5.1	210
215	5.4	4.4	3.5	5.9	4.6	3.6	6.4	4.7	3.6	6.7	4.9	3.7	7	5	215
220	5.2	4.2	3.5	5.7	4.4	3.5	6.1	4.6	3.6	6.5	4.8	3.7	6.7	4.9	220
225	5	4.1	3.4	5.5	4.3	3.5	5.9	4.5	3.5	6.3	4.7	3.6	6.5	4.8	225
230	4.8	4		5.3	4.2	3.4	5.7	4.4	3.5	6.1	4.5	3.5	6.3	4.7	230
235	4.6	3.9		5.1	4.1	3.4	5.5	4.3	3.5	5.9	4.5	3.5	6.1	4.5	235
240	4.5	3.9		4.9	4		5.3	4.2	3.4	5.7	4.4	3.5	6	4.4	240
245	4.3	3.8		4.7	3.9		5.2	4.1	3.4	5.5	4.3	3.4	5.8	4.3	245
250	4.1	3.7		4.6	3.9		5	4		5.4	4.2	3.4	5.6	4.3	250
255	4	3.6		4.4	3.8		4.8	3.9		5.2	4.1	3.4	5.4	4.2	255
260	3.8			4.3	3.7		4.6	3.8		5	4		5.2	4.1	260
265	3.7			4.1	3.6		4.5	3.8		4.9	3.9		5.1	4	265
270				3.9			4.3	3.7		4.7	3.8		4.9	3.9	270
275				3.6			4.2	3.6		4.5	3.8		4.7	3.9	275
280							4	3.6		4.4	3.7		4.5	3.8	280
285							3.7			4.2	3.6		4.2	3.7	285
290							3.4			3.5	3.6		3.5	3.7	290
295										2.8	3.5			3.4	295
300											3.5				300
305											2.6				305

* adapter · pièce d'adaptateur

t_180_61701_00_000 / 61721_00_000 / 61741_00_000

Lifting capacities Forces de levage


TYVEF

132 – 198 ft T Y 11.5 ft V E 138 ft F 360° 220500 lbs 85%															
ft	132 + 20 ft*			149 + 20 ft*			165 + 20 ft*			182 + 20 ft*			198 + 20 ft*		ft
	138 ft			138 ft			138 ft			138 ft			138 ft		
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	
50	22.4														50
55	21.3			21.1											55
60	20.3			20.2			20.2			19.9					60
65	19.3			19.3			19.4			19.3					65
70	18.5			18.5			18.6			18.5			18		70
75	17.7			17.7			17.8			17.8			17.3		75
80	16.9			17			17.1			17.1			16.7		80
85	16.1			16.3			16.4			16.4			16.1		85
90	15.5			15.6			15.8			15.9			15.6		90
95	14.8	10		15			15.2			15.3			15		95
100	14.2	9.6		14.5	9.7		14.6			14.7			14.5		100
105	13.6	9.2		13.9	9.3		14.1	9.5		14.2			14.1		105
110	13.1	8.9		13.3	9		13.6	9.1		13.8	9.2		13.6		110
115	12.6	8.5		12.8	8.7		13.1	8.8		13.3	8.9		13.1	8.8	115
120	12.1	8.2		12.4	8.3		12.6	8.5		12.8	8.6		12.7	8.5	120
125	11.6	7.9		11.9	8		12.2	8.2		12.4	8.3		12.3	8.3	125
130	11.1	7.5		11.5	7.7		11.8	7.9		12	8		11.9	8	130
135	10.7	7.3	5.1	11.1	7.4	5.1	11.4	7.6		11.6	7.7		11.6	7.7	135
140	10.2	7	5	10.7	7.2	5	11	7.4	5	11.2	7.5		11.2	7.5	140
145	9.7	6.8	4.8	10.3	7	4.9	10.6	7.1	4.9	10.9	7.3	4.9	10.9	7.2	145
150	9.3	6.5	4.7	9.9	6.7	4.7	10.3	6.9	4.8	10.5	7	4.8	10.5	7	150
155	8.9	6.3	4.6	9.4	6.5	4.6	9.9	6.7	4.7	10.2	6.8	4.7	10.2	6.9	155
160	8.5	6.1	4.5	9	6.3	4.5	9.5	6.5	4.6	9.8	6.6	4.6	9.9	6.7	160
165	8.2	5.9	4.3	8.7	6.1	4.4	9.2	6.3	4.4	9.5	6.4	4.5	9.6	6.5	165
170	7.8	5.7	4.2	8.3	5.9	4.3	8.8	6.1	4.3	9.2	6.3	4.4	9.3	6.3	170
175	7.4	5.5	4.1	8	5.7	4.2	8.5	5.9	4.3	8.9	6.1	4.3	9	6.1	175
180	7.2	5.4	4	7.7	5.6	4.1	8.2	5.8	4.2	8.6	5.9	4.2	8.7	6	180
185	6.9	5.2	3.9	7.4	5.4	4	7.9	5.6	4.1	8.3	5.7	4.1	8.5	5.8	185
190	6.6	5.1	3.9	7.1	5.2	3.9	7.6	5.4	4	8	5.6	4.1	8.2	5.7	190
195	6.4	4.9	3.8	6.8	5.1	3.8	7.3	5.3	3.9	7.7	5.4	4	7.9	5.5	195
200	6.1	4.7	3.7	6.6	5	3.8	7	5.1	3.8	7.5	5.3	3.9	7.6	5.4	200
205	5.8	4.6	3.6	6.4	4.8	3.7	6.8	5	3.8	7.2	5.2	3.8	7.4	5.3	205
210	5.6	4.5	3.6	6.1	4.7	3.6	6.6	4.9	3.7	6.9	5	3.8	7.1	5.1	210
215	5.4	4.4	3.5	5.9	4.6	3.6	6.4	4.7	3.6	6.7	4.9	3.7	6.9	5	215
220	5.2	4.2	3.5	5.7	4.4	3.5	6.1	4.6	3.6	6.5	4.8	3.7	6.6	4.9	220
225	5	4.1	3.4	5.5	4.3	3.5	5.9	4.5	3.5	6.2	4.7	3.6	6.4	4.8	225
230	4.8	4		5.3	4.2	3.4	5.7	4.4	3.5	6	4.5	3.5	6	4.7	230
235	4.6	3.9		5.1	4.1	3.4	5.4	4.3	3.5	5.8	4.5	3.5	5.4	4.5	235
240	4.5	3.9		4.9	4		5.3	4.2	3.4	5.6	4.4	3.5	4.8	4.4	240
245	4.3	3.8		4.7	3.9		5.1	4.1	3.4	5.2	4.3	3.4	4.2	4.3	245
250	4.1	3.7		4.5	3.9		4.9	4		4.7	4.2	3.4	3.5	4.2	250
255	4	3.6		4.2	3.8		4.7	3.9		4.2	4	3.4	2.9	4.1	255
260	3.8			3.6	3.7		4.5	3.8		3.7	4			3.6	260
265	3.7			2.9	3.6		4.2	3.8		3.1	3.9			2.9	265
270							3.9	3.7		2.5	3.6				270
275							3.4	3.6			3				275
280							2.8	3.6							280

G

* adapter · pièce d'adaptateur


t_180_61705_00_000 / 61725_00_000 / 61745_00_000



US2343.01

Lifting capacities Forces de levage

TYF



	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	20 ft				20 ft				20 ft				20 ft				20 ft				20 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
32	88.4				81.4																				32
34	88.4				81.3																				34
36	88.3				81.2																				36
38	88	76.4		53.4	81	76.8			69.9																38
40	87.7	75.6	59.4	53.4	80.7	76.3	59.8		70.8																40
45	86.8	73.2	58.6	53.2	79.9	74.6	59.1	53.2	72.3	71.2			59.6												45
50	85.8	70.7	57.8	53	79.1	72.5	58.2	53.1	72.5	68.9	57.2	52.1	62		51.6		45.2								50
55	84.3	68.1	57	52.8	78.4	70.4	57.5	52.9	72.2	66.5	56	51.5	63.4	64.3	51.1	50.6	47.8	50.3			35.6				55
60	82	65.6	56.3		77.7	68.3	56.8		71.6	64.3	54.7	50.7	64.4	63.6	54.1	50.1	50.7	52.7	52.7		37.3	40.2			60
65	78	63.3	55.2		76.9	66.1	56.2		70.3	62.3	53.5	50	63.5	61.6	52.9	49.3	51.8	52.8	51.6	48.4	39.7	42.2	41.5	39.4	65
70	74.5	61.2	54		75.6	63.9	55.4		69	60.4	52.3		62.4	59.7	51.8	48.6	51.3	51.7	50.5	47.7	41	42.5	40.5	38.7	70
75	71.2	59.2	52.8		73.9	62	54.5		67.7	58.7	51.3		61.1	58.1	50.7		50.4	50.5	49.4	47	41.3	41.9	39.4	37.9	75
80	68.2	57.4	51.7		71.9	60.1	53.4		66.1	57	50.3		59.5	56.4	49.7		49.3	49.3	48.4		40.7	40.8	38.4	37.1	80
85	65.4	55.7	50.7		69.6	58.4	52.4		64.4	55.5	49.4		58	54.9	48.8		48.1	48	47.4		39.9	39.6	37.4	36.4	85
90	62.8	54.2	49.8		65	56.8	51.5		62.5	54.1	48.5		56.5	53.6	47.9		47	46.9	46.6		38.9	38.4	36.5		90
95	59.7	52.8	49		60.3	55.4	50.6		59.8	52.8	47.7		55	52.3	47.1		45.8	45.8	45.7		37.9	37.3	35.5		95
100	55.9	51.5			55.8	54	49.8		56.2	51.5	47		53.5	51	46.3		44.8	44.7	44.9		37	36.1	34.6		100
105	51.8	50.3			51.6	52.6	49.1		52.2	50.3	46.4		51.6	49.9	45.6		43.7	43.7	44		36.1	35.1	33.6		105
110	48.1	48.6			48	49.2	48.3		48.6	48.5	45.8		48.7	47.7	45		42.8	42.8	43.2		35.1	34.1	32.8		110
115	44.7	45.8			44.6	45.9			45.8	46	45		45.7	45.7	44.1		41.8	41.9	42.3		34.3	33.1	31.9		115
120	41.5	42.5			41.4	42.6			43.7	43.1			43	43.6	42.9		40.4	40.8	41.3		33.5	32.2	31.1		120
125	38.4	39.4			38.3	39.5			41.9	40.1			41	40.9	41.1		38.3	39.4	40		32.7	31.3	30.4		125
130	35.5	36.4			35.5	36.6			39.5	38.3			38.6	38.1	38.6		35.8	36.9	37.7		31.9	30.5	29.7		130
135	32.3				32.9	33.9			37	36.9			36.1	36.2			34.2	34.5	35.2		31.2	29.7	29		135
140	27.9				30.4	31.3			34.6	35.2			33.7	34.3			32.6	32.4			30.3	29	28.4		140
150	12.9				25.6				30.1	30.8			29.3	30.1			28.7	29.5			27.6	27.7	27.2		150
160					16.6				26.2				25.5	26.1			24.9	25.8			23.9	24.7			160
170									20.8				22.1	22.6			21.5	22.3			20.5	21.2			170
180													18.4				18.5	19.2			17.5	18.1			180
190													12.3				15.8	16.4			14.8	15.3			190
200																	11.4				12.3	12.8			200
210																					9.4				210
220																					4.7				220

* adapter · pièce d'adaptateur

t_180_18101_00_000 / 18121_00_000 / 18141_00_000 / 18164_00_000

H

Lifting capacities Forces de levage

TYF

		 132 – 215 ft T				 15° Y				 20 ft F				 360°				 220500 lbs				 85%				 15° Y					
 ft	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				 ft						
	20 ft				20 ft				20 ft				20 ft				20 ft				20 ft										
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°							
28	88.3																								28						
30	88.4				81.4																				30						
32	88.4	77.9			81.4																				32						
34	88.4	77.5			81.3																				34						
36	88.3	77	60.4		81.2	77.2																			36						
38	88	76.4	60	53.4	81	76.8			69.9																38						
40	87.7	75.6	59.6	53.4	80.7	76.3	59.9		70.8																40						
45	86.8	73.2	58.6	53.2	79.9	74.6	59.1	53.2	72.3	71.2			60.1												45						
50	85.8	70.7	57.8	53	79.1	72.5	58.2	53.1	72.5	68.9	57.2	52.1	62		51.6		45.2								50						
55	84.3	68.1	57	52.8	78.4	70.4	57.5	52.9	72.2	66.5	56	51.5	63.4	64.3	51.1	50.6	47.8	50.3			35.6				55						
60	82	65.6	56.3		77.7	68.3	56.8		71.6	64.3	54.7	50.7	64.4	63.6	54.1	50.1	50.7	52.7	52.7		37.3	40.2			60						
65	78	63.3	55.2		76.9	66.1	56.2		70.3	62.3	53.5	50	63.5	61.6	52.9	49.3	51.8	52.8	51.6	48.4	39.7	42.2	41.5	39.4	65						
70	74.5	61.2	54		74.8	63.9	55.4		69	60.4	52.3		62.4	59.7	51.8	48.6	51.3	51.7	50.5	47.7	41	42.5	40.5	38.7	70						
75	71	59.2	52.8		70.9	62	54.5		67.1	58.7	51.3		61	58.1	50.7		50.4	50.5	49.4	47	41.3	41.9	39.4	37.9	75						
80	66.9	57.4	51.7		65.7	60.1	53.4		64.1	57	50.3		59.1	56.4	49.7		49.3	49.3	48.4		40.7	40.8	38.4	37.1	80						
85	61.2	55.7	50.7		60.1	58.4	52.4		59.2	55.5	49.4		56.8	54.9	48.8		48.1	48	47.4		39.9	39.6	37.4	36.4	85						
90	55.9	54.2	49.8		55.2	56.2	51.5		54.5	53.6	48.5		53.5	52.5	47.9		47	46.9	46.6		38.9	38.4	36.5		90						
95	51.1	51.7	49		50.7	52.6	50.5		51.5	51	47.6		50.2	50	47.1		45.5	45.6	45.7		37.9	37.3	35.5		95						
100	46.6	48.2			46.4	48.2	48.7		49.1	47.7	46.4		47	47.1	46		43.6	43.9	44.5		37	36.1	34.6		100						
105	42.5	44			42.4	44	44.9		46	43.9	44.8		44	43.7	44.4		40.7	41.6	42.5		36.1	35.1	33.6		105						
110	38.9	40.2			38.8	40.3	41.1		42.6	41.7	41.4		40.8	40.7	41.3		38.6	38.4	39.5		35.1	34.1	32.8		110						
115	35.5	36.8			35.4	36.8			39.4	39.7	39.2		37.8	38.4	38.3		36.1	36.1	36.5		33.5	33	31.9		115						
120	32.4	33.6			32.4	33.7			36.4	37.4			35	36.1	35.9		33.4	34.3	34.2		31.5	31.9	31.1		120						
125	29.6	30.6			29.5	30.7			33.5	34.5			32.5	33.5	34.3		30.9	32.4	32.8		29.2	30.4	30.3		125						
130	27	27.9			27	28.1			31	31.9			30.1	31.1	31.7		28.7	30.1	30.7		27	28.1	28.8		130						
135	24.6				24.6	25.6			28.6	29.4			27.8	28.7			26.5	27.9	28.5		24.9	26	26.8		135						
140	22.3				22.4	23.3			26.4	27.1			25.6	26.4			24.6	25.8			23	24	24.7		140						
150	12.6				18.4				22.4	23			21.6	22.4			20.9	22			19.4	20.3	20.9		150						
160					14.3				19				18.2	18.8			17.6	18.5			16.3	17.1			160						
170									15.9				15.2	15.7			14.6	15.4			13.5	14.2			170						
180													12.5				11.9	12.6			10.9	11.5			180						
190													10				9.4	10			8.3	8.9			190						
200																	7.1				6.1	6.5			200						
210																					4				210						

* adapter · pièce d'adaptateur

t_180_18105_00_000 / 18125_00_000 / 18145_00_000 / 18165_00_000

Lifting capacities Forces de levage

TYF

																									
 ft	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				 ft
	39 ft				39 ft				39 ft				39 ft				39 ft				39 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
36	70.7				67.3																				36
38	69.6				67																				38
40	68.4				66.7				60.4																40
45	65.1	42.6			65	43.1			60.5				47												45
50	61.6	41.4			62.6	41.9			59.9	41.9			49.5												50
55	58.4	40			60.1	40.7			58.9	41.1			51.3	40.7			37.4				28.3				55
60	55.5	38.7	30.8	23.7	57.6	39.4	30.9		57.2	39.9			52.4	40.3			39.5				29.4				60
65	52.6	37.5	30.3	23.5	55	38.3	30.4	23.5	55.4	38.8	30.5	23.5	51.7	39.3	30.6		40.6	37.7			31.2				65
70	50.3	36.4	29.8	23.3	52.6	37.2	30	23.3	53.5	37.8	30.1	23.4	50.5	38.3	30.4	23.2	41.6	36.8			32.4	31.2			70
75	48.1	35.4	29.3	23.1	50.3	36.3	29.5	23.2	51.5	36.8	29.7	23.2	49.2	37.4	30.2	23.1	42	35.7	28.1	22.9	32.9	30.4	25.5		75
80	45.9	34.5	28.9		48.3	35.3	29.2		49.6	35.9	29.3	23	47.8	36.6	29.8	23	41.6	34.7	29	22.8	32.7	29.5	25.2		80
85	44	33.6	28.5		46.3	34.4	28.8		47.8	35.1	28.9	22.9	46.5	35.8	29.4	22.8	40.9	33.8	28.4	22.7	32.3	28.6	24.6	23.2	85
90	42	32.8	28.2		44.6	33.7	28.5		46.1	34.3	28.6		45.1	34.9	29.1	22.7	40.1	32.9	27.9	22.6	31.6	27.8	24.1	22.8	90
95	40.3	32.1	28		43	32.9	28.2		44.5	33.5	28.3		43.6	34.1	28.7		39.2	32.1	27.4	22.6	30.8	27	23.5	22.5	95
100	38.8	31.4	27.7		41.4	32.2	27.9		43	32.8	28		42.1	33.2	28.4		38.2	31.3	26.9		30	26.2	23	22.2	100
105	37.3	30.8	27.6		40	31.6	27.7		41.6	32.2	27.8		40.6	32.4	27.9		37.3	30.5	26.5		29.2	25.5	22.5		105
110	35.9	30.1	27.3		38.7	31	27.5		40.3	31.6	27.6		39.3	31.7	27.5		36.5	29.8	26.1		28.4	24.9	22.1		110
115	34.7	29.5	27.1		37.4	30.5	27.3		39	31	27.4		38.1	30.9	27.1		35.6	29.1	25.7		27.7	24.3	21.7		115
120	33.5	28.8			36.3	29.9	27.2		37.8	30.5	27.2		36.9	30.3	26.8		34.7	28.5	25.3		27	23.7	21.3		120
125	32.4	28.2			35.2	29.5	27		36.7	30	27		35.7	29.6	26.4		33.7	27.9	25		26.3	23.1	20.9		125
130	31.4	27.7			34.2	29	26.9		35.4	29.6	26.9		34.7	29	26.1		32.8	27.3	24.7		25.7	22.5	20.6		130
135	30.5	27.2			33.2	28.6			33.9	29.1	26.7		33.3	28.5	25.8		31.9	26.8	24.4		25.1	22	20.2		135
140	29.6	26.8			32	28.2			32.3	28.7			31.9	28	25.6		30.9	26.3	24.1		24.4	21.5	19.9		140
150	28.2	26.1			28.3	27.4			28.6	27.8			28.9	27	25.2		27.8	25.4	23.6		23.3	20.6	19.3		150
160	21.3				24.5	25.6			27	25.7			25.6	25.6			24.3	24.6			22.2	19.8	18.8		160
170					20				24.4	24			23.3	23.3			22.4	22.2			21	19.1	18.3		170
180					11.9				21.1				20.4	21.3			19.9	19.7			18.6	18.4			180
190									15.9				17.7	18.7			17.2	18.2			15.9	17.1			190
200													14.1				14.7	15.6			13.5	14.5			200
210													8.5				12.4				11.2	12.2			210
220																	8.1				9.2	10			220
230																					6.1				230


* adapter · pièce d'adaptateur

t_180_18201_00_000 / 18221_00_000 / 18241_00_000 / 18264_00_000

H

Lifting capacities Forces de levage

TYF



	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	39 ft				39 ft				39 ft				39 ft				39 ft				39 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
28	72.5																								28
30	72.4																								30
32	72.2																								32
34	71.6				67.3																				34
36	70.7				67.3																				36
38	69.6				67				57.8																38
40	68.4	44			66.7				60.4																40
45	65.1	42.9			65	43.1			60.5				47												45
50	61.6	41.4	31.8		62.6	41.9			59.9	41.9			49.5												50
55	58.4	40	31.4		60.1	40.7	31.3		58.9	41.1			51.3	40.7			37.4				28.3				55
60	55.5	38.7	30.8	23.7	57.6	39.4	30.9		57.2	39.9			52.4	40.3			39.5				29.4				60
65	52.6	37.5	30.3	23.5	55	38.3	30.4	23.5	55.4	38.8	30.5	23.5	51.7	39.3	30.6		40.6	37.7			31.2				65
70	50.3	36.4	29.8	23.3	52.6	37.2	30	23.3	53.5	37.8	30.1	23.4	50.5	38.3	30.4	23.2	41.6	36.8			32.4	31.2			70
75	48.1	35.4	29.3	23.1	50.3	36.3	29.5	23.2	51.5	36.8	29.7	23.2	49.2	37.4	30.2	23.1	42	35.7	28.1	22.9	32.9	30.4	25.5		75
80	45.9	34.5	28.9		48.3	35.3	29.2		49.6	35.9	29.3	23	47.8	36.6	29.8	23	41.6	34.7	29	22.8	32.7	29.5	25.2		80
85	44	33.6	28.5		46.3	34.4	28.8		47.8	35.1	28.9	22.9	46.5	35.8	29.4	22.8	40.9	33.8	28.4	22.7	32.3	28.6	24.6	23.2	85
90	42	32.8	28.2		44.6	33.7	28.5		46.1	34.3	28.6		45.1	34.9	29.1	22.7	40.1	32.9	27.9	22.6	31.6	27.8	24.1	22.8	90
95	40.3	32.1	28		43	32.9	28.2		44.5	33.5	28.3		43.6	34.1	28.7		39.2	32.1	27.4	22.6	30.8	27	23.5	22.5	95
100	38.8	31.4	27.7		41.4	32.2	27.9		42.9	32.8	28		42	33.2	28.4		38.2	31.3	26.9		30	26.2	23	22.2	100
105	37.3	30.8	27.6		40	31.6	27.7		41.3	32.2	27.8		40.2	32.4	27.9		37.3	30.5	26.5		29.2	25.5	22.5		105
110	35.9	30.1	27.3		38.6	31	27.5		39.2	31.6	27.6		38.1	31.7	27.5		36	29.8	26.1		28.4	24.9	22.1		110
115	34.7	29.5	27.1		36.9	30.5	27.3		36.7	31	27.4		36	30.9	27.1		34.1	29.1	25.7		27.7	24.3	21.7		115
120	33.4	28.8			34.6	29.9	27.2		34.4	30.5	27.2		33.6	30.3	26.8		31.8	28.5	25.3		27	23.7	21.3		120
125	32	28.2			31.8	29.5	27		32.7	30	27		31.3	29.6	26.4		29.4	27.9	25		26.3	23.1	20.9		125
130	29.6	27.7			29.3	29	26.9		31.5	29.2	26.9		30	28.7	26.1		28	27.3	24.7		25.6	22.5	20.6		130
135	27.3	27.2			26.9	28			29.8	28.2	26.7		28.3	27.7	25.8		26.7	26.5	24.4		24.6	22	20.2		135
140	25.1	26.1			24.7	26.4			27.9	27.1			26.5	26.5	25.4		25.2	25.1	24.1		23.3	21.5	19.9		140
150	21.1	22.2			20.7	22.1			23.9	24.9			22.8	23.9	23.9		21.8	22	22.6		19.9	20.6	19.3		150
160	17.5				17.3	18.4			20.5	21.7			19.5	21.1			18.7	20.1			16.9	18.5	18.6		160
170					14.2				17.4	18.4			16.5	17.9			15.9	17.3			14.2	15.6	16.6		170
180					10.5				14.7				13.8	15			13.3	14.5			11.7	13.1			180
190									12.3				11.4	12.5			10.9	12			9.5	10.7			190
200													9.3				8.7	9.6			7.4	8.5			200
210													7.2				6.6				5.3	6.3			210
220																	4.8				3.5	4.3			220

* adapter · pièce d'adaptateur

t_180_18205_00_000 / 18225_00_000 / 18245_00_000 / 18265_00_000

H

Lifting capacities Forces de levage

TYF

ft	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				ft	
	59 ft				59 ft				59 ft				59 ft				59 ft				59 ft					
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°		
38	50.5				50																				38	
40	49.6				49.4				46.9																	40
45	47.2				47.5				46.4																	45
50	45				45.6				44.9				41.4													50
55	42.7	28.8			43.7	28.5			43.4				41.8				30.7									55
60	40.6	27.7			41.8	28			41.9				41.3				31.9				21.6					60
65	38.7	26.7			40	27.1			40.4	27.4			40.1	27.6			32.8				22.1					65
70	36.8	25.8	20.2		38.3	26.3	20		38.8	26.6			38.8	26.9			33.6	25.8			22.7					70
75	35.1	25	19.8	13.5	36.6	25.5	19.8		37.4	25.9	19.8		37.5	26.1	19.7		33.9	25.3			23.6	22.7				75
80	33.5	24.2	19.4	13.4	35	24.8	19.4		36	25.1	19.5		36.3	25.4	19.6		33.6	24.8			24.6	22.4				80
85	32	23.5	18.9	13.3	33.6	24.1	19	13.3	34.6	24.5	19.1	13.3	35.1	24.8	19.2		32.9	24.2	19.4		25.3	21.8				85
90	30.7	22.9	18.5	13.2	32.3	23.4	18.6	13.2	33.3	23.8	18.8	13.2	33.9	24.2	18.9	13.1	32.1	23.6	19	13.6	25.6	21.1	17.4			90
95	29.5	22.3	18.2	13.1	31	22.8	18.3	13.1	32.1	23.2	18.5	13.1	32.8	23.6	18.6	13	31.3	23.1	18.6	13.5	25.4	20.5	17.1	13.4		95
100	28.3	21.7	17.8		29.9	22.3	18		30.9	22.7	18.2	13	31.7	23.1	18.3	12.9	30.4	22.6	18.2	13.4	24.9	20	16.7	13.3		100
105	27.2	21.1	17.6		28.8	21.7	17.7		29.8	22.2	17.9		30.7	22.6	18	12.8	29.6	22.1	17.8	13.3	24.2	19.4	16.4	13.3		105
110	26.3	20.6	17.3		27.7	21.2	17.5		28.8	21.7	17.6		29.7	22	17.8	12.8	28.7	21.6	17.5	13.3	23.5	18.9	16.1	13.2		110
115	25.3	20.1	17		26.8	20.7	17.2		27.9	21.2	17.4		28.7	21.6	17.5		27.9	21.2	17.3	13.3	22.8	18.4	15.8	13.2		115
120	24.4	19.6	16.8		25.9	20.2	17		27	20.7	17.1		27.9	21.1	17.3		27	20.7	17.1		22.1	17.9	15.5			120
125	23.6	19.1	16.6		25	19.8	16.8		26.1	20.2	16.9		27	20.7	17.1		26.2	20.3	16.9		21.5	17.5	15.2			125
130	22.9	18.7	16.5		24.2	19.3	16.6		25.3	19.8	16.7		26.2	20.2	16.9		25.4	19.9	16.7		20.9	17	14.9			130
135	22.2	18.3	16.3		23.5	18.9	16.5		24.6	19.4	16.6		25.5	19.8	16.7		24.7	19.5	16.5		20.2	16.6	14.6			135
140	21.5	18			22.8	18.5	16.3		23.9	19	16.4		24.8	19.4	16.6		24	19.2	16.4		19.7	16.2	14.4			140
150	20.2	17.3			21.5	17.8	16.1		22.6	18.3	16.2		23.5	18.7	16.3		22.6	18.4	16.1		18.5	15.5	13.9			150
160	19	16.9			20.3	17.3			21.3	17.7			22.3	18.1	16.1		21.4	17.8	15.9		17.5	14.9	13.5			160
170	17.9	16.5			19.2	16.8			20.2	17.2			21.1	17.5	15.9		20.3	17.2	15.7		16.6	14.3	13.2			170
180	15.5				18.2	16.5			19.2	16.7			19.7	17.1			18.8	16.6			15.7	13.7	12.8			180
190					15.5				17.7	16.4			17.6	16.7			16.3	16.2			15	13.2	12.5			190
200					8.5				16.4				16.4	16.1			15.3	15.2			14.2	12.8				200
210									12.1				14.4				13.6	13.8			12.6	12.4				210
220													10.7				11.6	12.8			10.6	11.7				220
230																	9				8.7	9.9				230
240																	5.3				6.6	8				240


* adapter · pièce d'adaptateur

t_180_18301_00_000 / 18321_00_000 / 18341_00_000 / 18363_00_000

H

Lifting capacities Forces de levage

TYF



	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	59 ft				59 ft				59 ft				59 ft				59 ft				59 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
36	51.4																								36
38	50.5				50																				38
40	49.6				49.4				46.9																40
45	47.2				47.5				46.4																45
50	45	29.4			45.6				44.9				41.4												50
55	42.7	28.8			43.7	28.5			43.4				41.8				30.7								55
60	40.6	27.7			41.8	28			41.9				41.3				31.9				21.6				60
65	38.7	26.7			40	27.1			40.4	27.4			40.1	27.6			32.8				22.1				65
70	36.8	25.8	20.2		38.3	26.3	20		38.8	26.6			38.8	26.9			33.6	25.8			22.7				70
75	35.1	25	19.8	13.5	36.6	25.5	19.8		37.4	25.9	19.8		37.5	26.1	19.7		33.9	25.3			23.6	22.7			75
80	33.5	24.2	19.4	13.4	35	24.8	19.4		36	25.1	19.5		36.3	25.4	19.6		33.6	24.8			24.6	22.4			80
85	32	23.5	18.9	13.3	33.6	24.1	19	13.3	34.6	24.5	19.1	13.3	35.1	24.8	19.2		32.9	24.2	19.4		25.3	21.8			85
90	30.7	22.9	18.5	13.2	32.3	23.4	18.6	13.2	33.3	23.8	18.8	13.2	33.9	24.2	18.9	13.1	32.1	23.6	19	13.6	25.6	21.1	17.4		90
95	29.5	22.3	18.2	13.1	31	22.8	18.3	13.1	32.1	23.2	18.5	13.1	32.8	23.6	18.6	13	31.3	23.1	18.6	13.5	25.4	20.5	17.1	13.4	95
100	28.3	21.7	17.8		29.9	22.3	18		30.9	22.7	18.2	13	31.7	23.1	18.3	12.9	30.4	22.6	18.2	13.4	24.9	20	16.7	13.3	100
105	27.2	21.1	17.6		28.8	21.7	17.7		29.8	22.2	17.9		30.7	22.6	18	12.8	29.6	22.1	17.8	13.3	24.2	19.4	16.4	13.3	105
110	26.3	20.6	17.3		27.7	21.2	17.5		28.8	21.7	17.6		29.7	22	17.8	12.8	28.7	21.6	17.5	13.3	23.5	18.9	16.1	13.2	110
115	25.3	20.1	17		26.8	20.7	17.2		27.9	21.2	17.4		28.7	21.6	17.5		27.9	21.2	17.3	13.3	22.8	18.4	15.8	13.2	115
120	24.4	19.6	16.8		25.9	20.2	17		27	20.7	17.1		27.9	21.1	17.3		27	20.7	17.1		22.1	17.9	15.5		120
125	23.6	19.1	16.6		25	19.8	16.8		26.1	20.2	16.9		27	20.7	17.1		26.2	20.3	16.9		21.5	17.5	15.2		125
130	22.9	18.7	16.5		24.2	19.3	16.6		25.3	19.8	16.7		26.2	20.2	16.9		25.4	19.9	16.7		20.9	17	14.9		130
135	22.2	18.3	16.3		23.5	18.9	16.5		24.6	19.4	16.6		25.3	19.8	16.7		24.7	19.5	16.5		20.2	16.6	14.6		135
140	21.5	18			22.8	18.5	16.3		23.8	19	16.4		24.4	19.4	16.6		23.5	19.2	16.4		19.7	16.2	14.4		140
150	20.2	17.3			21.5	17.8	16.1		22.1	18.3	16.2		22.1	18.7	16.3		20.2	18.4	16.1		18.5	15.5	13.9		150
160	18.9	16.9			19.3	17.3			20.4	17.7			20.1	18.1	16.1		18.6	17.8	15.9		17.2	14.9	13.5		160
170	16.7	16.5			16.2	16.8			18.8	17.2			17.8	17.4	15.9		16.5	16.6	15.7		15	14.3	13.2		170
180	13.8				13.5	14.9			16.2	16.5			15.2	16.1			14.1	15			12.7	13.7	12.8		180
190					11.1				13.8	15			12.8	14.3			11.9	13.8			10.5	12.3	12.5		190
200					7.6				11.6				10.7	11.9			9.9	11.6			8.6	10.2			200
210									9.7				8.7				7.9	9.5			6.7	8.3			210
220													6.9				6	7.5			4.9	6.3			220
230																	4.3				4.4				230

* adapter · pièce d'adaptateur

t_180_18305_00_000 / 18325_00_000 / 18345_00_000 / 18365_00_000

Lifting capacities Forces de levage

TYF

132 – 215 ft T 15° Y 79 ft F 360° 308600 lbs 85% 15° Y																									
ft	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				ft
	79 ft				79 ft				79 ft				79 ft				79 ft				79 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
40	37.9				37.8																			40	
45	36.3				36.6				35.9															45	
50	34.7				35.1				34.9				33.2											50	
55	33.1				33.7				33.7				33.2				23.8							55	
60	31.6				32.3				32.4				32.4				24.4				17.7			60	
65	30.1	21			31.1				31.2				31.3				25.1				18			65	
70	28.9	20.3			29.9	20.3			30.1	20.3			30.3				25.9				18.4			70	
75	27.6	19.5			28.7	19.7			29.1	19.9			29.3	20.2			26.5	18.9			19.2			75	
80	26.4	18.8			27.6	19			28	19.2			28.4	19.7			26.7	18.8			20			80	
85	25.2	18.1	13.6		26.5	18.3			27	18.6			27.4	19.1			26.1	18.5			20.7			85	
90	24.2	17.5	13.3		25.4	17.8	13.3		26.1	18	13.3		26.6	18.5			25.4	18			20.7	16.8		90	
95	23.1	16.9	13	8.4	24.4	17.2	13.1		25.1	17.5	13.1		25.7	17.9	13.3		24.7	17.5	12.8		20.5	16.3		95	
100	22.2	16.3	12.7	8.4	23.5	16.7	12.8	8.4	24.2	17	12.9	8.3	24.9	17.4	13	8.3	23.9	17	12.7		20.2	15.8		100	
105	21.3	15.7	12.4	8.3	22.6	16.2	12.5	8.3	23.3	16.5	12.6	8.3	24.1	16.9	12.8	8.3	23.2	16.6	12.6		19.7	15.3		105	
110	20.4	15.3	12.1	8.2	21.7	15.7	12.3	8.2	22.5	16	12.4	8.2	23.3	16.5	12.6	8.2	22.5	16.2	12.4	8.1	19.1	14.9	12		110
115	19.6	14.8	11.9	8.1	20.9	15.2	12	8.1	21.7	15.6	12.1	8.1	22.5	16	12.3	8.1	21.9	15.8	12.2	8.1	18.5	14.5	11.8	7.9	115
120	18.8	14.4	11.6		20.1	14.8	11.8		20.9	15.2	11.9	8.1	21.8	15.6	12.1	8.1	21.2	15.4	12	8	18	14.1	11.6	7.9	120
125	18.1	13.9	11.4		19.3	14.4	11.6		20.2	14.8	11.7		21.1	15.2	11.9	8	20.6	15	11.8	8	17.4	13.7	11.4	7.9	125
130	17.4	13.6	11.2		18.6	14	11.4		19.5	14.4	11.6		20.4	14.9	11.8	8	19.9	14.7	11.6	7.9	16.9	13.3	11.1	7.8	130
135	16.7	13.2	11.1		17.9	13.7	11.3		18.8	14.1	11.4		19.7	14.5	11.6		19.3	14.3	11.5	7.9	16.5	12.9	10.9	7.8	135
140	16.1	12.9	10.9		17.3	13.3	11.1		18.1	13.7	11.2		19	14.2	11.4		18.8	14	11.3		16	12.6	10.7		140
150	15	12.3	10.7		16.2	12.7	10.8		17	13.1	10.9		17.9	13.5	11.1		17.7	13.4	11		15.1	12	10.3		150
160	14	11.8			15.1	12.2	10.6		15.9	12.5	10.7		16.8	12.9	10.8		16.6	12.9	10.8		14.2	11.4	9.9		160
170	13.1	11.3			14.2	11.7	10.5		15	12.1	10.5		15.8	12.4	10.6		15.8	12.4	10.6		13.3	10.9	9.6		170
180	12.3	11			13.3	11.3			14.1	11.6			14.9	12	10.5		15	12	10.4		12.6	10.4	9.3		180
190	11.6	10.8			12.5	11			13.3	11.3			14.1	11.6	10.4		14.2	11.6	10.3		11.9	10	9.1		190
200	10.4				11.8	10.8			12.6	11			13.4	11.3			13.6	11.3			11.3	9.6	8.9		200
210					11.2				12	10.8			12.6	11			12.7	11			10.7	9.3			210
220					5.5				11.3				12	10.8			11.3	10.7			10.2	8.9			220
230									8.9				11.1				10.6	10.4			9.4	8.7			230
240													7.7				8.9	9.6			7.7	8.4			240
250																	6.3				6.1	7.5			250
260																					3.9	5.9			260


* adapter · pièce d'adaptateur

t_180_18401_00_000 / 18421_00_000 / 18441_00_000 / 18462_00_000

H

Lifting capacities Forces de levage

TYF



	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	79 ft				79 ft				79 ft				79 ft				79 ft				79 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
38	38.6																								38
40	38.1				37.8																				40
45	36.3				36.6				35.9																45
50	34.7				35.1				34.9				33.2												50
55	33.1				33.7				33.7				33.2				23.8								55
60	31.6				32.3				32.4				32.4				24.4				17.7				60
65	30.1	21			31.1				31.2				31.3				25.1				18				65
70	28.9	20.3			29.9	20.3			30.1	20.3			30.3				25.9				18.4				70
75	27.6	19.5			28.7	19.7			29.1	19.9			29.3	20.2			26.5	18.9			19.2				75
80	26.4	18.8			27.6	19			28	19.2			28.4	19.7			26.7	18.8			20				80
85	25.2	18.1	13.6		26.5	18.3			27	18.6			27.4	19.1			26.1	18.5			20.7				85
90	24.2	17.5	13.3		25.4	17.8	13.3		26.1	18	13.3		26.6	18.5			25.4	18			20.7	16.8			90
95	23.1	16.9	13	8.4	24.4	17.2	13.1		25.1	17.5	13.1		25.7	17.9	13.3		24.7	17.5	12.8		20.5	16.3			95
100	22.2	16.3	12.7	8.4	23.5	16.7	12.8	8.4	24.2	17	12.9	8.3	24.9	17.4	13	8.3	23.9	17	12.7		20.2	15.8			100
105	21.3	15.7	12.4	8.3	22.6	16.2	12.5	8.3	23.3	16.5	12.6	8.3	24.1	16.9	12.8	8.3	23.2	16.6	12.6		19.7	15.3			105
110	20.4	15.3	12.1	8.2	21.7	15.7	12.3	8.2	22.5	16	12.4	8.2	23.3	16.5	12.6	8.2	22.5	16.2	12.4	8.1	19.1	14.9	12		110
115	19.6	14.8	11.9	8.1	20.9	15.2	12	8.1	21.7	15.6	12.1	8.1	22.5	16	12.3	8.1	21.9	15.8	12.2	8.1	18.5	14.5	11.8	7.9	115
120	18.8	14.4	11.6		20.1	14.8	11.8		20.9	15.2	11.9	8.1	21.8	15.6	12.1	8.1	21.2	15.4	12	8	18	14.1	11.6	7.9	120
125	18.1	13.9	11.4		19.3	14.4	11.6		20.2	14.8	11.7		21.1	15.2	11.9	8	20.6	15	11.8	8	17.4	13.7	11.4	7.9	125
130	17.4	13.6	11.2		18.6	14	11.4		19.5	14.4	11.6		20.4	14.9	11.8	8	19.9	14.7	11.6	7.9	16.9	13.3	11.1	7.8	130
135	16.7	13.2	11.1		17.9	13.7	11.3		18.8	14.1	11.4		19.7	14.5	11.6		19.3	14.3	11.5	7.9	16.5	12.9	10.9	7.8	135
140	16.1	12.9	10.9		17.3	13.3	11.1		18.1	13.7	11.2		19	14.2	11.4		18.8	14	11.3		16	12.6	10.7		140
150	15	12.3	10.7		16.2	12.7	10.8		17	13.1	10.9		17.9	13.5	11.1		17.7	13.4	11		15.1	12	10.3		150
160	14	11.8			15.1	12.2	10.6		15.9	12.5	10.7		16.7	12.9	10.8		16.6	12.9	10.8		14.2	11.4	9.9		160
170	13.1	11.3			14.2	11.7	10.5		15	12.1	10.5		15.5	12.4	10.6		15.1	12.4	10.6		13.3	10.9	9.6		170
180	12.3	11			13.3	11.3			14.1	11.6			14.6	12	10.5		13.8	12	10.4		12.4	10.4	9.3		180
190	11.6	10.8			12.4	11			13	11.3			13.6	11.6	10.4		12.5	11.6	10.3		10.7	10	9.1		190
200	10.4				10.4	10.8			12.3	11			11.7	11.2			10.6	11			8.9	9.6	8.9		200
210					8.3				10.7	10.7			9.8	10.8			8.8	10.4			7.1	9.1			210
220					5.1				9				8	9.4			7.1	8.8			5.5	7.4			220
230									7.3				6.3				5.4	7			4	5.8			230
240													4.7				3.8	5.2				4.1			240

* adapter · pièce d'adaptateur

t_180_18405_00_000 / 18425_00_000 / 18445_00_000 / 18465_00_000

H

Lifting capacities Forces de levage

TYF

132 – 215 ft		15°		98 ft				360°		308600 lbs		85%		15°											
 ft	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				 ft
	98 ft				98 ft				98 ft				98 ft				98 ft				98 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
45	28.1				27.8				26.8				26.4											45	
50	26.9				26.9				26.8				25.9				19.1							50	
55	25.7				25.8				25.9				24.9				20.4							55	
60	24.5				24.8				25				24.9				20.8							60	
65	23.5				23.8				24				24.1				21.1							65	
70	22.5				22.9				23.1				23.2				21.6				14.9			70	
75	21.6	14.9			22	14.6			22.3				22.4				21.4				15.3			75	
80	20.6	14.5			21.2	14.4			21.5				21.7				20.8				15.8			80	
85	19.7	13.9			20.4	13.9			20.7	14.1			20.9	14.4			20.1				16.5			85	
90	18.8	13.4			19.6	13.4			20	13.6			20.2	13.9			19.5	13.5			16.6			90	
95	18	12.9			18.8	12.9			19.3	13.2			19.6	13.5			18.9	13.2			16.4	12.3		95	
100	17.3	12.4	9.1		18.1	12.5	9		18.7	12.8			19	13			18.4	12.8			16.2	12.1		100	
105	16.6	11.9	8.9		17.4	12.1	8.9		18	12.4			18.3	12.6			17.8	12.4			15.9	11.8		105	
110	15.9	11.5	8.6		16.7	11.7	8.7		17.4	12	8.7		17.8	12.3	8.8		17.3	12.1			15.5	11.5		110	
115	15.2	11.1	8.4	5.4	16.1	11.3	8.5	5.4	16.7	11.6	8.6		17.2	11.9	8.7		16.8	11.7	8.5		15	11.2		115	
120	14.6	10.7	8.2	5.4	15.5	11	8.3	5.4	16.1	11.3	8.4	5.3	16.7	11.5	8.5	5.3	16.3	11.4	8.4		14.6	10.9	8	120	
125	14	10.4	8	5.3	14.9	10.6	8.1	5.3	15.5	10.9	8.2	5.3	16.1	11.2	8.3	5.3	15.8	11.1	8.2		14.1	10.6	7.9	125	
130	13.4	10	7.8	5.3	14.3	10.3	7.9	5.3	15	10.6	8	5.3	15.6	10.9	8.1	5.3	15.3	10.8	8	5.2	13.7	10.3	7.8	130	
135	12.9	9.7	7.7		13.7	10	7.8	5.2	14.5	10.3	7.9	5.2	15.1	10.6	8	5.2	14.8	10.5	7.9	5.2	13.3	10	7.7	5.1	135
140	12.3	9.4	7.5		13.2	9.7	7.6		13.9	10	7.7	5.2	14.5	10.3	7.8	5.2	14.4	10.2	7.8	5.1	12.9	9.8	7.6	5.1	140
150	11.4	8.9	7.3		12.2	9.2	7.4		12.9	9.5	7.5		13.5	9.8	7.6	5.1	13.5	9.7	7.5	5.1	12.1	9.3	7.4	5	150
160	10.6	8.4	7.1		11.4	8.7	7.2		12	9	7.3		12.6	9.3	7.4		12.7	9.3	7.3		11.4	8.8	7.2		160
170	9.8	8	6.9		10.6	8.3	7		11.2	8.6	7.1		11.8	8.8	7.1		11.9	8.9	7.1		10.7	8.4	7		170
180	9.1	7.7			9.9	7.9	6.9		10.5	8.2	6.9		11.1	8.5	7		11.2	8.5	7		10.1	8	6.9		180
190	8.5	7.4			9.2	7.6			9.8	7.8	6.8		10.4	8.1	6.9		10.6	8.1	6.9		9.5	7.6	6.7		190
200	7.9	7.2			8.7	7.3			9.3	7.6			9.8	7.8	6.8		10	7.8	6.8		8.9	7.3	6.5		200
210	7.5				8.1	7.2			8.7	7.3			9.2	7.5			9.5	7.6	6.7		8.4	7	6.4		210
220	6.9				7.6	7			8.2	7.1			8.8	7.3			9	7.3			8	6.8	6.3		220
230					7.2				7.8	7			8.3	7.1			8.5	7.1			7.6	6.5			230
240									7.3				7.8	7			8	7			7.2	6.3			240
250									6.2				7.3				7.6	6.9			6.8	6.2			250
260													5.2				6.4	6.8			5.4	6			260
270																					3.8	5.5			270


* adapter · pièce d'adaptateur

t_180_18501_00_000 / 18521_00_000 / 18541_00_000 / 18561_00_000

H

Lifting capacities Forces de levage

TYF



H

	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	98 ft				98 ft				98 ft				98 ft				98 ft				98 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
40	29.1																								40
45	28.2				27.8																				45
50	26.9				26.9				26.8				26.4												50
55	25.7				25.8				25.9				25.9				19.1								55
60	24.5				24.8				25				24.9				20.4								60
65	23.5				23.8				24				24.1				21.1								65
70	22.5				22.9				23.1				23.2				21.6				14.9				70
75	21.6	14.9			22	14.6			22.3				22.4				21.4				15.3				75
80	20.6	14.5			21.2	14.4			21.5				21.7				20.8				15.8				80
85	19.7	13.9			20.4	13.9			20.7	14.1			20.9	14.4			20.1				16.5				85
90	18.8	13.4			19.6	13.4			20	13.6			20.2	13.9			19.5	13.5			16.6				90
95	18	12.9			18.8	12.9			19.3	13.2			19.6	13.5			18.9	13.2			16.4	12.3			95
100	17.3	12.4	9.1		18.1	12.5	9		18.7	12.8			19	13			18.4	12.8			16.2	12.1			100
105	16.6	11.9	8.9		17.4	12.1	8.9		18	12.4			18.3	12.6			17.8	12.4			15.9	11.8			105
110	15.9	11.5	8.6		16.7	11.7	8.7		17.4	12	8.7		17.8	12.3	8.8		17.3	12.1			15.5	11.5			110
115	15.2	11.1	8.4	5.4	16.1	11.3	8.5	5.4	16.7	11.6	8.6		17.2	11.9	8.7		16.8	11.7	8.5		15	11.2			115
120	14.6	10.7	8.2	5.4	15.5	11	8.3	5.4	16.1	11.3	8.4	5.3	16.7	11.5	8.5	5.3	16.3	11.4	8.4		14.6	10.9	8		120
125	14	10.4	8	5.3	14.9	10.6	8.1	5.3	15.5	10.9	8.2	5.3	16.1	11.2	8.3	5.3	15.8	11.1	8.2		14.1	10.6	7.9		125
130	13.4	10	7.8	5.3	14.3	10.3	7.9	5.3	15	10.6	8	5.3	15.6	10.9	8.1	5.3	15.3	10.8	8	5.2	13.7	10.3	7.8		130
135	12.9	9.7	7.7		13.7	10	7.8	5.2	14.5	10.3	7.9	5.2	15.1	10.6	8	5.2	14.8	10.5	7.9	5.2	13.3	10	7.7	5.1	135
140	12.3	9.4	7.5		13.2	9.7	7.6		13.9	10	7.7	5.2	14.5	10.3	7.8	5.2	14.4	10.2	7.8	5.1	12.9	9.8	7.6	5.1	140
150	11.4	8.9	7.3		12.2	9.2	7.4		12.9	9.5	7.5		13.5	9.8	7.6	5.1	13.5	9.7	7.5	5.1	12.1	9.3	7.4	5	150
160	10.6	8.4	7.1		11.4	8.7	7.2		12	9	7.3		12.6	9.3	7.4		12.7	9.3	7.3		11.4	8.8	7.2		160
170	9.8	8	6.9		10.6	8.3	7		11.2	8.6	7.1		11.8	8.8	7.1		11.9	8.9	7.1		10.7	8.4	7		170
180	9.1	7.7			9.9	7.9	6.9		10.5	8.2	6.9		11.1	8.5	7		11.2	8.5	7		10.1	8	6.9		180
190	8.5	7.4			9.2	7.6			9.8	7.8	6.8		10.4	8.1	6.9		10.6	8.1	6.9		9.5	7.6	6.7		190
200	7.9	7.2			8.7	7.3			9.3	7.6			9.7	7.8	6.8		9.7	7.8	6.8		8.8	7.3	6.5		200
210	7.5				8.1	7.2			8.7	7.3			9	7.5			9.1	7.6	6.7		7.4	7	6.4		210
220	6.9				7.5	7			8	7.1			8.4	7.3			7.5	7.3			5.9	6.8	6.3		220
230					6				7.6	7			7.2	7.1			6.1	7.1			4.5	6.3			230
240									6.7				5.6	6.8			4.7	6.4			3.1	5.2			240
250									5.2				4.2				5				3.7				250
260													2.9				3.4								260

* adapter · pièce d'adaptateur

t_180_18505_00_000 / 18525_00_000 / 18545_00_000 / 18565_00_000

Lifting capacities Forces de levage

TYF

132 – 215 ft		15°		118 ft				360°		308600 lbs		85%													
T		Y		F										15°											
ft	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				ft
	118 ft				118 ft				118 ft				118 ft				118 ft				118 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
50	21.5				22																				50
55	20.6				21.3				21.1				20.4												55
60	19.7				20.4				20.4				20.3				15.7								60
65	18.9				19.6				19.6				19.8				16.1								65
70	18.1				18.9				18.9				19.2				16.6				11.3				70
75	17.3				18.1				18.2				18.5				17				11.6				75
80	16.6				17.5				17.6				17.8				17				12				80
85	15.9				16.8				17				17.2				16.5				12.4				85
90	15.2	10.5			16.2	11.1			16.4				16.6				16				12.8				90
95	14.6	10.1			15.6	10.8			15.8	11			16.1	11.1			15.5				12.9				95
100	13.9	9.6			15	10.4			15.3	10.6			15.6	10.9			15	10.6			12.9				100
105	13.3	9.2			14.4	10.1			14.8	10.3			15.1	10.5			14.6	10.3			12.8				105
110	12.7	8.9			13.9	9.7			14.3	10			14.6	10.2			14.2	10			12.7	9.4			110
115	12.2	8.5	6.2		13.4	9.4			13.8	9.6			14.2	9.9			13.8	9.7			12.5	9.2			115
120	11.6	8.2	6.1		12.8	9	6.6		13.3	9.3	6.6		13.7	9.5	6.6		13.4	9.4			12.2	8.9			120
125	11.1	7.8	5.9		12.3	8.7	6.5		12.8	9	6.5		13.3	9.2	6.6		13	9.1			11.9	8.7			125
130	10.6	7.6	5.8		11.9	8.4	6.3		12.3	8.7	6.4		12.8	8.9	6.5		12.6	8.8	6.4		11.5	8.4			130
135	10.1	7.3	5.6	2.9	11.5	8.1	6.2		11.9	8.4	6.3		12.4	8.6	6.4		12.2	8.6	6.3		11.2	8.2	6.1		135
140	9.6	7.1	5.5	2.9	11.1	7.9	6.1	3.4	11.5	8.1	6.1	3.4	12	8.4	6.2		11.8	8.3	6.2		10.9	7.9	6		140
150	8.8	6.6	5.3	2.9	10.3	7.4	5.8	3.4	10.7	7.6	5.9	3.4	11.2	7.9	6	3.4	11.1	7.8	5.9		10.3	7.5	5.8		150
160	8.1	6.3	5		9.5	7	5.6		9.9	7.2	5.7	3.4	10.5	7.4	5.8	3.4	10.5	7.4	5.7	3.4	9.6	7.2	5.6	3.4	160
170	7.5	5.9	4.9		8.7	6.6	5.4		9.2	6.8	5.5		9.8	7	5.6	3.4	9.8	7	5.5	3.4	9.1	6.8	5.5	3.4	170
180	7	5.6	4.7		8.1	6.3	5.2		8.6	6.5	5.3		9.1	6.7	5.4		9.2	6.7	5.4		8.5	6.5	5.3		180
190	6.5	5.4	4.6		7.5	6	5.1		8	6.2	5.2		8.5	6.4	5.3		8.6	6.4	5.2		8	6.3	5.2		190
200	6.1	5.1			7	5.7	5		7.5	5.9	5.1		8	6.1	5.1		8.1	6.2	5.1		7.6	6	5		200
210	5.7	5			6.6	5.5			7	5.7	5		7.5	5.9	5		7.6	5.9	5		7.1	5.8	4.9		210
220	5.3	4.8			6.2	5.3			6.6	5.5			7	5.6	4.9		7.2	5.7	4.9		6.7	5.6	4.9		220
230	5				5.8	5.2			6.2	5.3			6.6	5.4			6.8	5.5	4.9		6.4	5.4	4.8		230
240	4.7				5.5	5.1			5.9	5.2			6.3	5.3			6.5	5.3			6.1	5.2	4.7		240
250					5.1				5.6	5			6	5.1			6.2	5.2			5.8	5			250
260									5.3				5.7	5			5.8	5.1			5.5	4.8			260
270													5.2				5.5	5			4.9	4.7			270
280																	4.3	4.9			3.7	4.5			280
290																					4.1				290


* adapter · pièce d'adaptateur

t_180_18601_00_000 / 18621_00_000 / 18641_00_000 / 18661_00_000

H

Lifting capacities Forces de levage

TYF



H

	132 + 8 ft*				149 + 8 ft*				165 + 8 ft*				182 + 8 ft*				198 + 8 ft*				215 + 8 ft*				
	118 ft				118 ft				118 ft				118 ft				118 ft				118 ft				
	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	0°	20°	40°	60°	
50	21.5				22																				50
55	20.6				21.3				21.1				20.4												55
60	19.7				20.4				20.4				20.3				15.7								60
65	18.9				19.6				19.6				19.8				16.1								65
70	18.1				18.9				18.9				19.2				16.6				11.3				70
75	17.3				18.1				18.2				18.5				17				11.6				75
80	16.6				17.5				17.6				17.8				17				12				80
85	15.9				16.8				17				17.2				16.5				12.4				85
90	15.2	10.5			16.2	11.1			16.4				16.6				16				12.8				90
95	14.6	10.1			15.6	10.8			15.8	11			16.1	11.1			15.5				12.9				95
100	13.9	9.6			15	10.4			15.3	10.6			15.6	10.9			15	10.6			12.9				100
105	13.3	9.2			14.4	10.1			14.8	10.3			15.1	10.5			14.6	10.3			12.8				105
110	12.7	8.9			13.9	9.7			14.3	10			14.6	10.2			14.2	10			12.7	9.4			110
115	12.2	8.5	6.2		13.4	9.4			13.8	9.6			14.2	9.9			13.8	9.7			12.5	9.2			115
120	11.6	8.2	6.1		12.8	9	6.6		13.3	9.3	6.6		13.7	9.5	6.6		13.4	9.4			12.2	8.9			120
125	11.1	7.8	5.9		12.3	8.7	6.5		12.8	9	6.5		13.3	9.2	6.6		13	9.1			11.9	8.7			125
130	10.6	7.6	5.8		11.9	8.4	6.3		12.3	8.7	6.4		12.8	8.9	6.5		12.6	8.8	6.4		11.5	8.4			130
135	10.1	7.3	5.6	2.9	11.5	8.1	6.2		11.9	8.4	6.3		12.4	8.6	6.4		12.2	8.6	6.3		11.2	8.2	6.1		135
140	9.6	7.1	5.5	2.9	11.1	7.9	6.1	3.4	11.5	8.1	6.1	3.4	12	8.4	6.2		11.8	8.3	6.2		10.9	7.9	6		140
150	8.8	6.6	5.3	2.9	10.3	7.4	5.8	3.4	10.7	7.6	5.9	3.4	11.2	7.9	6	3.4	11.1	7.8	5.9		10.3	7.5	5.8		150
160	8.1	6.3	5		9.5	7	5.6		9.9	7.2	5.7	3.4	10.5	7.4	5.8	3.4	10.5	7.4	5.7	3.4	9.6	7.2	5.6	3.4	160
170	7.5	5.9	4.9		8.7	6.6	5.4		9.2	6.8	5.5		9.8	7	5.6	3.4	9.8	7	5.5	3.4	9.1	6.8	5.5	3.4	170
180	7	5.6	4.7		8.1	6.3	5.2		8.6	6.5	5.3		9.1	6.7	5.4		9.2	6.7	5.4		8.5	6.5	5.3		180
190	6.5	5.4	4.6		7.5	6	5.1		8	6.2	5.2		8.5	6.4	5.3		8.6	6.4	5.2		8	6.3	5.2		190
200	6.1	5.1			7	5.7	5		7.5	5.9	5.1		8	6.1	5.1		8.1	6.2	5.1		7.6	6	5		200
210	5.7	5			6.6	5.5			7	5.7	5		7.5	5.9	5		7.6	5.9	5		7.1	5.8	4.9		210
220	5.3	4.8			6.2	5.3			6.6	5.5			7	5.6	4.9		7	5.7	4.9		6.4	5.6	4.9		220
230	5				5.8	5.2			6.2	5.3			6.5	5.4			6.6	5.5	4.9		5.2	5.4	4.8		230
240	4.7				5.2	5.1			5.8	5.2			6.1	5.3			5.4	5.3			3.9	5.2	4.7		240
250					4.1				5.5	5			5.2	5.1			4.2	5.1				4.8			250
260									4.9				3.9	5			2.9	4.7				3.6			260
270																		3.5							270

* adapter · pièce d'adaptateur

t_180_18605_00_000 / 18625_00_000 / 18645_00_000 / 18665_00_000

Lifting capacities Forces de levage

TYF

132-215 ft T 15° Y 138 ft F 360° 308600 lbs 85% 15° Y																			
ft	132 + 8 ft*			149 + 8 ft*			165 + 8 ft*			182 + 8 ft*			198 + 8 ft*			215 + 8 ft*			ft
	138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
50	17.6																		50
55	17.1			16.9			16.7			16.4									55
60	16.4			16.3			16.4			16.3									60
65	15.7			15.7			15.8			15.9									65
70	15.1			15.1			15.2			15.3			13.2						70
75	14.5			14.5			14.6			14.7			13.4			8.9			75
80	13.9			13.9			14.1			14.2			13.4			9.1			80
85	13.3			13.4			13.6			13.7			13.1			9.3			85
90	12.8			12.9			13.1			13.2			12.7			9.6			90
95	12.3			12.4			12.6			12.8			12.3			10			95
100	11.8	8.2		12	8		12.2	8		12.3			11.9			10.2			100
105	11.3	7.9		11.6	7.8		11.8	7.9		11.9			11.5			10.2			105
110	10.8	7.6		11.1	7.5		11.4	7.6		11.5	7.9		11.2	7.6		10			110
115	10.3	7.3		10.7	7.2		11	7.4		11.2	7.6		10.8	7.4		9.9			115
120	9.9	7		10.3	7		10.6	7.1		10.8	7.3		10.5	7.2			6.8		120
125	9.4	6.7		9.9	6.8		10.2	6.9		10.4	7.1		10.2	7			6.6		125
130	9	6.5		9.4	6.5		9.9	6.7		10.1	6.9		9.9	6.8			6.5		130
135	8.6	6.3	4.6	9.1	6.3	4.6	9.5	6.5		9.7	6.6		9.6	6.6			6.3		135
140	8.3	6.1	4.5	8.7	6.1	4.5	9.1	6.3	4.5	9.4	6.4	4.6	9.3	6.4			6.1		140
150	7.5	5.6	4.2	8	5.7	4.3	8.4	5.9	4.4	8.8	6	4.4	8.7	6	4.4		5.8	4.2	150
160	7	5.3	4	7.4	5.4	4.1	7.8	5.5	4.2	8.2	5.7	4.2	8.1	5.7	4.2		5.5	4	160
170	6.4	4.9	3.8	6.8	5.1	3.9	7.2	5.2	4	7.6	5.4	4	7.6	5.4	4		5.2	3.9	170
180	5.9	4.6	3.6	6.4	4.8	3.7	6.7	4.9	3.8	7	5.1	3.9	7.1	5.1	3.8			3.7	180
190	5.5	4.4	3.5	5.9	4.5	3.6	6.2	4.7	3.7	6.6	4.8	3.7	6.6	4.8	3.7			3.6	190
200	5.1	4.1	3.4	5.5	4.3	3.5	5.8	4.4	3.5	6.2	4.6	3.6	6.3	4.6	3.6			3.5	200
210	4.7	3.9	3.3	5.1	4	3.3	5.5	4.2	3.4	5.8	4.4	3.5	5.9	4.4	3.5			3.4	210
220	4.4	3.7		4.8	3.8	3.3	5.1	4	3.3	5.4	4.1	3.4	5.5	4.2	3.4			3.3	220
230	4.1	3.5		4.5	3.7		4.8	3.8	3.2	5.1	3.9	3.3	5.2	4	3.3			3.2	230
240	3.8	3.4		4.2	3.5		4.5	3.6		4.8	3.8	3.2	4.9	3.8	3.2			3.2	240
250	3.5			3.9	3.4		4.2	3.5		4.5	3.6		4.6	3.7	3.2				250
260	3.2			3.7	3.3		4	3.4		4.2	3.5		4.4	3.5					260
270							3.8	3.3		4	3.4		4.2	3.4					270
280							3.5			3.8	3.3		3.9	3.3					280
290													3.6	3.2					290
300														3.2					300


* adapter · pièce d'adaptateur

t_180_18701_00_000 / 18721_00_000 / 18741_00_000

H

Lifting capacities Forces de levage

TYF




H

	132 + 8 ft*			149 + 8 ft*			165 + 8 ft*			182 + 8 ft*			198 + 8 ft*			215 + 8 ft*			
	138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			
	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	0°	20°	40°	
50	17.7																		50
55	17.1			16.9			16.7			16.4									55
60	16.4			16.3			16.4			16.3									60
65	15.7			15.7			15.8			15.9									65
70	15.1			15.1			15.2			15.3			13.2						70
75	14.5			14.5			14.6			14.7			13.4			8.9			75
80	13.9			13.9			14.1			14.2			13.4			9.1			80
85	13.3			13.4			13.6			13.7			13.1			9.3			85
90	12.8			12.9			13.1			13.2			12.7			9.6			90
95	12.3			12.4			12.6			12.8			12.3			10			95
100	11.8	8.2		12	8		12.2	8		12.3			11.9			10.2			100
105	11.3	7.9		11.6	7.8		11.8	7.9		11.9			11.5			10.2			105
110	10.8	7.6		11.1	7.5		11.4	7.6		11.5	7.9		11.2	7.6		10			110
115	10.3	7.3		10.7	7.2		11	7.4		11.2	7.6		10.8	7.4		9.9			115
120	9.9	7		10.3	7		10.6	7.1		10.8	7.3		10.5	7.2			6.8		120
125	9.4	6.7		9.9	6.8		10.2	6.9		10.4	7.1		10.2	7			6.6		125
130	9	6.5		9.4	6.5		9.9	6.7		10.1	6.9		9.9	6.8			6.5		130
135	8.6	6.3	4.6	9.1	6.3	4.6	9.5	6.5		9.7	6.6		9.6	6.6			6.3		135
140	8.3	6.1	4.5	8.7	6.1	4.5	9.1	6.3	4.5	9.4	6.4	4.6	9.3	6.4			6.1		140
150	7.5	5.6	4.2	8	5.7	4.3	8.4	5.9	4.4	8.8	6	4.4	8.7	6	4.4		5.8	4.2	150
160	7	5.3	4	7.4	5.4	4.1	7.8	5.5	4.2	8.2	5.7	4.2	8.1	5.7	4.2		5.5	4	160
170	6.4	4.9	3.8	6.8	5.1	3.9	7.2	5.2	4	7.6	5.4	4	7.6	5.4	4		5.2	3.9	170
180	5.9	4.6	3.6	6.4	4.8	3.7	6.7	4.9	3.8	7	5.1	3.9	7.1	5.1	3.8			3.7	180
190	5.5	4.4	3.5	5.9	4.5	3.6	6.2	4.7	3.7	6.6	4.8	3.7	6.6	4.8	3.7			3.6	190
200	5.1	4.1	3.4	5.5	4.3	3.5	5.8	4.4	3.5	6.2	4.6	3.6	6.3	4.6	3.6			3.5	200
210	4.7	3.9	3.3	5.1	4	3.3	5.5	4.2	3.4	5.8	4.4	3.5	5.9	4.4	3.5			3.4	210
220	4.4	3.7		4.8	3.8	3.3	5.1	4	3.3	5.4	4.1	3.4	5.5	4.2	3.4			3.3	220
230	4.1	3.5		4.5	3.7		4.8	3.8	3.2	5.1	3.9	3.3	5.1	4	3.3			3.2	230
240	3.8	3.4		4.2	3.5		4.5	3.6		4.7	3.8	3.2	4.8	3.8	3.2			3.2	240
250	3.5			3.9	3.4		4.2	3.5		4.4	3.6		4.3	3.7	3.2				250
260	3.2			3.6	3.3		3.9	3.4		4.1	3.5		3.4	3.5					260
270							3.7	3.3		3.4	3.4			3.4					270
280							3.3			3.3				3					280

* adapter · pièce d'adaptateur

t_180_18705_00_000 / 18725_00_000 / 18745_00_000



H

Lifting capacities Forces de levage

TN

																							
 ft	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			149 + 11.5 ft*		 ft		
	39 ft**			39 ft**			39 ft**			39 ft**			39 ft**			39 ft**			39 ft**				
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	75°	68°			
22	156.1																				22		
24	156.1																				24		
26	156.1			156.1																	26		
28	156.1			156.1																	28		
30	155.6			155.8			142.3														30		
32	153.5			154.6			143.2														32		
34	150.1			152.9			143.4			117.6											34		
36	145.6	147.8		150.9			143			117.9											36		
38	139.7	142.1		147.3	149.4		141.5			118.1			98.5			75.1					38		
40	132.9	136.7		142.5	148.2		140			118.3			98.6			75					40		
42	124.2	132.3		135.2	144.7		138.9			118.7			98.7			74.9			57.9		42		
44		128.6	129.3	127.1	140.7		135.4	136.9		119.3			99			74.9			57.9		44		
46		125.2	128		136.6			135.8		119.9			99.3			74.9			57.8		46		
48		121	123.8		133.2			132.9		119.5			99.8			74.6			57.8		48		
50			119.5		129.9	127.1		130		119.2	114		100.3			74.4			57.8		50		
55						119.2		120.9			112			94.6					57.8		55		
60						109					106.8			93.9							60		
65									96.3		98.3			93.2				62.1			65		
70												84.8					59			49.4	70		
75												79				76.2				47.5	75		
80																71.2					80		
85																66.5			45.8		85		
90																			43.3		90		

* adapter · pièce d'adaptateur

** Hookblock with deadweight of 6615 lbs necessary · Moufle à crochet de poids minimal de 6615 lbs nécessaire

t_180_54105_00_000

Lifting capacities Forces de levage

TN

49—215 ft  59 ft   360°  220500 lbs  85% 																
 ft	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			 ft
	59 ft***			59 ft***			59 ft***			59 ft***			59 ft***			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
28	130.7															28
30	130.1															30
32	128.4			121.7												32
34	126.6			121.6												34
36	124.7			121			108.4									36
38	122.7			119.6			108.3			90.5						38
40	120.7			118.1			108.3			90.5						40
42	119			116.6			108.3			90.5			76.9			42
44	117.2	117.7		115.2			107.8			90.5			76.9			44
46	115.6	115.5		114			107.2			90.5			76.9			46
48	114.3	113.3		113			106.4			90.5			76.9			48
50	113.1	111		112	111		105.6			90.5			76.9			50
55	109.5	105.4		110.2	107.6		104.2	103.1		90.5			76.9			55
60	104	100.1	100.2	107.5	104.2		103.3	100.4		90.5	87.7		76.9			60
65		97.3	93.7	98.3	101.9	99.2	102.6	98		90.5	88.1		76.9	74.6		65
70			89.4		96.3	92.7		93.3		90.5	87.5		76.9	74.5		70
75						86.3		87.6	82.6		84.2			74.3		75
80						80.6			77.2		79.1	73.2		73.7		80
85									72.5		74.1	68.6		72.2		85
90												64.4			61.8	90
95												60.5			58.1	95
100															54.6	100

* adapter - pièce d'adaptateur

t_180_54205_00_000

*** Hookblock with deadweight of 3200 lbs necessary - Moufle à crochet de poids minimal de 3200 lbs nécessaire

49 – 215 ft 59 ft     85%																	215 + 11.5 ft*																
 ft	132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			182 + 11.5 ft*		198 + 11.5 ft*		59 ft***		 ft																	
	59 ft***			59 ft***			59 ft***			59 ft***		59 ft***		59 ft***																			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	82°	75°	82°																			
44	59.7															44																	
46	59.7															46																	
48	59.6															48																	
50	59.6			45.8			34.7									50																	
55	59.6			45.7			34.6			25.4		18				55																	
60	59.5			45.7			34.5			25.3		18				60																	
65	59.4			45.7			34.4			25.3		17.9		11.9		65																	
70	58.8	54.1		45.7			34.4			25.2		17.9		11.8		70																	
75		52.7		45.7	42		34.4			25.2		17.9		11.7		75																	
80		50.6			41.3							17.9		11.6		80																	
85		48.5			40			30.9				17.9		11.5		85																	
90		46.7			38.7			30			22.4					90																	
95			40		37.5			29.1			22					95																	
100			38.3			31.7					21.4		15.8			100																	
105			36.5			30.9							15.4			105																	
110			35			29.5			22.3				15			110																	
115									21.6							115																	

* adapter - pièce d'adaptateur

t_180_54205_00_000

*** Hookblock with deadweight of 3200 lbs necessary - Moufle à crochet de poids minimal de 3200 lbs nécessaire

Lifting capacities Forces de levage

TN

49 – 215 ft  79 ft   360°  220500 lbs  85% 																
 ft	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			 ft
	79 ft			79 ft			79 ft			79 ft			79 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
36	101.5															36
38	100.3			94.6												38
40	99.1			94.4												40
42	97.8			93.9			84.5									42
44	96.6			93.2			84.4			71.7						44
46	95.3			92.4			84.4			71.7						46
48	94.3			91.5			84.3			71.7						48
50	93.2	92.2		90.6			84.1			71.7						50
55	90.7	90.4		88.7			83.3			71.7			61.7			55
60	88.4	87.3		87	86.5		82			71.7			61.8			60
65	86.9	84.5		85.7	84.1		80.9	80		71.7			62			65
70	86.3	82.2	81.9	85.1	82.1		80.2	78.4		71.7	69.6		62.3			70
75	86.2	80.4	78.8	84.8	80.4	80	80	76.9		71.6	69.3		62.5			75
80	82.4	79.1	75.6	84.1	79.1	77.8	80	75.8		71.6	68.7		62.6	59.9		80
85		78.5	72.7	81.3	78.3	74.9	80	74.9	71.6	71.6	68.1		62.5	59.9		85
90			71.3		74	70.7		71.6	67.6	71.6	67.7	63.4	62.5	59.8		90
95						66.7		67.9	63.7		65.4	59.8		59.8	55.1	95
100									60		61.8	56.3		59	53.6	100
105									56.5			53.1			50.6	105
110												50.3			47.9	110
115												47.6			45.4	115
120															43.1	120

* adapter · pièce d'adaptateur

t_180_54305_00_000

* adapter · pièce d'adaptateur

t_180_54305_00_000

49—215 ft T 79 ft N 360° 220500 lbs 85%																		
ft	132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			182 + 11.5 ft*			198 + 11.5 ft*			215 + 11.5 ft*		ft
	79 ft			79 ft			79 ft			79 ft			79 ft			79 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	
50	48																	50
55	47.9			36.7			27											55
60	47.8			36.5			27											60
65	47.7			36.3			27			19.9			13.8					65
70	47.6			36.3			27			19.8			13.7			7.6		70
75	47.6			36.3			27			19.7			13.6			7.6		75
80	47.6			36.3			27			19.7			13.4			7.5		80
85	47.4	44		36.3	34.9		27			19.7			13.3			7.4		85
90	47.1	42.8		36.3	34.4		27			19.7			13.3			7.4		90
95		41.5		36.3	33.6		27	25		19.7			13.2			7.3		95
100		40.2	35.4		32.7			24.4			18		13.2			7.3		100
105		38.9	35.2		31.8			23.8			17.7							105
110		37.8	33.5		31			23.3			17.3			11.7				110
115			32.1		30.3	26.7		22.7			16.9			11.6			5.9	115
120			30.8			25.7			18.5		16.5			11.6			5.9	120
125						24.7			18.2					11.4			5.9	125
130						23.7			17.4					11.2			5.9	130
135									16.8			11.9						135
140												11.5			7.4			140
145															7.3			145
150															7			150

* adapter · pièce d'adaptateur

t 180_54305_00_000

* adapter · pièce d'adaptateur

t_180_54305_00_000

Lifting capacities Forces de levage

TN

49—215 ft  98 ft   360°  220500 lbs 85%																
 ft	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			 ft
	98 ft			98 ft			98 ft			98 ft			98 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
42	78.7															42
44	78.1															44
46	77.4			73.3												46
48	76.8			73												48
50	76.1			72.8			65.9			56.9						50
55	74.5			71.9			65.8			56.7			49.2			55
60	73			70.7			65.7			56.5			49.2			60
65	71.6	70.5		69.7	68.7		65.2			56.3			49			65
70	70.4	68.8		68.7	67.5		64.6	63.4		56.3			48.9			70
75	69.4	67.3		67.9	66.2		64	62.7		56.2			48.9			75
80	68.9	66	65.2	67.4	65.1		63.5	61.8		56.2	54.7		48.9			80
85	68.7	64.8	63.5	67.3	64.1	63.3	63.3	60.9		56.2	54.7		48.9	47.2		85
90	68.7	64.1	62.1	67.2	63.4	62.1	63.3	60.3		56.2	54.5		48.9	47.2		90
95	65.2	63.9	61	67.2	63	60.9	63.3	59.8	58.6	56.2	54.1		48.9	47.2		95
100		63.9	60.1	64.8	62.7	59.9	63.3	59.5	57.4	56.2	53.9	52.7	48.9	47.2		100
105		63.9	59.7		62.2	58.9		59.4	55.9	56.2	53.7	52.1	48.9	47.2		105
110			57.9		59	55.8		56.8	52.9		53.6	49.4	48.9	47.2	45.7	110
115						52.9		54	50.2		51.7	46.8		47.2	44.4	115
120									47.6		49	44.4		46.7	42.4	120
125									45.2			42.2			40.3	125
130												40.2			38.4	130
135												38.3			36.6	135
140															34.9	140

* adapter · pièce d'adaptateur

t_180_54405_00_000

49 – 215 ft T 98 ft N 360° 220500 lbs 85%																	
ft	132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			182 + 11.5 ft*			198 + 11.5 ft*			215 + 11.5 ft*	ft
	98 ft			98 ft			98 ft			98 ft			98 ft			98 ft	
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	
55	39																55
60	38.9																60
65	38.7			29			22.2										65
70	38.6			28.9			22.1			15.8			9.4				70
75	38.5			28.7			22			15.7			9.3			4.1	75
80	38.4			28.6			21.8			15.6			9.2			4	80
85	38.4			28.6			21.7			15.5			9.1			4	85
90	38.4	36.9		28.6			21.7			15.4			9			3.9	90
95	38.4	36.4		28.6	27.8		21.7			15.3			8.9			3.8	95
100	38.4	35.8		28.6	27.8		21.7	20.7		15.2			8.8			3.8	100
105	38.4	35.1		28.6	27.6		21.7	20.5		15.2			8.8			3.7	105
110	38.4	34.2		28.6	27.2		21.7	20.1		15.2	13.9		8.7			3.7	110
115		33.4	29.6	28.6	26.7		21.7	19.7		15.2	13.8		8.7	7.5		3.7	115
120		32.6	28.9		26.1	22.7		19.3			13.7		8.7	7.5		3.7	120
125		31.9	27.7		25.6	22.6		18.9			13.6			7.5			125
130		31.2	26.7		25.1	21.8		18.5			13.3			7.4			130
135			25.8		24.7	21		18.1	15		13			7.4			135
140			25			20.3			14.6		12.7	9.7		7.4			140
145						19.6			14			9.6		7.3			145
150						19			13.5			9.2		7.3			150
155									13			8.8			5.5		155
160												8.4			5.4		160
165															5.2		165
170															4.9		170

* adapter · pièce d'adaptateur

t_180_54405_00_000

Lifting capacities Forces de levage

TN

49—198 ft  118 ft   360°  220500 lbs 85%																
 ft	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			 ft
	118 ft			118 ft			118 ft			118 ft			118 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
50	61.8			57.6												50
55	61.3			57.3			52.3			45.4			39.8			55
60	60.3			57			52			45.3			39.8			60
65	59.2			57			51.7			45.1			39.5			65
70	58.1	57.4		56.3			51.5			45			39.4			70
75	57.2	56.5		55.6	54.9		51.4			44.8			39.3			75
80	56.4	55.4		55	54.1		51.3	50.2		44.7			39.2			80
85	55.6	54.3		54.3	53.3		51.1	50.1		44.7	43.4		39.2			85
90	55.1	53.4	52.7	53.9	52.4		50.7	49.6		44.7	43.2		39.1	38		90
95	54.2	52.5	51.8	53.5	51.7	51	50.4	49		44.7	43.1		39.1	37.9		95
100	52.9	51.8	50.7	52.6	51.1	50.4	49.8	48.5	47.6	44.7	43.1		39.1	37.8		100
105	51.3	51.3	49.8	51.1	50.6	49.5	48.8	48.1	47.3	44.7	43.1		39.1	37.7		105
110	49.7	50.6	49	49.6	50.3	48.7	47.4	47.7	46.6	44.6	43.1	42.4	39.1	37.7		110
115	48	49.6	48.5	48.1	49.6	48.1	46.1	47.5	46	44.2	43.1	42.2	39.1	37.7		115
120		48.3	48.1	46.7	48.5	47.7	44.8	47	45.5	43.4	43.1	41.8	39.1	37.7	36.9	120
125		46.8	47.8		47.3	47.2		45.8	44.9	42.6	43.1	41.4	39.1	37.7	37.1	125
130			46.8		46	45		44.6	42.8		43	39.7	39.1	37.7	37.2	130
135					42.9			43.5	40.8		41.9	38		37.7	35.9	135
140									39		40.2	36.2		37.6	34.3	140
145									37.2			34.6			32.7	145
150												33.1			31.3	150
155												31.7			30	155
160															28.7	160

* adapter · pièce d'adaptateur

t_180_54505_00_000

* adapter · pièce d'adaptateur

t_180_54505_00_000

49 – 198 ft  118 ft   360°  220500 lbs  85% 																
 ft	132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			182 + 11.5 ft*			198 + 11.5 ft*			 ft
	118 ft			118 ft			118 ft			118 ft			118 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
65	31.8															65
70	31.7			23.2			17.9									70
75	31.5			23.1			17.8			11.6			5.9			75
80	31.4			23			17.7			11.5			5.8			80
85	31.3			22.9			17.6			11.3			5.7			85
90	31.3			22.8			17.6			11.2			5.6			90
95	31.3	30.1		22.8			17.5			11.1			5.5			95
100	31.3	30.1		22.8			17.5			11			5.5			100
105	31.3	30		22.8	22.1		17.4			10.9			5.4			105
110	31.3	29.7		22.8	22.1		17.4	16.3		10.9			5.4			110
115	31.3	29.4		22.8	22.2		17.3	16.2		10.8	9.7		5.3			115
120	31.3	29		22.8	22.1		17.3	16.1		10.8	9.6		5.3	4.2		120
125	31.3	28.5		22.8	22		17.3	16		10.7	9.6		5.3	4.2		125
130	31.3	28	25.1	22.8	21.7		17.3	15.9		10.7	9.5		5.3	4.1		130
135		27.4	24.3	22.8	21.4	18.9	17.3	15.7		10.7	9.4		5.3	4.1		135
140		26.9	23.4		21.1	18.5		15.4			9.4		5.3	4.1		140
145		26.4	22.6		20.7	17.9		15.1			9.4			4.1		145
150		26	21.9		20.4	17.4		14.8	12.2		9.4			4		150
155			21.2		20.2	16.8		14.5	11.8		9.4	7.5		4		155
160			20.6			16.3			11.3		9.4	7.3		4		160
165						15.8			10.9			7		4		165
170						15.4			10.5			6.7		4		170
175									10.1			6.4			3.5	175
180												6.2			3.5	180
185															3.4	185
190															3.2	190

* adapter · pièce d'adaptateur

t_180_54505_00_000

Lifting capacities Forces de levage

TN

		 49-182 ft T			 138 ft N						 360° 220500 lbs			 85%														
 ft	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			182 + 11.5 ft*			 ft
	138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
55	49.1			46.2																							55	
60	48.7			46																							60	
65	48.7			45.6			41.9			36.6			32.3														65	
70	48.2			45.3			41.7			36.4			32.1			25.9			18.8								70	
75	47.5	46.8		45			41.4			36.3			31.9			25.9			18.7			13.9					75	
80	46.8	46.5		44.9			41.1			36.2			31.7			25.8			18.6			13.8					80	
85	46	45.6		44.7	44.1		40.8			36			31.6			25.7			18.5			13.6			7.8		85	
90	45.3	44.8		44.1	43.6		40.8	39.9		35.9	35.1		31.6			25.6			18.5			13.5			7.7		90	
95	44.3	44.1		43.5	43		40.8	39.8		35.9	35		31.6	30.6		25.5			18.4			13.3			7.6		95	
100	43.2	43.3	42.8	42.7	42.5		40.7	39.8		35.8	34.8		31.6	30.6		25.5	24.6		18.4			13.2			7.5		100	
105	41.6	42.4	42.2	41.5	41.9		40.4	39.8		35.7	34.7		31.6	30.6		25.5	24.6		18.3			13.1			7.4		105	
110	40.1	41.5	41.5	40.1	41.2	41	39.3	39.4		35.7	34.6		31.6	30.5		25.5	24.5		18.3	17.6		13			7.3		110	
115	38.6	40.3	40.8	38.7	40.4	40.4	38.2	39	38.5	35.7	34.6		31.6	30.5		25.5	24.5		18.3	17.6		12.9	11.9		7.3		115	
120	37.2	38.9	39.9	37.3	39.3	39.8	37	38.6	38.1	35.5	34.6		31.6	30.4		25.5	24.4		18.3	17.6		12.8	11.8		7.2	6.2	120	
125	35.9	37.5	38.9	36	38	39.2	35.9	38	37.7	34.8	34.6	33.9	31.6	30.4		25.5	24.3		18.3	17.6		12.7	11.7		7.1	6.2	125	
130	34.6	36.2	37.6	34.8	36.7	38.3	34.7	36.8	37.3	33.9	34.6	34	31.6	30.4	29.6	25.5	24.1		18.3	17.6		12.7	11.7		7.1	6.1	130	
135	33.5	34.9	36.4	33.7	35.5	37.2	33.7	35.7	36.8	33	34.5	33.9	31.5	30.4	29.5	25.5	23.8	21.8	18.3	17.6		12.6	11.6		7.1	6	135	
140		33.7	35.1	32.7	34.3	36.1	32.7	34.6	36.2	32.2	34.1	33.7	31.2	30.4	29.5	25.5	23.6	21.5	18.3	17.6		12.6	11.5		7.1	6	140	
145		32.7	33.9		33.2	34.9		33.6	35.5		33.2	33.5	30.6	30.4	29.5	25.5	23.3	20.8	18.3	17.6		12.6	11.5		7.1	6	145	
150			32.8		32.3	33.8		32.6	34.4		32.4	32.5	30.1	30.4	29.5	25.5	22.9	20.2	18.3	17.5	15.7	12.6	11.5		7.1	5.9	150	
155						32.8		31.7	33.4		31.6	31.2		30.4	29		22.5	19.6	18.3	17.4	15.2	12.6	11.5	10.3	7.1	5.9	155	
160									32.3		30.9	29.9		30.2	28.2		22.2	19		17.2	14.8		11.5	10.1		5.9		160
165									30.9						28.6		21.8	18.4		17	14.4		11.5	9.7		5.9		165
170												27.5			25.9		21.7	17.9		16.8	14		11.5	9.4		5.9	5.5	170
175														24.9				17.4		16.7	13.6		11.5	9		5.9	5.4	175
180																		17			13.2			8.7		5.9	5.3	180
185																					12.8			8.3			5.1	185
190																						12.5			8		4.9	190
195																								7.8			4.7	195
200																											4.5	200

* adapter · pièce d'adaptateur

t_180_54605_00_000

Lifting capacities Forces de levage

TN


																												
	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			182 + 11.5 ft*			
	157 ft			157 ft			157 ft			157 ft			157 ft			157 ft			157 ft			157 ft			157 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
65	39.3			37.1			34.1						29.8			26.3			21.3			15.1						65
70	38.9			36.8			33.9			29.6			26.2															70
75	38.6			36.5			33.6			29.4			26						21.2			15.1						75
80	38.4			36.2			33.4			29.4			26						21.2			15.1						80
85	38.2			36			33.2			29.2			25.8			21.2					15			10.4			5.3	85
90	37.9	37.5		35.8	35.1		33.1			29.1			25.7			21.1			14.9			10.3			5.2			90
95	37.5	37		35.7	35		32.9	32.2		29			25.6			21			14.8			10.1			5.1			95
100	37.1	36.5		35.6	34.9		32.8	32.1		29	28.3		25.5			21			14.8			10			5			100
105	36.6	36		35.4	34.9		32.8	31.9		28.9	28.2		25.5			20.9			14.7			9.9			4.9			105
110	36.3	35.5	34.8	35.3	34.6		32.7	31.8		28.9	28.1		25.5	24.8		20.9			14.7			9.8			4.8			110
115	36	35.1	34.5	35.2	34.3	33.6	32.7	31.8		28.8	28		25.5	24.7		20.9	20.1		14.6			9.7			4.7			115
120	35.8	34.7	34.2	35	34	33.4	32.7	31.8		28.8	27.9		25.5	24.7		20.9	20		14.6	14		9.6			4.7			120
125	35.7	34.3	33.7	34.9	33.7	33.1	32.7	31.8	31.1	28.8	27.8		25.5	24.6		20.9	20		14.5	13.9		9.5			4.6			125
130	35.7	34.1	33.2	34.8	33.4	32.7	32.7	31.6	31.1	28.8	27.8	27.2	25.5	24.6		20.9	20		14.5	13.8		9.4	8.6		4.6			130
135	35.7	33.8	32.9	34.8	33.2	32.4	32.7	31.5	30.9	28.8	27.8	27.1	25.5	24.6		20.9	19.9		14.5	13.8		9.4	8.5		4.5	3.6		135
140	35.7	33.7	32.6	34.8	33	32	32.7	31.4	30.6	28.8	27.8	27	25.5	24.6	23.9	20.9	19.9		14.5	13.7		9.3	8.4		4.5	3.6		140
145	35.6	33.7	32.3	34.8	32.9	31.7	32.6	31.4	30.3	28.8	27.8	27	25.5	24.6	23.9	20.9	19.8		14.5	13.6		9.3	8.4		4.5	3.6		145
150	35.2	33.7	32	34.8	32.9	31.5	32.6	31.3	30.1	28.8	27.8	27	25.5	24.6	23.8	20.9	19.7	18.2	14.5	13.6		9.3	8.4		4.5	3.5		150
155	33.4	33.7	32	34.8	32.9	31.3	32.6	31.3	30	28.8	27.8	27	25.5	24.6	23.8	20.9	19.5	17.8	14.5	13.6	13	9.3	8.4		4.5	3.5		155
160		33.7	32	33.5	32.9	31.3	32.6	31.3	29.9	28.8	27.8	27	25.5	24.6	23.8	20.9	19.4	17.4	14.5	13.6	12.9	9.3	8.4		4.5	3.5		160
165		33.1	32		32.9	31.2		31.3	29.7		27.8	27	25.5	24.6	23.8	20.9	19.2	16.9	14.5	13.6	12.7	9.3	8.4		4.5	3.5		165
170			32		32.9	30.9		31.3	29.1		27.8	26.7	25.5	24.6	23.8	20.9	18.9	16.5	14.5	13.6	12.4	9.3	8.4	8	4.5	3.5		170
175						29.8		30.5	28		27.8	25.8		24.6	23.8		18.7	16		13.6	12.1	9.3	8.4	7.7	4.5	3.5		175
180									26.9		27.5	24.8		24.6	23.4		18.4	15.6		13.6	11.8		8.4	7.5		3.5		180
185							25.9					23.8			22.6		18.3	15.1		13.6	11.5		8.4	7.2		3.5	3.4	185
190												22.9			21.7		18.2	14.7		13.6	11.2		8.4	6.9		3.5	3.5	190
195												22			20.9			14.3		13.6	10.8		8.4	6.7		3.5	3.6	195
200																		13.9			10.5			6.5		3.5	3.5	200
205																					10.2			6.3			3.4	205
210																								6			3.2	210
215																									5.9		3	215
220																											2.8	220

* adapter · pièce d'adaptateur

t_180_54705_00_000

Lifting capacities Forces de levage

TN



	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*			
	177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
70	31.8			29.9			27						21.4											70	
75	31.5			29.7			27			24.2			21.4											75	
80	31.2			29.5			27			24.1			21.3											80	
85	30.9			29.3			26.9			23.9			21.2			17.2			11.7					85	
90	30.6			29.1			26.8			23.7			21			17.1			11.6			6.8		90	
95	30.5	30.1		28.9			26.7			23.6			20.9			17.1			11.4			6.7		95	
100	30.4	30		28.7	28.3		26.5	26		23.4			20.7			17			11.3			6.6		100	
105	30.3	30		28.5	28		26.4	26		23.4			20.6			16.9			11.2			6.5		105	
110	30	29.6		28.5	27.8		26.3	25.8		23.3	22.8		20.6			16.8			11			6.4		110	
115	29.7	29.3		28.5	27.8		26.2	25.7		23.3	22.7		20.5	19.9		16.7			10.9			6.3		115	
120	29.5	28.9	28.2	28.4	27.8		26.1	25.5		23.2	22.6		20.5	19.9		16.6	15.8		10.8			6.2		120	
125	29.3	28.6	28	28.4	27.7		26	25.4		23.2	22.5		20.5	19.9		16.5	15.7		10.7			6.1		125	
130	29.1	28.3	27.8	28.3	27.6	27.1	25.9	25.3		23.2	22.5		20.5	19.8		16.4	15.6		10.6	9.9		6		130	
135	28.9	28	27.5	28.2	27.4	26.9	25.9	25.3		23.2	22.4		20.5	19.8		16.3	15.5		10.5	9.8		6	5.2	135	
140	28.8	27.7	27.1	28.1	27.2	26.7	25.9	25.3	24.8	23.2	22.3	21.9	20.5	19.8		16.2	15.4		10.4	9.7		5.9	5.1	140	
145	28.8	27.5	26.8	28.1	27	26.4	25.9	25.3	24.8	23.2	22.3	21.8	20.5	19.7		16.2	15.3		10.4	9.7		5.8	5.1	145	
150	28.8	27.3	26.5	28	26.9	26.2	25.9	25.3	24.8	23.2	22.3	21.7	20.5	19.7	19.2	16.2	15.3		10.4	9.6		5.8	5.1	150	
155	28.8	27.2	26.2	27.9	26.8	26	25.9	25.3	24.6	23.2	22.3	21.6	20.5	19.7	19.2	16.2	15.3		10.4	9.6		5.8	5.1	155	
160	28.8	27.2	26	27.9	26.7	25.8	25.9	25.3	24.5	23.2	22.3	21.6	20.5	19.7	19.1	16.2	15.3	14.8	10.4	9.6		5.8	5.1	160	
165	28.8	27.2	25.9	27.9	26.7	25.6	25.9	25.2	24.3	23.2	22.3	21.6	20.5	19.7	19.1	16.2	15.3	14.7	10.4	9.6		5.8	5.1	165	
170	28.8	27.2	25.8	27.9	26.7	25.4	25.9	25.2	24.2	23.2	22.3	21.6	20.5	19.7	19.1	16.2	15.3	14.5	10.4	9.6		5.8	5.1	170	
175	27.3	27.2	25.8	27.9	26.7	25.4	25.9	25.2	24.1	23.2	22.3	21.6	20.5	19.7	19.1	16.2	15.3	14.2	10.4	9.6	9.6	5.8	5.1	175	
180		27.2	25.8	26.9	26.7	25.3	25.9	25.2	24.1	23.2	22.3	21.6	20.5	19.7	19.1	16.2	15.3	13.8	10.4	9.6	9.7	5.8	5.1	180	
185		26.7	25.8		26.7	25.3		25.2	24.1		22.3	21.6	20.5	19.7	19.1	16.2	15.3	13.5	10.4	9.6	9.6	5.8	5.1	5.1	185
190			25.8		26.7	25.3		25.2	24.1		22.3	21.6	20.5	19.7	19.1	16.2	15.3	13.1	10.4	9.6	9.4	5.8	5.1	5.2	190
195					24.8			25.2	23.5		22.3	21.4		19.7	19.1		15.2	12.8		9.6	9.2	5.8	5.1	5.2	195
200								22.7			22.3	20.8		19.7	19		15.1	12.4		9.6	9		5.1	5.2	200
205											20				18.6		15	12.1		9.6	8.7		5.1	5.1	205
210											19.2				17.9			11.7		9.6	8.5		5.1	4.9	210
215															17.3			11.3		9.6	8.2		5.1	4.8	215
220																		11			8			4.6	220
225																					7.7			4.4	225
230																								4.2	230
235																								4	235

* adapter · pièce d'adaptateur

t_180_54805_00_000

Lifting capacities Forces de levage

TN

49—165 ft T 197 ft N 360° 220500 lbs 85%																									ft	
49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			149 + 11.5 ft*			165 + 11.5 ft*		ft			
197 ft			197 ft			197 ft			197 ft			197 ft			197 ft			197 ft								
82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°					
75	25.4			23.9																		75				
80	25.1			23.8			22.1															80				
85	24.9			23.6			21.9			19.4			17									85				
90	24.7			23.4			21.7			19.2			16.9			12.9			7.6			90				
95	24.4			23.2			21.5			19.1			16.8			12.7			7.5			3.3	95			
100	24.2			23.1			21.3			18.9			16.7			12.5			7.3			3.2	100			
105	24	23.8		22.9			21.2			18.8			16.6			12.4			7.2			3.2	105			
110	23.9	23.6		22.7	22.4		21.1			18.7			16.5			12.2			7.1			3.1	110			
115	23.7	23.5		22.6	22.3		21	20.6		18.6	18.1		16.4			12.1			7			3	115			
120	23.6	23.4		22.5	22.1		20.9	20.5		18.5	18.1		16.3			12			6.9			3	120			
125	23.5	23.3		22.4	21.9		20.8	20.4		18.5	18		16.3	15.9		11.8			6.8			3	125			
130	23.4	23.1	22.4	22.3	21.8		20.7	20.3		18.4	18		16.2	15.8		11.8	11.1		6.7			2.9	130			
135	23.3	22.8	22.3	22.2	21.7		20.6	20.2		18.4	17.9		16.2	15.7		11.7	11		6.7	6		2.9	135			
140	23.2	22.6	22.1	22.1	21.7	21.3	20.6	20		18.3	17.8		16.2	15.7		11.6	10.9		6.7	6		2.9	140			
145	23	22.4	22	22.1	21.6	21.3	20.5	19.9		18.3	17.8		16.2	15.6		11.6	10.8		6.7	5.9		2.9	145			
150	22.9	22.2	21.8	22.1	21.6	21.3	20.5	19.9	19.5	18.3	17.7		16.2	15.6		11.6	10.8		6.6	5.9		2.9	150			
155	22.8	22	21.6	22.1	21.5	21.2	20.4	19.9	19.4	18.3	17.7	17.3	16.2	15.6		11.6	10.8		6.6	5.9		2.9	155			
160	22.8	21.9	21.3	22	21.4	21	20.4	19.9	19.4	18.3	17.6	17.2	16.2	15.6		11.6	10.8		6.6	5.9		2.9	160			
165	22.8	21.8	21.1	22	21.4	20.8	20.4	19.9	19.4	18.3	17.6	17.2	16.2	15.6	15.1	11.6	10.8		6.6	5.9		2.9	165			
170	22.8	21.7	20.8	21.9	21.3	20.7	20.4	19.9	19.4	18.3	17.6	17.1	16.2	15.6	15.1	11.6	10.8		6.6	5.9		2.9	170			
175	22.8	21.7	20.7	21.9	21.2	20.5	20.4	19.9	19.4	18.3	17.6	17	16.2	15.6	15.1	11.6	10.8	10.8	6.6	5.9		2.9	175			
180	22.8	21.7	20.6	21.9	21.2	20.4	20.4	19.9	19.4	18.3	17.6	17	16.2	15.6	15	11.6	10.8	10.9	6.6	5.9		2.9	180			
185	22.8	21.7	20.5	21.9	21.2	20.3	20.4	19.9	19.4	18.3	17.6	17	16.2	15.6	15	11.6	10.8	11	6.6	5.9	6	2.9	185			
190	22.7	21.7	20.5	21.9	21.2	20.3	20.4	19.9	19.3	18.3	17.6	17	16.2	15.6	15	11.6	10.8	11	6.6	5.9	6.2	2.9	190			
195	21.3	21.7	20.5	21.9	21.2	20.3	20.4	19.9	19.3	18.3	17.6	17	16.2	15.6	15	11.6	10.8	11	6.6	5.9	6.3	2.9	195			
200		21.7	20.5	21.1	21.2	20.3	20.4	19.9	19.3	18.3	17.6	17	16.2	15.6	15	11.6	10.8	10.8	6.6	5.9	6.4	2.9	200			
205			20.5		21.2	20.3		19.9	19.3		17.6	17	16.2	15.6	15	11.6	10.8	10.5	6.6	5.9	6.5	2.9	205			
210			20.5			20.3		19.9	19.3		17.6	17		15.6	15		10.8	10.3		5.9	6.6	2.9	210			
215					20.3		19.9	19.3		17.6	17			15.6	15		10.8	10		5.9	6.6	2.9	215			
220							18.9			17.6	16.9			15.6	15		10.8	9.7		5.9	6.6		220			
225											16.6				14.9		10.8	9.4		5.9	6.4		225			
230											15.9				14.7			9		5.9	6.3		230			
235															14.2			8.7		5.9	6.1		235			
240																		8.5			5.9		240			
245																					5.7		245			

* adapter · pièce d'adaptateur

t_180_54905_00_000

Lifting capacities Forces de levage

TN




	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			149 + 11.5 ft*			
	217 ft			217 ft			217 ft			217 ft			217 ft			217 ft			217 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
85	20.3			19.3			17.9						13.4									85
90	20.2			19.1			17.7			15.6												90
95	20			18.9			17.5			15.5			13.4			9.1			4.4			95
100	19.8			18.7			17.4			15.4			13.3			8.9			4.3			100
105	19.6			18.6			17.2			15.2			13.1			8.8			4.2			105
110	19.4			18.5			17			15.1			13			8.6			4.1			110
115	19.2	19		18.3			16.9			15			12.8			8.5			4			115
120	19.1	18.9		18.2	18		16.8			14.9			12.7			8.4			3.9			120
125	19	18.7		18.1	17.8		16.8	16.5		14.8			12.5			8.3			3.8			125
130	18.9	18.6		18	17.7		16.7	16.4		14.7	14.4		12.4	11.9		8.2			3.8			130
135	18.8	18.5		17.8	17.5		16.6	16.3		14.6	14.3		12.3	11.8		8.1	7.5		3.7			135
140	18.7	18.4		17.7	17.4		16.5	16.2		14.6	14.2		12.3	11.7		8.1	7.4		3.6	3		140
145	18.6	18.3	17.9	17.6	17.3		16.4	16.1		14.6	14.2		12.3	11.7		8.1	7.3		3.6	3		145
150	18.6	18.2	17.8	17.5	17.1	16.8	16.4	16		14.5	14.1		12.3	11.7		8.1	7.3		3.6	3		150
155	18.5	18	17.7	17.5	17.1	16.8	16.3	15.9		14.5	14.1		12.3	11.7		8.1	7.3		3.6	3.1		155
160	18.4	17.9	17.6	17.5	17.1	16.8	16.3	15.8	15.6	14.5	14		12.3	11.7		8.1	7.3		3.6	3.2		160
165	18.3	17.8	17.5	17.4	17.1	16.8	16.2	15.8	15.5	14.5	14	13.7	12.3	11.7		8.1	7.3		3.6	3.3		165
170	18.3	17.6	17.3	17.4	17.1	16.8	16.2	15.7	15.4	14.5	14	13.6	12.3	11.7		8.1	7.3		3.6	3.3		170
175	18.3	17.5	17.1	17.4	17.1	16.7	16.2	15.6	15.3	14.5	13.9	13.5	12.3	11.7	11.7	8.1	7.3		3.6	3.4		175
180	18.2	17.4	17	17.4	17	16.7	16.2	15.6	15.3	14.5	13.9	13.5	12.3	11.7	11.7	8.1	7.3		3.6	3.5		180
185	18.2	17.4	16.8	17.4	17	16.6	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.7	8.1	7.3	7.5	3.6	3.6		185
190	18.1	17.4	16.7	17.4	17	16.5	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.7	8.1	7.3	7.5	3.6	3.6		190
195	18.1	17.4	16.6	17.4	17	16.4	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.7	8.1	7.3	7.5	3.6	3.7	3.3	195
200	18.1	17.4	16.5	17.4	17	16.3	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.6	8.1	7.3	7.5	3.6	3.8	3.3	200
205	18.1	17.4	16.5	17.4	17	16.3	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.6	8.1	7.3	7.5	3.6	3.8	3.4	205
210	18.1	17.4	16.5	17.4	17	16.2	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.6	8.1	7.3	7.5	3.6	3.8	3.6	210
215	17.5	17.4	16.5	17.4	17	16.2	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.6	8.1	7.3	7.5	3.6	3.7	3.7	215
220		17.4	16.5	17.2	17	16.2	16.2	15.6	15.3	14.5	13.9	13.4	12.3	11.7	11.6	8.1	7.3	7.5	3.6	3.7	3.7	220
225			16.5		17	16.2		15.6	15.3		13.9	13.4	12.3	11.7	11.6	8.1	7.3	7.5	3.6	3.7	3.8	225
230			16.5			16.2		15.6	15.3		13.9	13.4		11.7	11.6		7.3	7.5		3.7	3.8	230
235						16.2		15.6	15.3		13.9	13.4		11.7	11.6		7.3	7.5		3.7	3.8	235
240								15.3			13.9	13.4		11.7	11.6		7.3	7.3		3.7	3.7	240
245												13.3			11.6		7.3	7.1		3.7	3.7	245
250															11.6			6.9		3.7	3.7	250
255															11.5			6.7		3.7	3.7	255
260																		6.5		3.7		260
265																				3.7		265

* adapter · pièce d'adaptateur

t_180_55005_00_000

Lifting capacities Forces de levage

TN




	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			132 + 11.5 ft*			
	236 ft			236 ft			236 ft			236 ft			236 ft			236 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
90	15.9																		90
95	15.8			15.1			13.9			12.2			10						95
100	15.7			15			13.9			12.1			10			6.2			100
105	15.6			14.8			13.7			12			9.8			6			105
110	15.4			14.6			13.6			11.9			9.7			5.9			110
115	15.3			14.5			13.4			11.8			9.5			5.8			115
120	15.1			14.4			13.3			11.7			9.4			5.7			120
125	15	14.5		14.2	13.7		13.2			11.6			9.3			5.6			125
130	14.8	14.5		14.1	13.7		13			11.5			9.1			5.5			130
135	14.7	14.5		14	13.7		12.9	12.7		11.4			9			5.4			135
140	14.6	14.4		13.9	13.7		12.9	12.6		11.3	11		8.9			5.4			140
145	14.5	14.3		13.8	13.6		12.8	12.6		11.3	10.9		8.8	8.5		5.3			145
150	14.4	14.2		13.7	13.5		12.7	12.5		11.2	10.9		8.8	8.5		5.3			150
155	14.3	14.1		13.6	13.4		12.6	12.4		11.2	10.8		8.8	8.6		5.3	4.9		155
160	14.2	14	13.6	13.5	13.3		12.6	12.3		11.1	10.8		8.8	8.6		5.3	4.9		160
165	14.1	13.9	13.6	13.4	13.2	12.8	12.5	12.2		11.1	10.7		8.8	8.6		5.3	5		165
170	14.1	13.8	13.6	13.4	13.1	12.8	12.5	12.2		11.1	10.7		8.8	8.6		5.3	5		170
175	14.1	13.7	13.6	13.3	13.1	12.8	12.5	12.1	11.8	11	10.7		8.8	8.6		5.3	5.1		175
180	14.1	13.6	13.5	13.3	13	12.8	12.4	12.1	11.8	11	10.6	10.3	8.8	8.6		5.3	5.2		180
185	14	13.6	13.3	13.2	12.9	12.7	12.4	12	11.8	11	10.6	10.3	8.8	8.6	8.6	5.3	5.3		185
190	14	13.5	13.2	13.2	12.9	12.7	12.4	11.9	11.7	11	10.5	10.3	8.8	8.6	8.6	5.3	5.3		190
195	14	13.5	13.1	13.2	12.9	12.7	12.4	11.9	11.6	11	10.5	10.2	8.8	8.6	8.6	5.3	5.3	5	195
200	14	13.4	13	13.2	12.9	12.7	12.4	11.9	11.6	11	10.5	10.1	8.8	8.6	8.6	5.3	5.4	5.1	200
205	14	13.4	12.9	13.2	12.9	12.7	12.4	11.9	11.6	11	10.4	10.1	8.8	8.6	8.6	5.3	5.4	5.2	205
210	14	13.4	12.8	13.2	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.4	5.3	210
215	14	13.4	12.7	13.2	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.4	5.3	215
220	14	13.4	12.7	13.2	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.4	5.4	220
225	14	13.4	12.7	13.2	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.4	5.4	225
230	14	13.4	12.7	13.2	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.3	5.4	230
235	13.9	13.4	12.7	13.2	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.3	5.4	235
240		13.4	12.7	13	12.9	12.6	12.4	11.9	11.6	11	10.4	10	8.8	8.6	8.6	5.3	5.3	5.3	240
245			12.7		12.9	12.6		11.9	11.6		10.4	10	8.8	8.6	8.6	5.3	5.3	5.3	245
250			12.7			12.6		11.9	11.6		10.4	10		8.6	8.6		5.3	5.3	250
255						12.6		11.9	11.6		10.4	10		8.6	8.6		5.3	5.3	255
260									11.6			10		8.6	8.6		5.3	5.3	260
265												10			8.6		5.3	5.3	265
270															8.6			5.1	270
275															8.6			4.9	275
280																		4.8	280

* adapter · pièce d'adaptateur

t_180_55105_00_000

Lifting capacities Forces de levage


TN



	49 + 11.5 ft*			66 + 11.5 ft*			82 + 11.5 ft*			99 + 11.5 ft*			115 + 11.5 ft*			
	256 ft			256 ft			256 ft			256 ft			256 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
95	12.5															95
100	12.4			11.7			10.7			9			6.6			100
105	12.4			11.7			10.7			8.9			6.5			105
110	12.3			11.6			10.6			8.7			6.4			110
115	12.1			11.5			10.6			8.6			6.3			115
120	12			11.3			10.5			8.4			6.1			120
125	11.9			11.2			10.4			8.3			6			125
130	11.7			11.1			10.2			8.2			5.9			130
135	11.6	11.2		11			10.1			8.1			5.8			135
140	11.5	11.2		10.9	10.5		10	9.5		8			5.7			140
145	11.4	11.2		10.8	10.5		9.9	9.6		8	7.6		5.7			145
150	11.3	11.1		10.7	10.5		9.8	9.6		7.9	7.6		5.7			150
155	11.2	11		10.6	10.5		9.8	9.5		7.9	7.7		5.7	5.4		155
160	11	10.9		10.5	10.4		9.7	9.5		7.9	7.7		5.7	5.5		160
165	10.9	10.8	10	10.4	10.3		9.6	9.4		7.9	7.8		5.7	5.5		165
170	10.8	10.7	10.2	10.4	10.2		9.6	9.3		7.9	7.8		5.7	5.6		170
175	10.8	10.6	10.2	10.3	10.1	9.4	9.5	9.3		7.9	7.8		5.7	5.6		175
180	10.7	10.6	10.3	10.2	10	9.5	9.5	9.2	8.5	7.9	7.8		5.7	5.7		180
185	10.7	10.5	10.4	10.2	10	9.6	9.5	9.1	8.6	7.9	7.8	7.3	5.7	5.7		185
190	10.7	10.5	10.3	10.1	9.9	9.7	9.4	9.1	8.6	7.9	7.8	7.4	5.7	5.8		190
195	10.6	10.4	10.3	10.1	9.8	9.6	9.4	9	8.7	7.9	7.8	7.5	5.7	5.8		195
200	10.6	10.4	10.2	10.1	9.8	9.5	9.4	8.9	8.6	7.9	7.7	7.5	5.7	5.8	5.6	200
205	10.6	10.3	10	10.1	9.7	9.4	9.4	8.9	8.6	7.9	7.7	7.5	5.7	5.9	5.7	205
210	10.6	10.3	9.9	10.1	9.7	9.4	9.4	8.8	8.6	7.9	7.7	7.5	5.7	5.9	5.8	210
215	10.6	10.2	9.8	10.1	9.7	9.4	9.4	8.8	8.6	7.9	7.7	7.4	5.7	5.9	5.8	215
220	10.5	10.2	9.7	10	9.7	9.4	9.4	8.8	8.5	7.9	7.7	7.4	5.7	5.9	5.8	220
225	10.4	10.2	9.7	10	9.7	9.4	9.4	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	225
230	10.3	10.1	9.6	9.9	9.7	9.4	9.3	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	230
235	10.3	10.1	9.6	9.9	9.7	9.4	9.3	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	235
240	10.3	10.1	9.6	9.9	9.7	9.4	9.3	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	240
245	10.3	10.1	9.6	9.9	9.7	9.4	9.2	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	245
250	10.3	10.1	9.6	9.9	9.7	9.4	9.2	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	250
255	10.3	10.1	9.6	9.9	9.7	9.4	9.2	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	255
260		10.1	9.6		9.7	9.4	9.2	8.8	8.5	7.9	7.7	7.4	5.7	5.8	5.8	260
265			9.6		9.7	9.4		8.8	8.5		7.7	7.4	5.7	5.8	5.8	265
270			9.6			9.4		8.8	8.5		7.7	7.4		5.8	5.8	270
275						9.4		8.8	8.5		7.7	7.4		5.8	5.8	275
280									8.5			7.4		5.8	5.8	280
285												7.4			5.8	285
290															5.8	290
295															5.8	295

* adapter · pièce d'adaptateur

t_180_55205_00_000



Lifting capacities Forces de levage

TYVEN

 115 - 149 ft T  Y  11.5 ft V  E  39 ft N   360°  264600 lbs 85%						
 ft	115 + 23 ft*		132 + 23 ft*		ft 	
	39 ft**		39 ft**			
	82°	75°	82°	82°		
	40	122.3				40
	42	124.9				42
	44	124.8				44
	46	123.3		109.9		46
	48	120.3		109.2		48
	50	117.4		108.5		50
55			104.5	97.6	55	
60				96.3	60	
65		100.1			65	
70		93.2			70	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64103_00_000

** Hookblock with deadweight of 6615 lbs necessary · Moufle à crochet de poids minimal de 6615 lbs nécessaire

115 – 149 ft

T

Y

11.5 ft

V

E

39 ft

N

360°

220500 lbs

85%

ft	115 + 23 ft*		132 + 23 ft*		149 + 23 ft*		ft
	39 ft**		39 ft**		39 ft**		
	82°	75°	82°		82°		
40	122.3						40
42	124.9						42
44	124.8						44
46	123.3		109.9				46
48	120.3		109.2				48
50	117.4		108.5		97.6		50
55			104.5		96.3		55
60							60
65		93.9					65
70		87.1					70

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64105_00_000

** Hookblock with deadweight of 6615 lbs necessary · Moufle à crochet de poids minimal de 6615 lbs nécessaire

Lifting capacities Forces de levage

TYVEN

 115 – 215 ft				 Y				 11.5 ft				 V				 E				 59 ft				 N				 360°				 286600 lbs				 85%			
 ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			 ft																	
	59 ft***			59 ft***			59 ft***			59 ft***			59 ft***			59 ft***			59 ft***																				
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°																		
46	83.5																					46																	
48	85.8																					48																	
50	88.2																					50																	
55	93.4			89.3						72.2												55																	
60	97.2			90.1			81.7			71.8												60																	
65	97.5			88.6			80.9			70.7			62			53.6						65																	
70	93.3	92.8		84.5			79.8			69.6			61.2			52.9			46.7			70																	
75		88.5		80.4	77.6		77.6			68			60.3			52.1			46.2			75																	
80		83			74.9								59.4			51.3			45.3			80																	
85		77.9			70.1		64.6						58.5			50.5			44.3			85																	
90		73.4	64.8		66.3		60.9			58.9												90																	
95			61.9				57.5			56.7			53.2									95																	
100			58.7			47.7				54.5			52			41.1						100																	
105						45.1										40.6						105																	
110						42.6			37							39.5			34.7			110																	
115								35.3			40.7								33.6			115																	
120											39.6											120																	
125																						125																	
130														32.5								130																	
135																	18.1					135																	
140																				17.8		140																	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft


*** Hookblock with deadweight of 3200 lbs necessary · Moufle à crochet de poids minimal de 3200 lbs nécessaire

t_180_64202_00_000

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64202_00_000

*** Hookblock with deadweight of 3200 lbs necessary · Moufle à crochet de poids minimal de 3200 lbs nécessaire

																										
			115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*					
			59 ft***			59 ft***			59 ft***			59 ft***			59 ft***			59 ft***								
			82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°			
46			83.5																						46	
48			85.8																						48	
50			88.2																						50	
55			93.4			89.3						72.2													55	
60			97.2			90.1			81.7			71.8													60	
65			97.5			88.6			80.9			70.7			62			53.6							65	
70			93.3	84.8		84.5			79.8			69.6			61.2			52.9			46.7				70	
75				80.4		80.4	73.9		77.6			68			60.3			52.1			46.2				75	
80				75.2			71								59.4			51.3			45.3				80	
85				70.5			66.6		62.8						58.5			50.5			44.3				85	
90				66.4	57.7		62.8		59.6			55.6													90	
95					54.9				56.4			52.7			46										95	
100					51.8			47				50			44.5			41.1							100	
105							44.4											40.6							105	
110							42			37								39			34.7				110	
115									35.3			32.3									33.6				115	
120												31.4													120	
125																									125	
130																24.1									130	
135																		18.1							135	
140																						17.3			140	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64205_00_000

*** Hookblock with deadweight of 3200 lbs necessary · Moufle à crochet de poids minimal de 3200 lbs nécessaire

Lifting capacities Forces de levage

TYVEN

115 – 215 ft T Y 11.5 ft V E 79 ft N 360° 308600 lbs 85%																						
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft
	79 ft			79 ft			79 ft			79 ft			79 ft			79 ft			79 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
55	70.3																				55	
60	74			71.4																	60	
65	78.2			74.6						61											65	
70	80			74.4			67.5			60.3			52.5			46.1					70	
75	79.8	78.9		73			67.2			59.5			52.1			45.6			40.2		75	
80	77.8	77.6		70.7			66.4			58.7			51.4			45			39.9		80	
85	74.4	74.7		67.6	66.2		65.5			57.8			50.7			44.3			39.3		85	
90	71.2	71.9		64.7	63.9		64.2			56.8			49.9			43.6			38.7		90	
95		69.2		61.9	61.5		62.1	61		55	52.4		49.2			43			37.9		95	
100		66.6	58.4		59.3			58.8			51.1		48.5	46.4		42.3			36.9		100	
105		63.9	57		57.1			56.7			49.3			46.3							105	
110		60.9	54.3		55	48.9		54.2			47.5			44.8			38.5				110	
115			51.7			46.8		51.8			45.9			43.4			37.8		30.5		115	
120			49.4			44.3			38.2		44.2			42			36.8		29.9		120	
125						42.1			36.5							35.6			28.9		125	
130						40.1			34.6			36.5				34.4			28		130	
135									32.9			35			31.9				27		135	
140											33.5				30.9						140	
145															29.7		15.8				145	
150															28.5		15.9				150	
155																	15.9				155	
160																			15.8		160	

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64301_00_000

115 – 215 ft T Y 11.5 ft V E 79 ft N 360° 220500 lbs 85%																						
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft
	79 ft			79 ft			79 ft			79 ft			79 ft			79 ft			79 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
55	70.3																				55	
60	74			71.4																	60	
65	78.2			74.6						61											65	
70	80			74.4			67.5			60.3			52.5			46.1					70	
75	79.8	77.8		73			67.2			59.5			52.1			45.6			40.2		75	
80	77.8	74.7		70.7			66.4			58.7			51.4			45			39.9		80	
85	74.4	70.1		67.6	66		65.5			57.8			50.7			44.3			39.3		85	
90	71.2	66.1		64.7	62.4		64.2			56.8			49.9			43.6			38.7		90	
95		62.4		61.9	58.9		62.1	54.5		55	49.4		49.2			43			37.9		95	
100		59.1	49.7		55.7			51.7			47.8		48.5	42.3		42.3			36.9		100	
105		56	48.3		52.6			49.2			45.4			41.2							105	
110		53.1	45.8		49.9	41		46.9			43.3			39.3			36.7				110	
115			43.5			39.3		44.7			41.4			37.6			35.3		30.5		115	
120			41.3			37.3			33.7		39.6			36			33.8		29.9		120	
125						35.5			32.2								32.3		28.9		125	
130						33.8			30.9			26.8					31		27.8		130	
135									29.6			25.7			21.8				26.7		135	
140												24.7			21.2						140	
145															20.3			15.8			145	
150															19.5			15.9			150	
155																		15.9		13.6	155	
160																				13	160	

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64305_00_000

Lifting capacities Forces de levage

TYVEN

115 – 215 ft T Y 11.5 ft V E 98 ft N 360° 308600 lbs 85%																						
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft
	98 ft			98 ft			98 ft			98 ft			98 ft			98 ft			98 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
60	58.9																				60	
65	61.1																				65	
70	63.7			61.8						51.2											70	
75	65.7			62.2			56.3			51.2			44.7			39.3					75	
80	66.9			61.9			56.1			50.6			44.5			39.1					80	
85	66.6			61.2			55.6			50			44			38.6			34		85	
90	65.6	65		60			54.9			49.4			43.4			38			33.6		90	
95	63.5	63.6		58	57.2		54.2			48.7			42.9			37.5			33		95	
100	60.9	61.4		55.5	54.9		53.4	52.5		48.1			42.3			36.9			32.5		100	
105	58.3	59.1		53.3	52.8		52.5	51.8		47.4			41.7			36.4			31.9		105	
110	55.8	56.9		51	50.8		50.5	49.9		46.7	45.7		41.1			35.8			31.4		110	
115		54.8	50.9	48.8	48.9		48.6	48.1		45.5	44.5		40.5	39.2		35.2	33.8		30.8		115	
120		52.8	48.5		47.1	44.7		46.4			42.9		39.9	38.6		34.7	33.6		30.2	28.1	120	
125		50.8	46.3		45.4	42.6		44.8			41.4			38			33.1		28		125	
130		48.8	44.4		43.7	40.8		43.3	38.7		40			37.2			32.3		26.9		130	
135			42.5			39.1		41.8	37.3		38.7			36.1			31.4		26		135	
140			40.8			37.4			35.7		37.4	32.5		34.9			30.5		25		140	
145						35.9			34.2			31.1				29.4			24.1		145	
150						34.6			32.9			29.9			27.1		28.3		23.3		150	
155									31.6			28.7			26.1			14.2	22.5		155	
160												27.6			25.1			14.2			160	
165															24.1			14.1		10.6	165	
170															23.2			13.8		10.8	170	
175																		13.4		10.9	175	
180																				10.8	180	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64401_00_000

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64401_00_000

115 – 215 ft 11.5 ft 98 ft 360° 220500 lbs 85%																						
	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			
	98 ft			98 ft			98 ft			98 ft			98 ft			98 ft			98 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
60	58.9																				60	
65	61.1																				65	
70	63.7			61.8						51.2											70	
75	65.7			62.2			56.3			51.2			44.7			39.3					75	
80	66.9			61.9			56.1			50.6			44.5			39.1					80	
85	66.6			61.2			55.6			50			44			38.6			34		85	
90	65.6	64.3		60			54.9			49.4			43.4			38			33.6		90	
95	63.5	61.8		58	57		54.2			48.7			42.9			37.5			33		95	
100	60.9	58.4		55.5	54.4		53.4	51		48.1			42.3			36.9			32.5		100	
105	58.3	55.4		53.3	51.7		52.5	48.4		47.4			41.7			36.4			31.9		105	
110	55.8	52.5		51	49.2		50.5	46.2		46.7	41.2		41.1			35.8			31.4		110	
115		49.9	42.7	48.8	46.7		48.6	44.1		45.5	39.4		40.5	35.7		35.2	32.9		30.8		115	
120		47.4	40.5		44.4	36		42.1			37.6		39.9	34.1		34.7	31.9		30.2	28.1	120	
125		45.1	38.6		42.3	34.4		40.3			36			32.6			30.5			27.8	125	
130		43	36.8		40.3	33		38.7	29.8		34.5			31.2			29.2			26.6	130	
135			35.1			31.5		37	28.8		33.1			30			28			25.5	135	
140			33.5			30			27.6		31.8	23.1		28.8			26.9			24.5	140	
145						28.7			26.5			22.1				25.8				23.5	145	
150						27.4			25.4			21.2			17.8		24.8			22.6	150	
155									24.5			20.4			17.1			14.2		21.7	155	
160												19.6			16.4			14.1			160	
165															15.8			14		10.6	165	
170															15.1			13.4		10.8	170	
175																		12.8		10.5	175	
180																				10	180	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t 180 64405 00 000

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64405_00_000

Lifting capacities Forces de levage

TYVEN

																	85%							
	ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*				ft
		118 ft			118 ft			118 ft			118 ft			118 ft			118 ft			118 ft				
		82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°		
70		50.2																					70	
75		51.8																					75	
80		53.4																					80	
85		54.5																					85	
90		54.2																					90	
95		53.6	52.2																				95	
100		52.6	52.1																				100	
105		51.1	52.1																				105	
110		49.4	51																				110	
115		47.8	49.5																				115	
120		46.1	47.9	45.8																			120	
125		44.6	46.2	45.1																			125	
130		43.1	44.7	43.8																			130	
135			43.3	42.2																			135	
140			41.8	40.5																			140	
145			40.4	38.8																			145	
150			38.9	37.3																			150	
155				35.9																			155	
160				34.5																			160	
165																							165	
170																							170	
175																							175	
180																							180	
185																							185	
190																							190	
195																							195	
200																							200	

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64501_00_000

		115 – 215 ft						11.5 ft															85%						ft	
		115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*										
		118 ft			118 ft			118 ft			118 ft			118 ft			118 ft			118 ft										
		82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°		
70		50.2																											70	
75		51.8					50.1			40																			75	
80		53.4					50.8			43.5				41.2															80	
85		54.5					51.1			46.1				42.2						32.5									85	
90		54.2					50.9			46.5				42.2			37.1			32.4						28.3			90	
95		53.6	52.2				50.5			46.3				41.8			36.8			32.1						28.1			95	
100		52.6	52.1				50	48.6		45.8				41.4			36.4			31.7						27.8			100	
105		51.1	52.1				49.2	47.8		45.4				40.9			36			31.3						27.5			105	
110		49.4	51				47.3	46.1		44.8	43.8			40.4			35.5			30.8						27			110	
115		47.8	49.3				45.6	44.5		44.3	42.3			39.9	37.1		35.1			30.4						26.6			115	
120		46.1	47.2	39.3			43.9	42.9		43.8	40.4			39.4	36		34.6	31.7		29.9	28.4					26.2			120	
125		44.6	45	38.2			42.2	41.5		43.3	38.7			38.9	34.4		34.2	31		29.5	28.4					25.7			125	
130		43.1	42.9	36.5			40.6	40.1	31.9	42	37.1			38.4	32.9		33.7	29.7		29	28					25.3			130	
135			41	34.8			38.4	30.8		40.6	35.6			37.7	31.6		33.3	28.4		28.6	27.1				24.9	23.6			135	
140			39.2	33.2			36.7	29.5			34.2	26.1			30.3		32.9	27.3		28.2	26				24.5	22.9			140	
145			37.5	31.8			35.1	28.3			32.9	25			29.1			26.2			24.9					22.1			145	
150			35.9	30.4			33.6	27.2			31.6	24			28	19.7		25.2			23.9					21.4			150	
155				29.2				26			30.4	23.1			27	18.9		24.2			23					20.7			155	
160				27.9				24.9				22.2			26	18.2		23.3	15		22.2					20.1			160	
165								23.9				21.4				17.4			14.4		21.3	8.2				19.4			165	
170								22.9				20.6				16.8			13.8		20.6	8.4				18.7			170	
175												19.8				16.1			13.2			8.5				18		9.2	175	
180																15.5			12.7			8.5					9.2		180	
185																			12.2			8.4					8.8		185	
190																			11.7								8.4		190	
195																						7.8					8		195	
200																											7.7		200	

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64505_00_000

Lifting capacities Forces de levage

TYVEN

115 – 215 ft 11.5 ft 138 ft 360° 308600 lbs 85%																						
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft
	138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
75	44.5			40.2																		75
80	45			41			36															80
85	45.3			41.5			37.4															85
90	44.9			41.8			37.9			33.3												90
95	44.2			41.8			38.2			34.4			26.9			26.5			23.5			95
100	43.3	42.5		41.7			38.2			34.7			30			26.5			23.4			100
105	42.2	42.4		41.3			38.1			34.7			30.5			26.4			23.3			105
110	41.1	42.4		40.7	40.5		37.8			34.4			30.3			26.2			23.1			110
115	39.7	41.5		40	40		37.4	36.5		34			30			25.9			22.9			115
120	38.2	40.2		38.9	39.1		37.1	36.4		33.6	32.2		29.7			25.6			22.6			120
125	36.8	38.8		37.5	37.7		36.7	36.1		33.2	32.2		29.3			25.3			22.3			125
130	35.5	37.5		36.2	36.5		36.2	35.8		32.8	32		29			24.9			21.9			130
135	34.2	36.3	34.7	34.9	35.2		35.3	35.5		32.5	31.7		28.6	27.5		24.6	23.5		21.6			135
140	33	35	33.7	33.7	34	31.6	34.2	34.8		32.1	31.4		28.3	27.2		24.2	23.3		21.2	19.9		140
145	31.9	33.9	32.7	32.5	32.9	30.8	33.1	33.8		31.7	31.2		27.9	27		23.9	23		20.9	19.8		145
150	30.9	32.8	31.8	31.5	31.8	30	32	32.7	30.7	31.4	30.8		27.6	26.8		23.6	22.7		20.5	19.6		150
155		31.6	30.8		30.8	29.1	31	31.7	29.9	31.1	30		27.3	26.5		23.3	22.5		20.2	19.1		155
160		30.5	29.9		29.8	28.2		30.7	29.1		29.1	25.9		26.2		23	22.2		19.8	18.6		160
165		29.4	29		28.7	27.4		29.8	28.1		28.2	24.8		25.8		22			18			165
170		28	28.2		27.7	26.6		28.9	27		27.4	23.9		25.5		21.7			17.5			170
175			27.3			25.8		28.1	26.1		26.6	23		24.9	20.4		21.2		16.9			175
180			26.4			25.1			25.1		25.8	22.2		24.3	19.6		20.3	7.3	16.4			180
185						24.3			24.2			21.3			18.9		18.8	7.3	15.9			185
190						23.5			23.4			20.6			18.1		17.2	7.3	15.4			190
195									22.5			19.8			17.5			7.3	14.9	7.8		195
200												19.1			16.8			7.2		7.8		200
205															16.2			7		7.7		205
210																		6.8		7.6		210
215																		6.4		7.5		215
220																				7.2		220

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64601_00_000

115 – 215 ft T 11.5 ft V E 138 ft N 360° 220500 lbs 85%																						
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft
	138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			138 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
75	44.5			40.2																	75	
80	45			41			36														80	
85	45.3			41.5			37.4														85	
90	44.9			41.8			37.9			33.3											90	
95	44.2			41.8			38.2			34.4			26.9			26.5			23.5		95	
100	43.3	42.5		41.7			38.2			34.7			30			26.5			23.4		100	
105	42.2	42.4		41.3			38.1			34.7			30.5			26.4			23.3		105	
110	41.1	42.4		40.7	40.5		37.8			34.4			30.3			26.2			23.1		110	
115	39.7	41.5		40	40		37.4	36.5		34			30			25.9			22.9		115	
120	38.2	40.2		38.9	39.1		37.1	36.4		33.6	32.2		29.7			25.6			22.6		120	
125	36.8	38.8		37.5	37.7		36.7	36.1		33.2	32.2		29.3			25.3			22.3		125	
130	35.5	37.5		36.2	36.5		36.2	35.8		32.8	31.7		29			24.9			21.9		130	
135	34.2	36.3	34.3	34.9	35.2		35.3	34.8		32.5	30.6		28.6	26.9		24.6	23.5		21.6		135	
140	33	35	32.9	33.7	34	28.4	34.2	33.5		32.1	29.4		28.3	25.9		24.2	23.3		21.2	19.9	140	
145	31.9	33.9	31.4	32.5	32.9	27.3	33.1	32.2		31.7	28.2		27.9	24.9		23.9	23		20.9	19.8	145	
150	30.9	32.8	30.1	31.5	31.8	26.2	32	31	23.2	31.4	27.1		27.6	23.9		23.6	22.7		20.5	19.6	150	
155		31.6	28.9		30.8	25.2	31	29.9	22.3	31.1	26.1		27.3	22.9		23.3	22.2		20.2	19.1	155	
160		30.5	27.7		29.8	24.2		28.8	21.5		25.1	17.2		22.1		23	21.5		19.8	18.6	160	
165		29.4	26.5		28.7	23.3		27.8	20.6		24.2	16.5		21.2			20.7		18		165	
170		28	25.4		27.7	22.4		26.8	19.9		23.3	15.8		20.5			19.9		17.4		170	
175			24.4			21.5		25.7	19.1		22.5	15.2		19.7	12		19.2		16.8		175	
180			23.4			20.6			18.5		21.8	14.6		19	11.5		18.5	7.3	16.2		180	
185						19.8			17.8			14		11			17.9	7.3	15.6		185	
190						19			17.2			13.5		10.5			17.2	7.3	15	7.2	190	
195									16.6			13			10.1			7.3	14.5	6.9	195	
200												12.5			9.6			7.2		6.5	200	
205															9.2			7		6.2	205	
210																		6.8		5.9	210	
215																		6.4		5.6	215	
220																				5.3	220	

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64605_00_000

Lifting capacities Forces de levage

TYVEN

115 – 215 ft T Y 11.5 ft V E 157 ft N 360° 308600 lbs 85%																							
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft	
	157 ft			157 ft			157 ft			157 ft			157 ft			157 ft			157 ft				
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°		
80	35.7			31.7																		80	
85	36.3			32.7																		85	
90	36.6			33.4			30.8															90	
95	36.6			33.9			31.3			27.3			24.3									95	
100	36.4			34.3			31.5			28.2			24.7			22.1						100	
105	36.1			34.5			31.6			28.6			25.1			22.2			19.6			105	
110	35.8	34.5		34.5			31.6			28.8			25.1			22.2			19.6			110	
115	35.5	34.4		34.4	33.2		31.5			28.8			25.1			22.1			19.5			115	
120	35.2	34.3		34.3	33.1		31.3	30.7		28.7			25			22.1			19.4			120	
125	34.9	34.2		34.2	33		31.2	30.6		28.4			24.8			21.9			19.3			125	
130	34.7	34.1		34	33		31	30.4		28.2	27.1		24.6			21.7			19.1			130	
135	34.5	34		33.8	32.9		30.8	30.2		27.9	27		24.3	23.2		21.5			18.8			135	
140	34	33.4	31	33.4	32.3		30.5	30		27.6	26.8		24.1	23.1		21.2	19.9		18.6			140	
145	33.1	32.3	30.5	32.9	31.3		30.2	29.8		27.3	26.6		23.8	22.9		20.9	19.8		18.3			145	
150	31.9	31.3	29.7	31.8	30.3		29.9	29.6		27	26.4		23.5	22.7		20.6	19.6		18	16.7		150	
155	30.8	30.3	28.9	30.6	29.3	27	29.7	29		26.7	26.2		23.2	22.5		20.4	19.4		17.7	16.6		155	
160	29.7	29.3	28.1	29.6	28.4	26.3	29.3	28.2	25.9	26.5	26		23	22.3		20.1	19.2		17.4	16.4		160	
165	28.5	28.4	27.3	28.5	27.5	25.6	28.6	27.3	25.2	26.2	25.7		22.7	22.1		19.8	19.1		17.1	16.2		165	
170	27.2	27.5	26.5	27.4	26.6	24.8	27.6	26.4	24.5	26	25.4	23.1	22.5	21.9		19.5	18.9		16.9	16		170	
175		26.6	25.8		25.8	24.2	26.6	25.6	23.8	25.8	24.7	22.3	22.3	21.7		19.3	18.6		16.6	15.5		175	
180		25.7	25		24.9	23.5		24.8	23.1		24	21.5		21.5	19.6	19.1	18.4		16.3	15.1		180	
185		24.7	24.3		24.1	22.8		24.1	22.5		23.3	20.7		21.2	19.2		18.2			14.6		185	
190		23.4	23.6		23.3	22.2		23.3	21.8		22.7	19.9		20.9	18.6		18			14.2		190	
195			22.9			21.6		22.5	21.2		22	19.2		20.3	17.9		17.6	6		13.8		195	
200			22.2			20.9			20.6		21.4	18.5		19.8	17.3		16.9	6		13.3	6.3	200	
205						20.3			20.1			17.9			16.6		15.9	6		12.9	6.4	205	
210									19.5			17.2			16.1			6		12.5	6.4	210	
215									18.9			16.6			15.5			5.9		12.2	6.4	215	
220												16.1			14.9			5.8			6.3	220	
225															14.4			5.6			6.2	225	
230																		5.2			6.1	230	
235																		4.9			6	235	
240																					5.7	240	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64701_00_000

Lifting capacities Forces de levage

TYVEN


115 – 215 ft T Y 11.5 ft V E 157 ft N 360° 220500 lbs 85%																							
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			ft	
	157 ft			157 ft			157 ft			157 ft			157 ft			157 ft			157 ft				
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°		
80	35.7			31.7																	80		
85	36.3			32.7																	85		
90	36.6			33.4			30.8														90		
95	36.6			33.9			31.3			27.3			24.3								95		
100	36.4			34.3			31.5			28.2			24.7			22.1					100		
105	36.1			34.5			31.6			28.6			25.1			22.2			19.6		105		
110	35.8	34.5		34.5			31.6			28.8			25.1			22.2			19.6		110		
115	35.5	34.4		34.4	33.2		31.5			28.8			25.1			22.1			19.5		115		
120	35.2	34.3		34.3	33.1		31.3	30.7		28.7			25			22.1			19.4		120		
125	34.9	34.2		34.2	33		31.2	30.6		28.4			24.8			21.9			19.3		125		
130	34.7	34.1		34	33		31	30.4		28.2	27.1		24.6			21.7			19.1		130		
135	34.5	34		33.8	32.9		30.8	30.2		27.9	27		24.3	23.2		21.5			18.8		135		
140	34	33.4	31	33.4	32.3		30.5	30		27.6	26.8		24.1	23.1		21.2	19.9		18.6		140		
145	33.1	32.3	30.5	32.9	31.3		30.2	29.8		27.3	26.5		23.8	22.9		20.9	19.8		18.3		145		
150	31.9	31.3	29.3	31.8	30.3		29.9	29.6		27	26		23.5	22.7		20.6	19.6		18	16.7	150		
155	30.8	30.3	28	30.6	29.3	23.8	29.7	28.8		26.7	25.1		23.2	22.5		20.4	19.4		17.7	16.6	155		
160	29.7	29.3	26.9	29.6	28.4	22.9	29.3	27.8	20.5	26.5	24.2		23	22.2		20.1	19.2		17.4	16.4	160		
165	28.5	28.4	25.7	28.5	27.5	22	28.6	26.8	19.7	26.2	23.3		22.7	21.7		19.8	19		17.1	16.2	165		
170	27.2	27.5	24.7	27.4	26.6	21.2	27.6	25.8	18.9	26	22.4	14.8	22.5	20.9		19.5	18.7		16.9	16	170		
175		26.6	23.7		25.8	20.4	26.6	25	18.2	25.8	21.6	14.2	22.3	20.2		19.3	18		16.6	15.5	175		
180		25.7	22.8		24.9	19.7		24.1	17.5		20.9	13.7		19.4	11.7	19.1	17.3		16.3	15	180		
185		24.7	21.9		24.1	19		23.3	16.8		20.2	13.1		18.8	11.2		16.7			14.4	185		
190		23.4	21		23.3	18.3		22.5	16.2		19.5	12.6		18.1	10.8		16.1			13.9	190		
195			20.2			17.6		21.6	15.7		18.8	12.1		17.5	10.3		15.5	6		13.4	5.6	195	
200			19.5			16.9			15.1		18.2	11.6		16.9	9.9		15	6		12.9	5.3	200	
205					16.2				14.6			11.2			9.5		14.5	6		12.4	5	205	
210									14.1			10.7			9.1			6		11.9	4.7	210	
215									13.6			10.3			8.7			5.9		11.5	4.4	215	
220												9.9			8.3			5.8			4.1	220	
225															8			5.6			3.9	225	
230																		5.2			3.6	230	
235																		4.9			3.4	235	
240																					3.1	240	

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64705_00_000

Lifting capacities Forces de levage

TYVEN



	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			
	177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
90	28.5			27.2																		90
95	28.9			27.5			23.9															95
100	29.3			27.7			24.6			22.2			16.5									100
105	29.5			27.8			25			22.7			19			17						105
110	29.4			27.8			25.3			22.9			19.4			17.3						110
115	29.3	27.9		27.8			25.5			23.1			19.8			17.6			15.4			115
120	29.1	27.9		27.8			25.5			23.1			20			17.7			15.5			120
125	28.8	27.8		27.7	27		25.4			23.1			20.1			17.7			15.5			125
130	28.6	27.7		27.6	26.9		25.4	25.1		23			20.1			17.6			15.4			130
135	28.4	27.6		27.5	26.8		25.3	25		22.9	22.2		20.1			17.5			15.3			135
140	28.2	27.6		27.4	26.8		25.2	24.8		22.8	22.1		19.9			17.4			15.2			140
145	28	27.6		27.3	26.7		25.1	24.7		22.7	21.9		19.8			17.3			15.1			145
150	27.9	27.5		27.1	26		24.9	24.5		22.5	21.8		19.7	18.8		17.1	16.1		14.9			150
155	27.7	27.3	25.4	26.7	25.2		24.7	24.3		22.3	21.6		19.5	18.6		17	15.9		14.7			155
160	27.6	27.1	25.4	26.1	24.5	21.7	24.6	24.2		22.1	21.5		19.3	18.5		16.8	15.8		14.5	13.2		160
165	27.4	26.8	25.1	25.2	23.7	21.4	24.4	24		21.9	21.3		19.1	18.3		16.5	15.6		14.2	13.1		165
170	26.6	25.9	24.4	24.3	22.9	20.8	24.2	23.9	22.2	21.7	21.1		18.9	18.2		16.3	15.5		14	13		170
175	25.7	25.1	23.8	23.5	22.2	20.2	24	23.6	21.7	21.4	21		18.7	18		16.1	15.3		13.8	12.8		175
180	24.8	24.4	23.2	22.7	21.5	19.7	23.8	23.1	21.1	21.2	20.8	19.2	18.4	17.8		15.9	15.2		13.5	12.7		180
185	23.9	23.6	22.6	21.9	20.9	19.2	23.6	22.4	20.5	21	20.6	18.7	18.2	17.7		15.7	15		13.3	12.5		185
190	22.9	22.9	21.9	21.1	20.2	18.6	23	21.8	20	20.9	20.5	18.2	18	17.5	16.1	15.4	14.8		13.1	12.3		190
195		22.1	21.3		19.5	18.1	22.2	21.1	19.4	20.8	19.9	17.7	17.9	17.3	15.8	15.3	14.7		12.9	12.1		195
200		21.4	20.7		18.9	17.6		20.5	18.9		19.3	17.2		17.2	15.5	15.1	14.5	4	12.6	11.8		200
205		20.6	20.1		18.3	17.1		19.9	18.4		18.7	16.8		17	15.3		14.3	4.2		11.5		205
210			19.6			16.5		19.3	17.9		18.1	16.3		16.9	14.9		14.2	4.3		11.2	4.5	210
215			19			16		18.7	17.4		17.6	15.8		16.7	14.4		14	4.4		10.8	4.7	215
220			18.4			15.6			16.9		17	15.4		16.2	13.9		13.8	4.4		10.5	4.8	220
225						15.1			16.5			14.9			13.4		13.1	4.4		10.2	4.9	225
230									16			14.5			12.9			4.4		9.8	4.9	230
235									15.5			14.1			12.4			4.4		9.5	4.8	235
240												13.6			11.9			4.2			4.8	240
245															11.5			4			4.7	245
250																		3.7			4.6	250
255																		3.4			4.4	255
260																					4.1	260

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64801_00_000

Lifting capacities Forces de levage

TYVEN




	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			
	177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			177 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
90	28.5			27.2																		90
95	28.9			27.5			23.9															95
100	29.3			27.7			24.6			22.2			16.5									100
105	29.5			27.8			25			22.7			19			17						105
110	29.4			27.8			25.3			22.9			19.4			17.3						110
115	29.3	27.9		27.8			25.5			23.1			19.8			17.6			15.4			115
120	29.1	27.9		27.8			25.5			23.1			20			17.7			15.5			120
125	28.8	27.8		27.7	27		25.4			23.1			20.1			17.7			15.5			125
130	28.6	27.7		27.6	26.9		25.4	25.1		23			20.1			17.6			15.4			130
135	28.4	27.6		27.5	26.8		25.3	25		22.9	22.2		20.1			17.5			15.3			135
140	28.2	27.6		27.4	26.8		25.2	24.8		22.8	22.1		19.9			17.4			15.2			140
145	28	27.6		27.3	26.7		25.1	24.7		22.7	21.9		19.8			17.3			15.1			145
150	27.9	27.5		27.1	26		24.9	24.5		22.5	21.8		19.7	18.8		17.1	16.1		14.9			150
155	27.7	27.3	25.4	26.7	25.2		24.7	24.3		22.3	21.6		19.5	18.6		17	15.9		14.7			155
160	27.6	27.1	25.2	26.1	24.5	21.7	24.6	24.2		22.1	21.5		19.3	18.5		16.8	15.8		14.5	13.2		160
165	27.4	26.8	24.7	25.2	23.7	21.3	24.4	24		21.9	21.3		19.1	18.3		16.5	15.6		14.2	13.1		165
170	26.6	25.9	23.7	24.3	22.9	20.5	24.2	23.9	17.9	21.7	21.1		18.9	18.2		16.3	15.5		14	13		170
175	25.7	25.1	22.8	23.5	22.2	19.8	24	23.6	17.3	21.4	20.9		18.7	18		16.1	15.3		13.8	12.8		175
180	24.8	24.4	21.8	22.7	21.5	19	23.8	23.1	16.6	21.2	20.4	13.1	18.4	17.8		15.9	15.2		13.5	12.7		180
185	23.9	23.6	21	21.9	20.9	18.3	23.6	22.4	15.9	21	19.6	12.6	18.2	17.4		15.7	15		13.3	12.5		185
190	22.9	22.9	20.1	21.1	20.2	17.7	23	21.7	15.3	20.9	18.9	12	18	16.8	9.3	15.4	14.7		13.1	12.3		190
195		22.1	19.3		19.5	17	22.2	21	14.8	20.8	18.3	11.5	17.9	16.2	8.9	15.3	14.2		12.9	12		195
200		21.4	18.6		18.9	16.4		20.3	14.2		17.7	11.1		15.6	8.5	15.1	13.7	4	12.6	11.5		200
205		20.6	17.9		18.3	15.9		19.6	13.7		17.1	10.6		15.1	8.1		13.2	4.2		11.1	3.4	205
210			17.2			15.3		18.9	13.2		16.5	10.2		14.5	7.7		12.7	4.3		10.6	3.3	210
215			16.5			14.7		18.2	12.7		16	9.8		14	7.4		12.2	4.4		10.2	3	215
220			15.9			14.1			12.3		15.5	9.4		13.5	7		11.8	4.4		9.8	2.7	220
225						13.5			11.8			9			6.7		11.4	4.4		9.4		225
230									11.4			8.6			6.4			4.4		9		230
235									11			8.3			6.1			4.3		8.7		235
240												7.9			5.8			4				240
245															5.5			3.8				245
250																		3.5				250
255																		3.3				255

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64805_00_000

Lifting capacities Forces de levage

TYVEN



 ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*			 ft
	197 ft			197 ft			197 ft			197 ft			197 ft			197 ft			197 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	
95	22			20.8						16.3												95
100	22.3			21.1			19			17.1			13.9									100
105	22.5			21.4			19.3			17.4			14.4									105
110	22.8			21.6			19.6			17.6			15			11.3						110
115	23			21.7			19.8			17.8			15			12.6						115
120	23.2			21.8			19.9			18			15.2			12.9						120
125	23.3			21.9			19.9			18			15.3			13.1			10.6			125
130	23.1			21.9			19.9			17.9			15.3			13.3			11.4			130
135	23	22.2		21.9	21.6		19.8	20		17.9			15.3			13.3			11.4			135
140	22.8	22.1		21.9	21.6		19.8	19.9		17.9			15.3			13.3			11.4			140
145	22.6	22.1		21.8	21.5		19.7	19.8		17.8	17.5		15.2			13.3			11.4			145
150	22.4	22		21.8	21.4		19.6	19.6		17.8	17.4		15.1	14.8		13.3			11.4			150
155	22.3	21.9		21.7	21.4		19.6	19.5		17.7	17.2		15.1	14.7		13.2			11.3			155
160	22.1	21.9		21.7	21.3		19.6	19.4		17.6	17.1		15	14.6		13.1	12.3		11.2			160
165	22	21.7	20.3	21.6	21.2		19.5	19.2		17.5	17		14.9	14.5		13.1	12.2		11.1	9.9		165
170	21.9	21.6	20.3	21.6	21.2		19.4	19.1		17.4	16.8		14.8	14.3		13	12.1		11			170
175	21.8	21.5	20.3	21.5	20.7	18.5	19.3	19	17.9	17.3	16.7		14.7	14.2		12.8	12		10.8	9.8		175
180	21.7	21.4	20.3	21.3	20.2	18	19.2	19	17.7	17.1	16.6		14.6	14.1		12.7	11.9		10.7	9.7		180
185	21.6	21.4	20.3	21	19.6	17.5	19	18.8	17.7	17	16.6		14.4	13.9		12.5	11.7		10.5	9.5		185
190	21.6	21.3	20.1	20.3	19	17.1	18.9	18.7	17.2	16.9	16.4	15.4	14.3	13.8		12.3	11.6		10.3	9.4		190
195	21.3	20.8	19.6	19.6	18.4	16.6	18.6	18.6	16.7	16.7	16.3	15.2	14.2	13.7		12.2	11.5		10.1	9.3		195
200	20.7	20.2	19.1	18.9	17.8	16.1	18.3	18.1	16.3	16.6	16.2	14.9	14	13.5	4.2	12	11.3		9.9	9.1		200
205	20	19.6	18.6	18.3	17.2	15.6	17.9	17.6	15.8	16.4	16.1	14.4	13.9	13.4	4.5	11.9	11.2		9.8	9		205
210		19	18.1		16.7	15.2	17.5	17.1	15.4	16.2	15.9	14	13.8	13.3	4.8	11.7	11.1		9.6	8.8		210
215		18.4	17.6		16.2	14.8	17	16.5	14.9	15.8	15.6	13.6	13.6	13.1	4.9	11.6	10.9		9.4	8.7		215
220		17.8	17.1		15.6	14.3		16	14.5		15.2	13.2		13	5	11.4	10.8		9.3	8.6		220
225		17.1	16.7		15.1	13.9		15.6	14.1		14.7	12.8		12.9	5		10.7			8.4		225
230			16.2			13.5		15	13.7		14.2	12.5		12.8	5.1		10.6	2.7		8.3	3	230
235			15.7			13.1		14.5	13.3		13.7	12.1		12.7	5.1		10.4	2.7		8.1	3.1	235
240			15.2			12.6			12.9		13.2	11.7		11.8	5		10.3	2.7		8	3.1	240
245						12.2			12.5			11.3			4.8		10	2.8		7.8	3.2	245
250									12.1			11			4.5			2.7		7.6	3.2	250
255									11.8			10.6			4.2			2.7		7.4	3.2	255
260												10.3			3.8					3.1		260
265															3.3					3		265
270																				2.9		270
275																				2.7		275

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64901_00_000

Lifting capacities Forces de levage

TYVEN

115 – 215 ft T Y 11.5 ft V E 197 ft N 360° 220500 lbs 85%																						
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*			215 + 23 ft*		ft	
	197 ft			197 ft			197 ft			197 ft			197 ft			197 ft			197 ft			
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°		
95	22			20.8																	95	
100	22.3			21.1			19			16.3											100	
105	22.5			21.4			19.3			17.1			13.9								105	
110	22.8			21.6			19.6			17.4			14.4								110	
115	23			21.7			19.8			17.6			14.7			11.3					115	
120	23.2			21.8			19.9			17.8			15			12.6					120	
125	23.3			21.9			19.9			18			15.2			12.9					125	
130	23.1			21.9			19.9			18			15.3			13.1			10.6		130	
135	23	22.2		21.9	21.6		19.9			17.9			15.3			13.3			11.4		135	
140	22.8	22.1		21.9	21.6		19.8	20		17.9			15.3			13.3			11.4		140	
145	22.6	22.1		21.8	21.5		19.8	19.9		17.8			15.2			13.3			11.4		145	
150	22.4	22		21.8	21.4		19.7	19.8		17.8	17.5		15.1	14.8		13.3			11.4		150	
155	22.3	21.9		21.7	21.4		19.6	19.6		17.7	17.4		15.1	14.7		13.2			11.3		155	
160	22.1	21.9		21.7	21.3		19.6	19.5		17.6	17.2		15	14.6		13.1	12.3		11.2		160	
165	22	21.7	20.3	21.6	21.2		19.5	19.4		17.5	17.1		14.9	14.5		13.1	12.2		11.1		165	
170	21.9	21.6	20.3	21.6	21.2		19.4	19.2		17.4	17		14.8	14.3		13	12.1		11	9.9	170	
175	21.8	21.5	20.3	21.5	20.7	18.4	19.3	19.1		17.3	16.8		14.7	14.2		12.8	12		10.8	9.8	175	
180	21.7	21.4	20.3	21.3	20.2	17.8	19.2	19	15.6	17.1	16.7		14.6	14.1		12.7	11.9		10.7	9.7	180	
185	21.6	21.4	20.2	21	19.6	17.1	19	18.8	15	17	16.6		14.4	13.9		12.5	11.7		10.5	9.5	185	
190	21.6	21.3	19.7	20.3	19	16.4	18.9	18.7	14.4	16.9	16.4	11.1	14.3	13.8		12.3	11.6		10.3	9.4	190	
195	21.3	20.8	18.9	19.6	18.4	15.8	18.6	18.6	13.8	16.7	16.3	10.6	14.2	13.7		12.2	11.5		10.1	9.3	195	
200	20.7	20.2	18.2	18.9	17.8	15.2	18.3	18.1	13.3	16.6	16.2	10.1	14	13.5	4.2	12	11.3		9.9	9.1	200	
205	20	19.6	17.5	18.3	17.2	14.7	17.9	17.6	12.8	16.4	16	9.7	13.9	13.4	4.5	11.9	11.2		9.8	9	205	
210		19	16.8		16.7	14.1	17.5	17.1	12.3	16.2	15.7	9.3	13.8	13.3	4.8	11.7	11.1		9.6	8.8	210	
215		18.4	16.1		16.2	13.6	17	16.5	11.8	15.8	15.1	8.9	13.6	13.1	4.9	11.6	10.9		9.4	8.7	215	
220		17.8	15.5		15.6	13.1	16	11.3		14.6	8.5		12.9	5		11.4	10.6		9.3	8.5	220	
225		17.1	14.9		15.1	12.7		15.6	10.9	14.1	8.1		12.6	5			10.2		8.3		225	
230			14.3			12.2	15	10.5		13.6	7.7		12.1	5.1			9.8	2.7		7.9		230
235			13.8			11.8		14.5	10.1	13.2	7.4		11.7	5.1			9.4	2.7		7.6		235
240			13.3			11.3			9.7	12.8	7.1		11.3	5			9.1	2.7		7.2		240
245						10.8			9.4			6.7			4.8		8.7			6.9		245
250									9			6.4			4.5					6.6		250
255									8.7			6.1			4.2					6.3		255
260												5.8			3.8							260
265															3.3							265

* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_64905_00_000

Lifting capacities Forces de levage

TYVEN

115 – 198 ft T Y 11.5 ft V E 217 ft N 360° 308600 lbs 85%																		
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*		ft
	217 ft			217 ft			217 ft			217 ft			217 ft			217 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	
95	18.3																	95
100	18.4			16			15											100
105	18.5			16.3			15.3			13								105
110	18.6			16.5			15.4			13.3								110
115	18.7			16.8			15.6			13.6			9.2			7.8		115
120	18.8			16.9			15.7			13.7			10.1			8.8		120
125	18.8			17.1			15.8			13.9			11			9.1		125
130	18.8			17.2			15.8			14			11.2			9.3		130
135	18.8			17.3			15.7			14			11.4			9.5		135
140	18.7	17.7		17.3			15.7			14			11.5			9.7		140
145	18.5	17.8		17.3	17.1		15.7	15.9		13.9			11.6			9.8		145
150	18.4	17.8		17.3	17.2		15.6	15.9		13.9			11.7			9.8		150
155	18.2	17.8		17.3	17.2		15.5	15.9		13.8	13.9		11.7			9.7		155
160	18.1	17.7		17.3	17.2		15.5	15.8		13.8	13.8		11.6	11.6		9.7		160
165	18	17.7		17.3	17.2		15.4	15.7		13.7	13.7		11.6	11.4		9.6		165
170	17.9	17.6		17.2	17.1		15.3	15.6		13.6	13.6		11.5	11.3		9.6		170
175	17.7	17.5		17.2	17.1		15.3	15.4		13.6	13.5		11.5	11.2		9.5	8.3	175
180	17.6	17.4	16.2	17.1	17		15.2	15.3		13.5	13.4		11.4	11.1		9.5	8.4	180
185	17.6	17.3	16.2	17	17	15.3	15.1	15.2		13.4	13.3		11.4	11		9.4	8.4	185
190	17.5	17.1	16.2	16.8	16.9	15.5	14.9	15.1	14.1	13.3	13.2		11.3	10.9		9.3	8.4	190
195	17.4	17.1	15.9	16.7	16.8	15	14.7	15	14.1	13.2	13.1		11.2	10.8		9.2	8.4	195
200	17.3	16.8	15.5	16.5	16.5	14.6	14.5	14.9	13.8	13.1	12.9		11.1	10.7		9.1	8.3	200
205	17.1	16.4	15.1	16.3	16.1	14.2	14.3	14.8	13.4	13	12.8	10.6	11	10.6		9	8.1	205
210	16.6	15.9	14.7	16.1	15.5	13.8	14.1	14.7	13	12.9	12.7	10.7	10.9	10.5		8.9	8	210
215	16	15.4	14.2	15.9	15.1	13.4	13.8	14.4	12.6	12.7	12.6	10.8	10.8	10.4		8.8	7.9	215
220	15.4	14.9	13.8	15.6	14.6	13	13.5	13.9	12.2	12.4	12.5	10.8	10.7	10.3		8.7	7.7	220
225	14.8	14.4	13.5	15.2	14.1	12.7	13.1	13.5	11.9	12.1	12.5	10.7	10.5	10.2	3.2	8.6	7.4	225
230		13.9	13.1		13.7	12.3	12.8	13	11.5	11.7	12.3	10.5	10.2	10.1	3.3	8.5	7.1	230
235		13.4	12.7		13.2	11.9	12.4	12.6	11.1	11.3	12	10.1	9.8	10	3.4	8.1	6.8	235
240		12.9	12.3		12.7	11.5		12.2	10.7		11.6	9.8		9.9	3.4	7.7	6.3	240
245			11.9		12.3	11.1		11.8	10.4		11.2	9.5		9.8	3.5		5.8	245
250			11.5			10.8		11.4	10.1		10.8	9.1		9.8	3.5		5.3	250
255			11.1			10.4		10.8	9.8		10.5	8.8		9.7	3.4		4.8	255
260			10.7			10.1			9.4		10	8.5		9.2	3.3		4.2	260
265						9.7			9.1			8.2			3.1		3.5	265
270									8.7			7.8						270
275									8.2			7.1						275
280												6.2						280

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_65001_00_000

J

Lifting capacities Forces de levage

TYVEN



	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*			198 + 23 ft*		
	217 ft			217 ft			217 ft			217 ft			217 ft			217 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	
95	18.3																	95
100	18.4			16			15											100
105	18.5			16.3			15.3			13								105
110	18.6			16.5			15.4			13.3								110
115	18.7			16.8			15.6			13.6			9.2			7.8		115
120	18.8			16.9			15.7			13.7			10.1			8.8		120
125	18.8			17.1			15.8			13.9			11			9.1		125
130	18.8			17.2			15.8			14			11.2			9.3		130
135	18.8			17.3			15.7			14			11.4			9.5		135
140	18.7	17.7		17.3			15.7			14			11.5			9.7		140
145	18.5	17.8		17.3	17.1		15.7	15.9		13.9			11.6			9.8		145
150	18.4	17.8		17.3	17.2		15.6	15.9		13.9			11.7			9.8		150
155	18.2	17.8		17.3	17.2		15.5	15.9		13.8	13.9		11.7			9.7		155
160	18.1	17.7		17.3	17.2		15.5	15.8		13.8	13.8		11.6	11.6		9.7		160
165	18	17.7		17.3	17.2		15.4	15.7		13.7	13.7		11.6	11.4		9.6		165
170	17.9	17.6		17.2	17.1		15.3	15.6		13.6	13.6		11.5	11.3		9.6		170
175	17.7	17.5		17.2	17.1		15.3	15.4		13.6	13.5		11.5	11.2		9.5	8.3	175
180	17.6	17.4	16.2	17.1	17		15.2	15.3		13.5	13.4		11.4	11.1		9.5	8.4	180
185	17.6	17.3	16.2	17	17	15.3	15.1	15.2		13.4	13.3		11.4	11		9.4	8.4	185
190	17.5	17.1	16.2	16.8	16.9	15.2	14.9	15.1	13.5	13.3	13.2		11.3	10.9		9.3	8.4	190
195	17.4	17.1	15.9	16.7	16.8	14.7	14.7	15	12.9	13.2	13.1		11.2	10.8		9.2	8.4	195
200	17.3	16.8	15.5	16.5	16.5	14.1	14.5	14.9	12.4	13.1	12.9	9.3	11.1	10.7		9.1	8.3	200
205	17.1	16.4	15.1	16.3	16.1	13.6	14.3	14.8	11.9	13	12.8	8.9	11	10.6		9	8.1	205
210	16.6	15.9	14.7	16.1	15.5	13	14.1	14.7	11.4	12.9	12.7	8.5	10.9	10.5		8.9	8	210
215	16	15.4	14.2	15.9	15.1	12.5	13.8	14.4	10.9	12.7	12.6	8.1	10.8	10.4		8.8	7.9	215
220	15.4	14.9	13.8	15.6	14.6	12	13.5	13.9	10.5	12.4	12.5	7.7	10.7	10.3		8.7	7.7	220
225	14.8	14.4	13.5	15.2	14.1	11.6	13.1	13.5	10.1	12.1	12.5	7.3	10.5	10.2	3.2	8.6	7.4	225
230		13.9	13.1		13.7	11.2	12.8	13	9.6	11.7	12.3	6.9	10.2	10.1	3.3	8.5	7.1	230
235		13.4	12.7		13.2	10.7	12.4	12.6	9.2	11.3	12	6.6	9.8	10	3.4	8.1	6.8	235
240		12.9	12.3		12.7	10.3		12.2	8.9		11.6	6.3		9.9	3.4	7.7	6.3	240
245			11.9		12.3	9.9		11.8	8.5		11.2	6		9.8	3.5		5.8	245
250			11.5			9.5		11.4	8.2		10.8	5.7		9.5	3.5		5.3	250
255			11.1			9.2		10.8	7.8		10.5	5.4		9.1	3.4		4.8	255
260			10.7			8.8			7.5		10	5.1		8.8	3.2		4.2	260
265						8.5			7.2			4.8			2.9		3.5	265
270									6.9			4.5						270
275									6.6			4.3						275
280												4						280

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_65005_00_000

Lifting capacities Forces de levage

TYVEN

115 – 198 ft T Y 11.5 ft V E 236 ft N 360° 308600 lbs 85%																	
ft	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*		198 + 23 ft*		ft
	236 ft			236 ft			236 ft			236 ft			236 ft		236 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	82°	75°	
100	14.3																100
105	14.3			12.3			11.3										105
110	14.4			12.4			11.6										110
115	14.5			12.6			11.8			9.7			6.7				115
120	14.6			12.8			12			10.1			7.3				120
125	14.6			13			12.1			10.3			7.7		4.9		125
130	14.7			13.1			12.2			10.5			8.2		5.7		130
135	14.6			13.2			12.2			10.7			8.4		6.3		135
140	14.5			13.3			12.3			10.7			8.5		6.7		140
145	14.5	13.2		13.4			12.3			10.8			8.7		6.9		145
150	14.4	13.4		13.4			12.3			10.8			8.7		7		150
155	14.3	13.5		13.4	12.8		12.2			10.8			8.8		7.1		155
160	14.3	13.6		13.4	13		12.2	12.2		10.8			8.8		7.2		160
165	14.2	13.7		13.5	13.1		12.1	12.4		10.7	10.9		8.8		7.2		165
170	14.1	13.8		13.5	13.2		12.1	12.4		10.7	10.8		8.7	8.9	7.2		170
175	14	13.7		13.4	13.3		12	12.3		10.6	10.7		8.7	8.8	7.1		175
180	13.9	13.7		13.4	13.3		11.9	12.3		10.6	10.7		8.7	8.7	7.1	6.2	180
185	13.8	13.6	11.7	13.3	13.3		11.8	12.2		10.5	10.6		8.6	8.6	7.1	6.3	185
190	13.7	13.5	11.9	13.2	13.2		11.7	12.1		10.5	10.5		8.6	8.5	7	6.3	190
195	13.6	13.5	12.1	13	13.2		11.6	12		10.4	10.4		8.5	8.4	7	6.4	195
200	13.5	13.4	12.3	12.9	13.1	11.4	11.5	11.9		10.4	10.3		8.5	8.3	6.9	6.4	200
205	13.4	13.3	12.4	12.8	13	11.6	11.3	11.8	10.6	10.3	10.2		8.4	8.2	6.9	6.4	205
210	13.3	13.3	12.5	12.7	13	11.8	11.2	11.8	10.7	10.1	10.1	7.9	8.4	8.1	6.8	6.4	210
215	13.2	13.2	12.5	12.5	12.9	11.9	11	11.7	10.8	10	10	8	8.3	8.1	6.7	6.3	215
220	13	13.2	12.4	12.4	12.9	11.7	10.8	11.6	10.7	9.8	9.9	8.2	8.2	8	6.6	6.2	220
225	12.9	13.1	12.2	12.2	12.8	11.3	10.6	11.5	10.6	9.7	9.8	8.3	8.1	7.9	6.6	6.1	225
230	12.8	13	11.8	12.1	12.7	11	10.4	11.5	10.2	9.5	9.8	8.4	8.1	7.8	6.5	6	230
235	12.7	12.5	11.4	11.9	12.3	10.7	10.1	11.4	9.9	9.3	9.7	8.4	7.8	7.7	6.4	5.8	235
240	12.5	12.1	11.1	11.8	11.9	10.3	9.9	11.2	9.6	9	9.6	8.3	7.6	7.6	6.2	5.6	240
245	12.1	11.7	10.8	11.6	11.4	10	9.6	10.8	9.3	8.7	9.6	8.1	7.3	7.6	6	5.4	245
250		11.3	10.5		11	9.7	9.4	10.5	9	8.5	9.5	7.9	7	7.5	5.7	5.2	250
255		10.9	10.1		10.6	9.4	9	10.1	8.6	8.2	9.5	7.7	6.7	7.4	5.4	4.8	255
260		10.4	9.8		10.3	9.1		9.7	8.3		9.2	7.5		7.4	5	4.4	260
265			9.4		9.8	8.8		9.4	8.1		8.9	7.2		7		3.9	265
270			9.1			8.5		9	7.8		8.5	7		6.3		3.5	270
275			8.8			8.1		8.5	7.6		8.2	6.8		5.4		3.1	275
280			8.4			7.9			7.3		7.8	6.6		4.5			280
285						7.6			7.1			6.3					285
290									6.8			6					290
295									6.4			5.6					295
300												4.7					300


* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_65101_00_000

J

Lifting capacities Forces de levage

TYVEN



	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*		198 + 23 ft*		
	236 ft			236 ft			236 ft			236 ft			236 ft		236 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	82°	75°	
100	14.3																100
105	14.3			12.3			11.3										105
110	14.4			12.4			11.6										110
115	14.5			12.6			11.8			9.7			6.7				115
120	14.6			12.8			12			10.1			7.3				120
125	14.6			13			12.1			10.3			7.7		4.9		125
130	14.7			13.1			12.2			10.5			8.2		5.7		130
135	14.6			13.2			12.2			10.7			8.4		6.3		135
140	14.5			13.3			12.3			10.7			8.5		6.7		140
145	14.5	13.2		13.4			12.3			10.8			8.7		6.9		145
150	14.4	13.4		13.4			12.3			10.8			8.7		7		150
155	14.3	13.5		13.4	12.8		12.2			10.8			8.8		7.1		155
160	14.3	13.6		13.4	13		12.2	12.2		10.8			8.8		7.2		160
165	14.2	13.7		13.5	13.1		12.1	12.4		10.7	10.9		8.8		7.2		165
170	14.1	13.8		13.5	13.2		12.1	12.4		10.7	10.8		8.7	8.9	7.2		170
175	14	13.7		13.4	13.3		12	12.3		10.6	10.7		8.7	8.8	7.1		175
180	13.9	13.7		13.4	13.3		11.9	12.3		10.6	10.7		8.7	8.7	7.1	6.2	180
185	13.8	13.6	11.7	13.3	13.3		11.8	12.2		10.5	10.6		8.6	8.6	7.1	6.3	185
190	13.7	13.5	11.9	13.2	13.2		11.7	12.1		10.5	10.5		8.6	8.5	7	6.3	190
195	13.6	13.5	12.1	13	13.2		11.6	12		10.4	10.4		8.5	8.4	7	6.4	195
200	13.5	13.4	12.3	12.9	13.1	11.4	11.5	11.9		10.4	10.3		8.5	8.3	6.9	6.4	200
205	13.4	13.3	12.4	12.8	13	11.6	11.3	11.8	10.6	10.3	10.2	7.5	8.4	8.2	6.9	6.4	205
210	13.3	13.3	12.5	12.7	13	11.8	11.2	11.8	10.4	10.1	10.1	7.4	8.4	8.1	6.8	6.4	210
215	13.2	13.2	12.5	12.5	12.9	11.5	11	11.7	9.9	10	10	7	8.3	8.1	6.7	6.3	215
220	13	13.2	12.4	12.4	12.9	11	10.8	11.6	9.5	9.8	9.9	6.6	8.2	8	6.6	6.2	220
225	12.9	13.1	12.2	12.2	12.8	10.6	10.6	11.5	9	9.7	9.8	6.3	8.1	7.9	6.6	6.1	225
230	12.8	13	11.8	12.1	12.7	10.2	10.4	11.5	8.6	9.5	9.8	5.9	8.1	7.8	6.5	6	230
235	12.7	12.5	11.4	11.9	12.3	9.7	10.1	11.4	8.3	9.3	9.7	5.6	7.8	7.7	6.4	5.8	235
240	12.5	12.1	11.1	11.8	11.9	9.3	9.9	11.2	7.9	9	9.6	5.3	7.6	7.6	6.2	5.6	240
245	12.1	11.7	10.8	11.6	11.4	9	9.6	10.8	7.5	8.7	9.6	5	7.3	7.6	6	5.4	245
250		11.3	10.5		11	8.6	9.4	10.5	7.2	8.5	9.5	4.7	7	7.5	5.7	5.2	250
255		10.9	10.1		10.6	8.2	9	10.1	6.9	8.2	9.5	4.4	6.7	7.4	5.4	4.8	255
260		10.4	9.8		10.3	7.9		9.7	6.5		9.2	4.1		7.4	5	4.4	260
265			9.4		9.8	7.6		9.4	6.2		8.9	3.8		7		3.9	265
270			9.1			7.3		9	5.9		8.5	3.6		6.3		3.5	270
275			8.8			7		8.5	5.7		8.2	3.3		5.4		3.1	275
280			8.4			6.7			5.4		7.8	3.1		4.5			280
285						6.4			5.1			2.9					285
290									4.9								290
295									4.6								295


* adapter 11.5 ft + telescopic boom extension 11.5 ft · pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_65105_00_000

J

Lifting capacities Forces de levage

TYVEN



	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*		
	256 ft			256 ft			256 ft			256 ft			256 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	
105	10.7														105
110	10.7														110
115	10.8			10			8.1								115
120	10.9			10.1			8.4			6.4					120
125	10.9			10.1			8.5			6.7			3		125
130	10.9			10.2			8.7			6.9			3.4		130
135	10.8			10.2			8.8			7.2			3.8		135
140	10.7			10.2			8.9			7.4			4.3		140
145	10.7			10.2			8.9			7.5			4.7		145
150	10.6			10.2			9			7.6			5.2		150
155	10.6	10		10.1			9			7.6			5.5		155
160	10.5	10.1		10.1	9.5		9			7.7			5.7		160
165	10.4	10.3		10	9.7		9	8.9		7.7			5.8		165
170	10.4	10.3		9.9	9.8		8.9	9.1		7.7			5.9		170
175	10.3	10.4		9.8	10		8.8	9.2		7.7	8		5.9	6.3	175
180	10.3	10.5		9.8	10.1		8.7	9.2		7.7	7.9		5.9	6.3	180
185	10.2	10.5		9.7	10.1		8.6	9.2		7.6	7.9		5.9	6.2	185
190	10.1	10.5		9.6	10.2		8.6	9.2		7.6	7.8		5.9	6.1	190
195	10	10.5		9.5	10.2		8.4	9.1		7.6	7.7		5.9	6.1	195
200	9.9	10.4	8.7	9.4	10.2		8.3	9.1		7.5	7.6		5.9	6	200
205	9.9	10.4	8.9	9.3	10.1		8.2	9		7.4	7.6		5.9	5.9	205
210	9.8	10.3	9	9.2	10.1		8.1	8.9	7.6	7.3	7.5		5.9	5.8	210
215	9.7	10.2	9.2	9.1	10		7.9	8.8	7.7	7.2	7.4		5.9	5.8	215
220	9.6	10.2	9.2	9	9.9		7.8	8.8	7.9	7	7.3		5.8	5.7	220
225	9.5	10.1	9.3	8.9	9.9		7.6	8.7	8	6.9	7.3	5.6	5.7	5.6	225
230	9.4	10	9.4	8.7	9.8		7.5	8.6	8	6.7	7.2	5.8	5.5	5.6	230
235	9.3	9.8	9.4	8.6	9.6		7.3	8.6	8	6.5	7.1	5.9	5.4	5.5	235
240	9.2	9.8	9.4	8.5	9.3		7.1	8.5	8	6.4	7	6	5.2	5.4	240
245	9.1	9.8	9.4	8.4	8.9	7.4	6.9	8.5	7.9	6.2	7	6.1	5	5.4	245
250	9	9.8	9.1	8.3	8.6	7.2	6.7	8.4	7.7	6	6.9	6.1	4.8	5.3	250
255	8.9	9.8	8.8	8.1	8.3	7	6.5	8.4	7.4	5.8	6.9	6.1	4.6	5.2	255
260	8.8	9.5	8.5	8	7.9	6.7	6.3	8.4	7.2	5.6	6.8	6	4.4	5.2	260
265	8.7	9.1	8.3	7.9	7.6	6.5	6.1	8.2	6.9	5.4	6.8	6	4.2	5.1	265
270		8.8	8		7.3	6.1		8	6.7	5.1	6.7	5.9	3.9	5.1	270
275		8.4	7.7		7	4.8		7.7	6.5	4.8	6.7	5.7	3.7	5	275
280		8	7.5		6.5	3.6		7.4	6.3		6.7	5.5		5	280
285			7.2		6.2			7.2	6.1		6.6	5.3		5	285
290			7					6.9	5.8		6.4	5.1		4.9	290
295			6.7					6.5	5.6		6.2	4.9		4.9	295
300			6.4						5.4		5.9	4.7		4.9	300
305									5.2			4.5			305
310									5						310


* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_65201_00_000

J

Lifting capacities Forces de levage

TYVEN




	115 + 23 ft*			132 + 23 ft*			149 + 23 ft*			165 + 23 ft*			182 + 23 ft*		
	256 ft			256 ft			256 ft			256 ft			256 ft		
	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	68°	82°	75°	
105	10.7														105
110	10.7														110
115	10.8			10			8.1								115
120	10.9			10.1			8.4			6.4					120
125	10.9			10.1			8.5			6.7			3		125
130	10.9			10.2			8.7			6.9			3.4		130
135	10.8			10.2			8.8			7.2			3.8		135
140	10.7			10.2			8.9			7.4			4.3		140
145	10.7			10.2			8.9			7.5			4.7		145
150	10.6			10.2			9			7.6			5.2		150
155	10.6	10		10.1			9			7.6			5.5		155
160	10.5	10.1		10.1	9.5		9			7.7			5.7		160
165	10.4	10.3		10	9.7		9	8.9		7.7			5.8		165
170	10.4	10.3		9.9	9.8		8.9	9.1		7.7			5.9		170
175	10.3	10.4		9.8	10		8.8	9.2		7.7	8		5.9	6.3	175
180	10.3	10.5		9.8	10.1		8.7	9.2		7.7	7.9		5.9	6.3	180
185	10.2	10.5		9.7	10.1		8.6	9.2		7.6	7.9		5.9	6.2	185
190	10.1	10.5		9.6	10.2		8.6	9.2		7.6	7.8		5.9	6.1	190
195	10	10.5		9.5	10.2		8.4	9.1		7.6	7.7		5.9	6.1	195
200	9.9	10.4	8.7	9.4	10.2		8.3	9.1		7.5	7.6		5.9	6	200
205	9.9	10.4	8.9	9.3	10.1		8.2	9		7.4	7.6		5.9	5.9	205
210	9.8	10.3	9	9.2	10.1		8.1	8.9	7.6	7.3	7.5		5.9	5.8	210
215	9.7	10.2	9.2	9.1	10		7.9	8.8	7.7	7.2	7.4		5.9	5.8	215
220	9.6	10.2	9.2	9	9.9		7.8	8.8	7.9	7	7.3	5.2	5.8	5.7	220
225	9.5	10.1	9.3	8.9	9.9		7.6	8.7	7.8	6.9	7.3	5	5.7	5.6	225
230	9.4	10	9.4	8.7	9.8		7.5	8.6	7.4	6.7	7.2	4.7	5.5	5.6	230
235	9.3	9.8	9.4	8.6	9.6		7.3	8.6	7	6.5	7.1	4.4	5.4	5.5	235
240	9.2	9.8	9.4	8.5	9.3		7.1	8.5	6.7	6.4	7	4	5.2	5.4	240
245	9.1	9.8	9.4	8.4	8.9	7.4	6.9	8.5	6.3	6.2	7	3.7	5	5.4	245
250	9	9.8	9.1	8.3	8.6	7.2	6.7	8.4	6	6	6.9	3.5	4.8	5.3	250
255	8.9	9.8	8.8	8.1	8.3	7	6.5	8.4	5.7	5.8	6.9	3.2	4.6	5.2	255
260	8.8	9.5	8.5	8	7.9	6.7	6.3	8.4	5.4	5.6	6.8	2.9	4.4	5.2	260
265	8.7	9.1	8.3	7.9	7.6	6.5	6.1	8.2	5.1	5.4	6.8		4.2	5.1	265
270		8.8	8		7.3	6.1		8	4.8	5.1	6.7		3.9	5.1	270
275		8.4	7.7		7	4.8		7.7	4.5	4.8	6.7		3.7	5	275
280		8	7.5		6.5	3.6		7.4	4.2		6.7			5	280
285			7.2		6.2			7.2	4		6.6			5	285
290			7					6.9	3.7		6.4			4.9	290
295			6.7					6.5	3.5		6.1			4.7	295
300			6.4						3.2		5.8			4.4	300
305									3						305
310									2.8						310

* adapter 11.5 ft + telescopic boom extension 11.5 ft - pièce d'adaptateur 11.5 ft + rallonge de flèche télescopique 11.5 ft

t_180_65205_00_000

J



Angle of the Y-suspension between 50° and 55° depending on the extension condition of the individual telescopic sections.
Angle du haubanage Y entre 50° et 55°, en fonction de l'état de sortie des différents éléments télescopiques.

Crane carrier

Frame	Self-manufactured, torsion-resistant box-type design of high-tensile fine grained structural steel.
Outriggers	4-point supporting system, hydraulically telescopic into horizontal and vertical direction. Operation with remote control, automatic support leveling, electronic inclination display
Engine	8-cylinder Diesel, make Liebherr, watercooled, output 450 kW (612 h.p.), max. torque 2106 lbs-ft. Exhaust emissions acc. to 97/68/EG and EPA/CARB. Fuel reservoir: 127 gallons.
Transmission	Automatic transmission system with torque converter and intarder, make ZF, type TC-TRONIC with 12 forward speeds and 2 reverse speeds, transfer case with transfer differential.
Axles	Low maintenance carrier axles, all 6 axles steered. Axle 1, 3 and 5 are equipped with planetary gears, all driven axles with transverse differential locks, axle 3 with longitudinal differential lock.
Cardan shaft	All cardan shafts with 70° diagonal toothing and maintenance free.
Suspension	All axles are hydro-pneumatically suspended with automatic leveling. Suspension hydraulically lockable.
Tyre equipment	12 tyres, all axles equipped with single tyres. Size of tyres: 445/95 R 25 (16.00 R 25).
Steering	2-circuit system with hydraulic servo steering. Active speed depending rear axle steering, special steering programs for various driving situations.
Brakes	Service brake: all-wheel servo-air brake, all axles are equipped with disc brakes, dual circuit. Additional brakes: exhaust flap brake, Telma Eddy current brake (optional), intarder in gearbox. Hand brake: Spring-loaded, acting on all wheels of axles 2 to 6.
Driving cab	Spacious and comfortable sheet steel cab mounted on rubber shock absorbers, safety glass windows.
Electrical system	Modern data bus technique, 24 Volt DC, 2 batteries of 170 Ah each.

Crane superstructure

Frame	Liebherr-manufactured, torsionally rigid steel construction made from high-tensile fine-grain steel. Triple-roller slewing rim.
Crane engine	4-cylinder Diesel, make Liebherr, watercooled, output 180 kW (245 h.p.), max. torque 845 lbs-ft. Exhaust emissions acc. to 97/68/EG and EPA/CARB. Fuel reservoir: 106 gallons.
Crane drive	Diesel-hydraulic, with 5 axial piston variable displacement pumps, with servo-control and capacity control.
Crane control	Two self-centering control levers (joy-sticks). Pedal switches for telescoping. Infinitely variable crane motions through displacement control of the hydraulic pumps. Additional working speed control by variation of the Diesel engine speed.
Hoist gear	Axial piston variable displacement motor, hoist drum with integrated planetary gear and spring-loaded static brake.
Luffing gear	1 differential hydraulic ram with nonreturn valve.
Slewing gear	Axial piston fixed displacement motor, planetary gear, spring-loaded static brake.
Crane cab	Large screen area, compound glass, comfort furnishing, cabin tilttable 20° to rear.
Safety devices	LICCON2 safe load indicator, test system, hoist limit switches, safety valves against rupture of pipes and hoses.
Counterweight	220500 lbs
Telescopic boom	1 base section and 5 telescopic sections. All telescopic sections extendable individually by means of the rapid-cycle telescoping system TELEMATIK. Boom length 49 ft – 230 ft.
Electric system	Modern data bus technique, 24 Volt DC, 2 batteries of 170 Ah each.

Additional equipment

Guying system for telescopic boom Y	Consisting of guying frames with stay ropes, tilttable hydraulically into transport position Self assembly.
Additional counterweight	4 additional counterweight slabs of 22050 lbs each for a total counterweight of 308600 lbs.
Lattice jibs	Fixed lattice jib 20 ft to 138 ft long, installation at 0°, 20°, 40° or 60°, luffing lattice jib 39 ft to 256 ft long.
2nd hoist gear	For 2-hook operation or for operating the luffing lattice jib.
Tyre equipment	12 tyres, size 525/80 R 25 (20.5 R 25).
Drive 12 x 8	The 4th axle is driven additionally.

Other items of equipment available on request.

Equipment Équipement

Châssis porteur

Châssis	Châssis résistant à la torsion de fabrication Liebherr, en acier à grains fins très résistant.
Stabilisateurs	Dispositif de calage horizontal et vertical en 4 points, entièrement déployable hydrauliquement. Utilisation avec commande à distance, mise à niveau automatique du calage, inclinomètre électronique.
Moteur	Moteur diesel, 8 cylindres, fabriqué par Liebherr, à refroidissement par eau, de 450 kW (612 ch), couple max. 2106 lbs-ft. Emissions des gaz d'échappement conformes aux directives 97/68/EG et EPA/CARB. Capacité du réservoir à carburant: 127 gallons.
Boîte de vitesse	Boîte automatique avec convertisseur de couple et ralentisseur, marque ZF, type TC-TRONIC avec 12 marches AV et 2 marches AR, boîte de transfert avec différentiel répartiteur.
Essieux	Essieux nécessitant peu d'entretien, les 6 essieux sont directeurs. Les essieux 1, 3 et 5 sont des essieux planétaires, tous les essieux moteurs avec différentiel transversal et l'essieu 3 avec différentiel longitudinal.
Arbres articulés	Tous les flasques de croisillons avec denture en croix 70° et sans entretien.
Suspension	Tous les essieux sont à suspension hydro-pneumatique avec mise à niveau automatique. Suspension blocable hydrauliquement.
Pneumatiques	12 roues à monte simple. Taille: 445/95 R 25 (16.00 R 25).
Direction	2 circuits avec direction assistée hydraulique. Direction active des essieux arrière et dépendante de la vitesse, programmes de direction spéciaux pour les différents modes de déplacement.
Freins	Freins de service: servofrein à air comprimé, tous les essieux sont munis de freins à disque, à 2 circuits. Freins auxiliaire : par clapet sur échappement, frein Telma (option), ralentisseur monté sur boîte de vitesse. Frein de secours et frein à main: par cylindres à ressorts sur les essieux 2 à 6.
Cabine	Cabine spacieuse, en tôle d'acier, équipement «grand confort», suspendue sur silent blocs, vitrage de sécurité.
Installation électrique	Technique moderne de transmission de données par BUS de données, courant continu 24 Volts, 2 batteries de 170 Ah chacune.

Partie tournante

Châssis	Fabrication Liebherr, construction soudée indéformable, en acier à grain fin haute résistance. Couronne d'orientation à triple rangée de rouleaux.
----------------	--

Moteur	Moteur diesel Liebherr, 4 cylindres, à refroidissement par eau, de 180 kW (245 ch), couple max. 845 lbs-ft. Emissions des gaz d'échappement conformes aux directives 97/68/EG et EPA/CARB. Capacité du réservoir à carburant: 106 gallons.
Entraînement	Diesel hydraulique à 5 pompes à débit variable servo commandées à régulation de puissance.
Commande	2 leviers à 4 directions avec rappel automatique au point mort. Commande des mouvements progressive en continu par variation de l'inclinaison des pompes et augmentation du régime moteur.
Treuil	Moteur hydraulique à cylindrée variable, treuil avec réducteur planétaire à frein d'arrêt à lamelles intégrées.
Relevage de flèche	1 vérin hydraulique différentiel avec clapet anti-retour de sécurité.
Orientation	Moteur à cylindrée constante à pistons axiaux, engrenage planétaire, frein d'arrêt commandé par ressort.
Cabine de grue	Large champ de vision, vitrage de sécurité, équipement pour un confort idéal, cabine inclinable de 20° vers l'arrière.
Sécurités	Contrôleur de charge LICCON2, système test, fin de course crochet haut, clapets de sécurité en cas de ruptures de flexibles.
Contrepoids	220500 lbs
Flèche télescopique	Un élément de base et de 5 télescopes. Chaque partie peut être télescopée individuellement à l'aide du système de télescopage séquentiel rapide TELEMATIK. Longueur de flèche: 49 ft – 230 ft.
Circuit électrique	Technique moderne de transmission de données par BUS de données. Courant continu 24 Volts, 2 batteries de 170 Ah chacune.

Équipement supplémentaire

Haubanage de flèche Y	Composé du chevalet d'haubanage avec haubanage du câble, rabattable hydrauliquement en position de transport. Montage autonome.
Contrepoids complémentaire	4 blocs latéraux de suspension de 22050 lbs pour un contrepoids total de 308600 lbs.
Fléchettes	Fléchette fixe de 20 ft à 138 ft; montable à 0°, 20°, 40° ou 60° fléchette à volée variable de 39 ft à 256 ft.
Deuxième treuil	Pour le travail avec 2 crochets ou le relevage de la fléchette à volée variable.
Pneumatiques	12 pneus. Taille 525/80 R 25 (20.5 R 25).
Entraînement 12 x 8	Le 4ème essieu est également entraîné.

Autres équipements supplémentaires sur demande.

K

Description of symbols Explication des symboles

General symbols Symboles généraux

	Page Page		Standard Norme
	Outriggers Calage		Driving speed Vitesse de translation
	Axle Essieu		Transmission Boîte de vitesse
	Radius Portée		Gear Vitesse
	Boom length Longueur de la flèche		Hookblock / Capacity Moufle à crochet / Capacité de charge
	Boom position Position de la flèche		Hoist gear Treuil de levage
	Counterweight Contrepoids		Crane carrier Châssis porteur
	Tyres Pneumatiques		Crane superstructure Partie tournante de la grue
	Slewing gear / Working area Mécanisme d'orientation / Plage de travail		Gradability Aptitude à gravir les pentes

Crane specific symbols Symboles spécifiques à la grue

	Telescopic boom Flèche télescopique		Telescopic boom extension Rallonge flèche télescopique
	Guying system for telescopic boom Y Haubanage de flèche Y		Fixed lattice jib Fléchette treillis fixe
	Eccentric Axe excentrique		Luffing fly jib Fléchette treillis à volée variable

L

Remarks referring to load charts

1. The lifting capacities do not exceed 85 % of the tipping load according to ASME B 30.5.
The crane's structural steelwork is in accordance with EN 13000 and ASME B 30.5.
2. For the calculation of the load charts at least a wind speed of 23 ft/s (7 m/s, 15.7 mph) and regarding the load a sail area of 1 m² per ton load and a wind resistance coefficient of 1.2 on the load have been taken into account. For lifting of loads with large sail areas and/or high wind resistance coefficients the maximum wind speed as stated in the load charts has to be reduced.
3. Lifting capacities are given in kips.
4. The weight of the hook blocks and hooks is part of the load and therefore it must be deducted from the lifting capacities.
5. Working radii are measured from the slewing centre.
6. The lifting capacities given for the telescopic boom apply if the folding jib is removed.
7. Subject to modification of lifting capacities.
8. Lifting capacities above 298600 lbs / 410000 lbs only with additional pulley block/special equipment.
9. The data of this brochure serves only for general information. All information is provided without warranty. Instructions for the correct commissioning of the crane please take from the operation manual and the load chart book.

Remarques relatives aux tableaux des charges

1. La capacité de charge ne doit pas dépasser 85 % de la charge de basculement conformément à ASME B 30.5.
La structure métallique de la grue est conforme à EN 13000 et ASME B 30.5.
2. Une vitesse de vent de 23 ft/s (7 m/s, 15.7 mph) minimum, une surface de prise au vent de 1 m² par tonne ainsi qu'un coefficient de résistance au vent de la charge 1,2 sont pris en compte pour le calcul des tableaux de charge. Lorsque des charges ayant une surface de prise au vent et/ou un coefficient de résistance au vent plus élevé(e)(s) sont levées, la vitesse de vent maximale indiquée dans les tableaux de charge doit être réduite.
3. Les charges sont indiquées en kips.
4. Le poids du crochet de levage resp. de la moufle à crochet est une partie de la charge et doit donc être déduit de la capacité de charge.
5. Les portées sont calculées à partir de l'axe de rotation.
6. Les charges indiquées pour la flèche télescopique sont valables lorsque la fléchette pliante est démontée.
7. Charges données sous réserve de modification.
8. Les charges supérieures à 298600 lbs / 410000 lbs seulement avec moufle additionnel/équipement supplémentaire.
9. Les données de cette brochure sont données à titre informatif. Ces renseignements sont sans garantie. Les consignes relatives à la bonne mise en service de la grue sont disponibles dans le manuel d'utilisation et le manuel de tableaux de charge.

Subject to modification / Sous réserve de modifications

Printed in Germany (1)

TD 180.03.US09.2014

Liebherr-Werk Ehingen GmbH

Postfach 1361, 89582 Ehingen, Germany

☎ +49 73 91 5 02-0, Fax +49 73 91 5 02-33 99

www.liebherr.com, E-mail: info.lwe@liebherr.com

www.facebook.com/LiebherrConstruction